

SHEET 1 OF 1

▲ SWITCH FUNCTION		
POS. 1	POS. 2	POS. 3
		
OFF	N/A	ON
OPEN	N/A	2-1, 5-4




RECOMMENDED PANEL MOUNTING


PANEL THICKNESS	X
1.2-1.8	29.9/30.0
1.8-2.4	30.3/30.4
2.4-3.0	30.7/30.8



CIRCUIT: DPST
FUNCTIONS







NOTES:
1. ALL DIMENSIONS IN mm [INCH]
2. GENERAL TOLERANCE: X.X=±0.4
   X.XX=±0.25
3. TERMINAL NUMBERS FOR REF. ONLY
4. RATING: 12VDC 18A
5. MECHANICAL LIFE: 50,000 CYCLES
6. CONTACT RESISTANCE: <30 MILLI-OHMS INITIAL
7. DIELECTRIC STRENGTH: 1000VAC 1MIN
8. ▲ DENOTES CRITICAL PARAMETER.
9. INSULATION RESISTANCE: 500M OHMS AT 500VDC
10. OPERATING TEMP: -20°C to 85°C
▲ 11. LAMP: 12VDC INCANDESCENT
12. RATING: IP66
13. 2002/95/EC (ROHS) COMPLIANT

REV	PCR NO	DESCRIPTION	DATE	BY
B	22310	UPDATED SWITCH RATING	5/20/16	MJR
A	22294	NEW RELEASE	5/5/16	MJR

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

E•SWITCH®

TITLE RBW2ABLKRILFF3

SCALE	DATE	DR	DWG	REV
1:1	5/5/2016	MJR	Y100015	B