

**LMB-20C Series, 20Watt**
**FEATURES:**

- ✓ Constant current output
- ✓ Input voltage range 200-240Vac
- ✓ Short circuit, overload over temperature protections
- ✓ Designed to worldwide safety standards for lighting
- ✓ Cooling by free air convection
- ✓ 3 years warranty



Model	Input voltage (Vac)	Output current (mA)	Output voltage (Vdc)		Output power (W)
			Min.	Max.	
LMB20-C350		350	30	57	20
LMB20-C500	200-240	500	24	40	20
LMB20-C700		700	17	29	20

**ELECTRICAL**

Input							
Parameters	Symbols	Test Conditions / Comment	Min.	Typ.	Max.	Units	
Input voltage	$V_{in}$	---	180	--	264	Vac	
Input frequency	$f_{line}$	---	47	--	63	Hz	
Input current	$I_{in}$	Full load, $V_{in} = 230\text{ Vac}$	--	--	0.3	A	
Inrush current	$I_{inrush}$	Cold start, $V_{in} = 230\text{ Vac}$	--	--	50	A	
Power factor	PF	70%~100% load, $V_{in} = 220\text{ Vac}$	0.5	--	--	PF	
Efficiency	$\eta$	Full voltage, full load	--	83	84	%	
Output							
Output current	$I_{out}$	LMB20-C350 LMB20-C500 LMB20-C700	315 450 630	350 500 700	385 550 770	mA	
Output voltage	$V_{out}$	LMB20-C350 LMB20-C500 LMB20-C700	30 24 17	--	57 40 29	V	

**LMB-20C Series, 20Watt**
**ELECTRICAL**

Output						
Parameters	Symbols	Test Conditions / Comment	Min.	Typ.	Max.	Units
Line regulation	I <sub>out-line</sub>	V <sub>in</sub> from 200Vac to 240Vac	--	--	1	%
Load regulation	I <sub>out-load</sub>	V <sub>out</sub> from min. To max.	--	--	5	%
Turn on delay time	T <sub>on_delay</sub>	Cold start, power on	--	--	2	s
Ripple	--	--	300	--	500	mV

**Protection**

Overload	Hiccup mode, it will recover automatically after fault conditions remove
Short circuit	Hiccup mode, it will recover automatically after fault conditions remove
Over temperature	Protection type: shut down O/P voltage recovers automatically after temperature goes down

**Environment**

Storage	T <sub>storage</sub>	Humidity: 5% RH to 95% RH	-40	--	+80	°C
Ambient operating temperature	T <sub>a</sub>	Startup at rated voltage	-20	--	+45	°C
Maximum case temperature	T <sub>c</sub>	Hot-spot on case	--	--	+80	°C
Operating relative humidity	H <sub>a</sub>	Non condensing	10	--	95	%
MTBF	T <sub>MTBF</sub>	Full load, 220Vac input, 25°C ambient temperature	--	--	30	kHrs

Dimension(LxWxH) 148x45.8x22.5mm

**Safety / EMC**

Safety standards	IEC61347-1	IEC61347-2-13
EMI	IEC55015	
EMS IMMUNITY	IEC61547	
THD	IEC61000-3-2	

**Notes:** Unless otherwise specified, all the above parameters are measured at ambient temperature of 25°C and Vin = 200Vac to 240Vac.

**LMB-20C Series, 20Watt****MECHANICAL**