



Specifications:

规格:

Voltage rating:600V AC/DC

额定电压: 600V AC/DC

Current rating:9A AC/DC

额定电流: 9A AC/DC

Withstanding voltage:1500V AC/minute

耐受电压: 1500V AC/分钟

Temperature range:-25°C+85°C

温度范围: -25°C+85°C

Insulation resistance:≥1000MΩ

绝缘电阻: ≥1000MΩ

Contact resistance:≤10mΩ

接触电阻: ≤10mΩ

After environmental testing:≤20mΩ

环境测试后: ≤20兆欧

X9357 W V - 2xXX B -N0 SN
① ② ③ ④ ⑤ ⑥ ⑦

- 1.Series No
- 2.Category:W-Wafer
- 3.Welding Board Angle:V-180°
- 4.Row No.-Pin No: 2xXXPin
- 5.Special No: B-Arrange ushering with positioning column
- 6.Material:N0-PA66 94V-0; N2-PA66 94V-2
- 7.Planting Category:V01:Gold Flash ; SN-Plating Tin

Poles	Dimensions(mm)	
	A	B
2x07	25.20	40.00
2x08	33.60	48.40
2x09	46.20	61.00

X9357WV-2xXXB-N0SN	Nylon 66 UL 94V-0	Phorphos Bronza	Tin-Plated	X9357HM-B
X9357WV-2xXXB-N2SN	Nylon 66 UL 94V-2	Phorphos Bronza	Tin-Plated	X9357HM-B
PART NO	Material	Material(Pin)	Finish(Pin)	Suitable XKB Terminal

广东星坤科技股份有限公司

MARK	DESCRIPTION	DATE	REVISED	APPROVED
Δx				
Δx				
Δx				

文件工程章

REVISIONS	DATE	REVISED	APPROVED	DESCRIPTION

DSND	DATE	SCALE: N/A	MODEL TYPE:
DWN	DATE	VIEW:	4.20 mm Crimp Style Connectors
CHKD	DATE	UNIT: mm/in	PART NO.: X9357WV-2xXXB-N0SN
APPD	DATE	SIZE: A4	DWG NO.: X-X9357WV-2xXXB-N0SN
XKB INDUSTRIAL PRECISION CO.,LIMITED			WEIGHT
			SHEET
			REVISION
			1/1
			A0