



VOLTAGE RANGE: 600 --- 1000 V
CURRENT: 1.2 A
DO - 15


Dimensions in millimeters

Features

- ◇ Low cost
- ◇ Diffused junction
- ◇ Low leakage
- ◇ Low forward voltage drop
- ◇ High current capability
- ◇ Easily cleaned with Freon, Alcohol, Isopropanol and similar solvents
- ◇ The plastic material carries U/L recognition 94V-0

Mechanical Data

- ◇ Case: JEDEC DO-15, molded plastic
- ◇ Terminals: Axial lead, solderable per MIL-STD-202, Method 208
- ◇ Polarity: Color band denotes cathode
- ◇ Weight: 0.014 ounces, 0.39 grams
- ◇ Mounting position: Any

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.





Single phase, half wave, 60 Hz, resistive or inductive load. For capacitive load, derate by 20%.

		ZRM11A	ZRM11B	ZRM11C	UNITS
Maximum recurrent peak reverse voltage	V_{RRM}	600	800	1000	V
Maximum RMS voltage	V_{RMS}	420	560	700	V
Maximum DC blocking voltage	V_{DC}	600	800	1000	V
Maximum average forward rectified current 9.5mm lead length, @ $T_A=75^{\circ}\text{C}$	$I_{F(AV)}$	1.2			A
Peak forward surge current 8.3ms single half-sine-wave superimposed on rated load @ $T_J=125^{\circ}\text{C}$	I_{FSM}	100.0			A
Maximum instantaneous forward voltage @ 1.5 A	V_F	0.92			V
Maximum reverse current @ $T_A=25^{\circ}\text{C}$ at rated DC blocking voltage @ $T_A=100^{\circ}\text{C}$	I_R	5.0 50.0			μA
Typical junction capacitance (Note1)	C_J	25			pF
Typical thermal resistance (Note2)	$R_{\theta JA}$	30			$^{\circ}\text{C/W}$
Operating junction temperature range	T_J	-55-----+150			$^{\circ}\text{C}$
Storage temperature range	T_{STG}	-55-----+150			$^{\circ}\text{C}$

NOTE: 1. Measured at 1.0MHz and applied reverse voltage of 4.0V DC.

2. Thermal resistance from junction to ambient.

Ratings AND Characteristic Curves

FIG.1 – FORWARD DERATING CURVE

FIG.2 – PEAK FORWARD SURGE CURRENT

FIG.3 – TYPICAL FORWARD CHARACTERISTIC

FIG.4 – TYPICAL REVERSE CHARACTERISTICS


PACKAGE	SPQ/PCS	CARTON SPQ/PCS	CARTON SIZE/CM	CARTON GW/KG	CARTON NW/KG
DO-15	3000/AMMO	30000	42X28X31	12.00	10.00