

## HWS300-24



 Sales Region
 Worldwide

 Series
 HWS

 Status
 Image: Production

 Feature
 Image: Production

 Option
 Image: Please refer to here.

 Recommended EMC Filter
 Please refer to here.

 Accessories
 Please refer to the catalog



| Electrical Characteristics |               |  |
|----------------------------|---------------|--|
| Input Voltage Range[AC]    | 85 to 265V    |  |
| Input Voltage Range[DC]    | 120 to 330V   |  |
| Efficiency                 | 85% Typ.      |  |
| Rated Output Voltage[DC]   | 24V           |  |
| Output Voltage Range[DC]   | 19.2 to 28.8V |  |
| Maximum Output Current     | 14A           |  |
| Maximum Average Current    |               |  |
| Maximum Peak Current       | 16.5A         |  |
| Maximum Output Power       | 336W          |  |
| Maximum Average Power      |               |  |
| Maximum Peak Power         |               |  |

| Cases Shape & Size |            |  |
|--------------------|------------|--|
| Case'[] shape      | Unit       |  |
| Width(W)           | 61mm Nom.  |  |
| Height(H)          | 82mm Nom.  |  |
| Depth(D)           | 165mm Nom. |  |
| Weight             | 1000g Typ. |  |

| Other                       |                      |  |
|-----------------------------|----------------------|--|
| Operating Temp. Range       | -10 to 70°C          |  |
| Cooling                     | Blower fan cooling   |  |
|                             | UL60950-1            |  |
|                             | CSA C22.2 No.60950-1 |  |
| Safety Standard(Certified)  | CSA C22.2 No.14-M95  |  |
| Salety Standard (Certified) | EN60950-1            |  |
|                             | UL508                |  |
|                             | EN50178              |  |
| Safety Standard(Conformed)  | Den-an               |  |

! Images are for reference only and show exemplary products. ! This PDF document was created based on the data listed on the TDK Corporation website.

! All specifications are subject to change without notice.