


Jun.1.2020 Copyright 2020 HIROSE ELECTRIC CO., LTD. All Rights Reserved.  
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



Detail of part No. label

HRS		検査
品名コード	CL536-0298-5-05	
品名	DF13-2630SCFA(05)	
数量	10000	
仕様		
LOT No.		
継ぎ目		

Section  
Lot No.  
Specification  
Quantity  
Part No.  
Code No.

Inspection

- △ Note 1. Applicable wire : 26 to 30 AWG  
Outer diameter : φ0.56 to 1.0mm
2. 1 reel:10000 contacts.
- ③ Style of reel and box are shown in figure.
- ① 4. A maximum of 5 reels are packed up in one box.
- ① 5. Please be sure to check the form of crimping using a cable when you adjust applicator.
- ① 6. Refer to the technical specification(ATAP-H0373-00)for the packing type.
- ① 7. Refer to the crimping quality standard(ETAD-H0953-00)for the packing type.

NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS
1	Phosphor bronze	Contact area:Gold plating 0.76μm Other:Nickel plating 0.5μm			

UNITS mm	SCALE 20:1	△の数 9	訂正記事 DIS-H-00004839	設計 HT. SATO	検 図 SZ. ONO	年月日 20190513
承認 : KJ. KATAYOSE 20050105		図番 : EDC-071220-05-03				
検 図 : TY. OMA 20050105		製品名 : DF13-2630SCFA(05)				
設計 : TS. KUMAZAWA 20050105		製品コード : CL536-0298-5-05				
製 図 : TS. KUMAZAWA 20050105						