

Is Now Part of



ON Semiconductor®

To learn more about ON Semiconductor, please visit our website at
www.onsemi.com

Please note: As part of the Fairchild Semiconductor integration, some of the Fairchild orderable part numbers will need to change in order to meet ON Semiconductor's system requirements. Since the ON Semiconductor product management systems do not have the ability to manage part nomenclature that utilizes an underscore (_), the underscore (_) in the Fairchild part numbers will be changed to a dash (-). This document may contain device numbers with an underscore (_). Please check the ON Semiconductor website to verify the updated device numbers. The most current and up-to-date ordering information can be found at www.onsemi.com. Please email any questions regarding the system integration to Fairchild_questions@onsemi.com.

ON Semiconductor and the ON Semiconductor logo are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

October 2015

FAN73895
3-Phase Half-Bridge Gate-Drive IC

Features

- Floating Channel for Bootstrap Operation to +600 V
- Typically 350 mA/650 mA Sourcing/Sinking Current-Driving Capability for All Channels
- Extended Allowable Negative V_S Swing to -9.8 V for Signal Propagation at V_{DD}=V_{BS}=15 V
- Output In- Phase with Input Signal
- Over-Current Shutdown Turns Off All Six Drivers
- Matched Propagation Delay for All Channels
- 3.3 V and 5.0 V Input Logic Compatible
- Adjustable Fault-Clear Timing
- Built-in Advanced Input Filter
- Built-in Shoot-Through Prevention Logic
- Built-in Soft Turn-Off Function
- Common-Mode dv/dt Noise-Canceling Circuit
- Built-in UVLO Functions for All Channels

Applications

- 3-Phase Motor Inverter Driver
- Air Conditioner, Washing Machine, Refrigerator, Dish Washer
- Industrial Inverter – Sewing Machine, Power Tool
- General-Purpose Three-Phase Inverter

Description

The FAN73895 is a monolithic three-phase half-bridge gate-drive IC designed for high-voltage, high-speed, driving MOSFETs and IGBTs operating up to +600 V.

Fairchild's high-voltage process and common-mode noise-canceling technique provide stable operation of high-side drivers under high-dv/dt noise circumstances.

An advanced level-shift circuit allows high-side gate driver operation up to V_S = -9.8 V (typical) for V_{BS} =15 V.

The protection functions include under-voltage lockout and inverter over-current trip with an automatic fault-clear function. Over-current protection that terminates all six outputs can be derived from an external current-sense resistor. An open-drain fault signal is provided to indicate that an over-current or under-voltage shutdown has occurred. The UVLO circuits prevent malfunction when V_{DD} and V_{BS} are lower than the threshold voltage.

Output drivers typically source and sink 350 mA and 650 mA, respectively; which is suitable for three-phase half-bridge applications in motor drive systems.



Figure 1. 28-SOIC

Ordering Information

Part Number	Package	Operating Temperature	Packing Method
FAN73895MX(1)	28-Lead, Small Outline Integrated Circuit, (SOIC)	-40 to +125°C	Tape & Reel

Note:

1. These devices passed wave-soldering test by JESD22A-111.

© 2015 Fairchild Semiconductor Corporation

Typical Application Diagram




Figure 2. 3-Phase BLDC Motor Drive Application

Internal Block Diagram




Figure 3. Functional Block Diagram

Pin Configuration




Figure 4. Pin Assignments

Pin Definitions

Pin	Name	Description
1	V_{DD}	Logic and low-side gate driver power supply voltage.
2	HIN1	Logic Input 1 for high-side gate 1 driver.
3	HIN2	Logic Input 2 for high-side gate 2 driver.
4	HIN3	Logic Input 3 for high-side gate 3 driver.
5	LIN1	Logic Input 1 for low-side gate 1 driver.
6	LIN2	Logic Input 2 for low-side gate 2 driver.
7	LIN3	Logic Input 3 for low-side gate 3 driver.
8	$\overline{FO}$	Fault output with open drain (indicates over-current and low-side under-voltage).
9	CS	Analog input for over-current shutdown.
10	EN	Logic input for shutdown functionality.
11	RCIN	An external RC network input used to define the fault-clear delay.
12	V_{SS}	Logic ground.
13	COM	Low-side driver return.
14	LO3	Low-side gate driver 3 output.
15	LO2	Low-side gate driver 2 output.
16	LO1	Low-side gate driver 1 output.
17, 21, 25	NC	No connect.
18	V_{S3}	High-side driver 3 floating supply offset voltage.
19	HO3	High-side driver 3 gate driver output.
20	V_{B3}	High-side driver 3 floating supply.
22	V_{S2}	High-side driver 2 floating supply offset voltage.
23	HO2	High-side driver 2 gate driver output.
24	V_{B2}	High-side driver 2 floating supply.
26	V_{S1}	High-side driver 1 floating supply offset voltage.
27	HO1	High-side driver 1 gate driver output.
28	V_{B1}	High-side driver 1 floating supply.

Absolute Maximum Ratings

Stresses exceeding the Absolute Maximum Ratings may damage the device. The device may not function or be operable above the recommended operating conditions and stressing the parts to these levels is not recommended. In addition, extended exposure to stresses above the recommended operating conditions may affect device reliability. The absolute maximum ratings are stress ratings only. T_A=25°C, unless otherwise specified.

Symbol	Parameter	Min.	Max.	Unit
V_S	High-Side Floating Offset Voltage	$V_{B1,2,3}$-25	$V_{B1,2,3}$+0.3	V
V_B	High-Side Floating Supply Voltage	-0.3	625.0	V
V_{DD}	Low-Side and Logic-Fixed supply voltage	-0.3	25.0	V
V_{HO}	High-Side Floating Output Voltage $V_{HO1,2,3}$	$V_{S1,2,3}$-0.3	$V_{B1,2,3}$+0.3	V
V_{LO}	Low-Side Floating Output Voltage $V_{LO1,2,3}$	-0.3	V_{DD}+0.3	V
V_{IN}	Input Voltage (HINx, LINx, CS, and EN)[2]	-0.3	5.5	V
V_{FO}	Fault Output Voltage ($\overline{FO}$)	-0.3	V_{DD}+0.3	V
dV_S/dt	Allowable Offset Voltage Slew Rate		±50	V/ns
P_D	Power Dissipation[3,4]		1.4	W
θ_{JA}	Thermal Resistance		70	°C/W
T_J	Junction Temperature		150	°C
T_{STG}	Storage Temperature	-55	150	°C

Notes:

2. All input voltage (HINx, LINx, CS, and EN) are referenced to V_{SS} and do not exceed maximum voltage rating.
3. Mounted on 76.2 x 114.3 x 1.6 mm PCB (FR-4 glass epoxy material). *Refer to the following standards:*
   JESD51-2: Integral circuit's thermal test method environmental conditions, natural convection;
   JESD51-3: Low effective thermal conductivity test board for leaded surface-mount packages.
4. Do not exceed maximum power dissipation (P_D) under any circumstances.

Recommended Operating Conditions

The Recommended Operating Conditions table defines the conditions for actual device operation. Recommended operating conditions are specified to ensure optimal performance to the datasheet specifications. Fairchild does not recommend exceeding them or designing to Absolute Maximum Ratings.

Symbol	Parameter	Min.	Max.	Unit
$V_{B1,2,3}$	High-Side Floating Supply Voltage	$V_{S1,2,3}$+10	$V_{S1,2,3}$+20	V
$V_{S1,2,3}$	High-Side Floating Supply Offset Voltage	6-V_{DD}	600	V
V_{DD}	Low-Side and Logic Fixed Supply Voltage	10	20	V
$V_{HO1,2,3}$	High-Side Output Voltage	$V_{S1,2,3}$	$V_{B1,2,3}$	V
$V_{LO1,2,3}$	Low-Side Output Voltage	COM	V_{DD}	V
V_{FO}	Fault Output Voltage ($\overline{FO}$)	V_{SS}	V_{DD}	V
V_{CS}	Current-Sense Pin Input Voltage	V_{SS}	5	V
V_{IN}	Logic Input Voltage (HIN1,2,3 and LIN1,2,3)	V_{SS}	5	V
COM	Low-side driver return	-5	5	V
T_A	Ambient Temperature	-40	+125	°C

© 2015 Fairchild Semiconductor Corporation

Electrical Characteristics

V_{BIAS} (V_{DD}, $V_{BS1,2,3}$) = 15.0 V and T_A = 25°C unless otherwise specified. The V_{IN} and I_{IN} parameters are referenced to V_{SS} and are applicable to all six channels. The V_O and I_O parameters are referenced to $V_{S1,2,3}$ and COM and are applicable to the respective output leads: HO1,2,3 and LO1,2,3. The V_{DDUV} parameters are referenced to V_{SS}. The V_{BSUV} parameters are referenced to $V_{S1,2,3}$.

Symbol	Parameter	Condition	Min.	Typ.	Max.	Unit
Low-Side Power Supply Section						
I_{QDD}	Quiescent V_{DD} Supply Current	$V_{LIN1,2,3}$=0 V or 5 V, EN=0 V		250	400	µA
I_{PDD}	Operating V_{DD} Supply Current	C_{LOAD}=1 nF, $f_{LIN1,2,3}$=20 kHz, rms Value		550	750	µA
V_{DDUV+}	V_{DD} Supply Under-Voltage Positive-Going Threshold	V_{DD}=Sweep	7.5	8.5	9.3	V
V_{DDUV-}	V_{DD} Supply Under-Voltage Negative-Going Threshold	V_{DD}=Sweep	7.0	8.0	8.7	V
V_{DDHYS}	V_{DD} Supply Under-Voltage Lockout Hysteresis	V_{DD}=Sweep		0.5		V
Bootstrapped Power Supply Section						
V_{BSUV+}	V_{BS} Supply Under-Voltage Positive-Going Threshold	$V_{BS1,2,3}$=Sweep	7.5	8.5	9.3	V
V_{BSUV-}	V_{BS} Supply Under-Voltage Negative-Going Threshold	$V_{BS1,2,3}$=Sweep	7.0	8.0	8.7	V
V_{BSHYS}	V_{BS} Supply Under-Voltage Lockout Hysteresis	$V_{BS1,2,3}$=Sweep		0.5		V
I_{LK}	Offset Supply Leakage Current	$V_{B1,2,3}$=$V_{S1,2,3}$=600 V			10	µA
I_{QBS}	Quiescent V_{BS} Supply Current	$V_{HIN1,2,3}$=0 V or 5 V, EN=0 V	10	50	80	µA
I_{PBS}	Operating V_{BS} Supply Current	C_{LOAD}=1 nF, $f_{HIN1,2,3}$=20 kHz, rms Value	200	320	480	µA
Gate Driver Output Section						
V_{OH}	High-Level Output Voltage, V_{BIAS}-V_O	I_O=0 mA (No Load)			100	mV
V_{OL}	Low-Level Output Voltage, V_O	I_O=0 mA (No Load)			100	mV
I_{O+}	Output HIGH Short-Circuit Pulse Current(5)	V_O=15 V, V_{IN}=0 V with PW≤10 µs	250	350		mA
I_{O-}	Output LOW Short-Circuit Pulse Current(5)	V_O=0 V, V_{IN}=5 V with PW≤10 µs	500	650		mA
V_S	Allowable Negative V_S Pin Voltage for HIN Signal Propagation to HO			-9.8	-9.0	V
Logic Input Section						
V_{IH}	Logic "1" Input Voltage HIN1,2,3, LIN1,2,3		2.5			V
V_{IL}	Logic "0" Input Voltage HIN1,2,3, LIN1,2,3				0.8	V
I_{IN+}	Logic Input Bias Current (HO=LO=HIGH)	V_{IN}=5 V	77	100	143	µA
I_{IN-}	Logic Input Bias Current (HO=LO=LOW)	V_{IN}=0 V			2	µA
R_{IN}	Logic Input Pull-Down Resistance		35	50	65	KΩ
Enable Control Section (EN)						
V_{EN+}	Enable Positive-Going Threshold Voltage		2.5			V
V_{EN-}	Enable Negative-Going Threshold Voltage				0.8	V
I_{EN+}	Logic Enable “1” Input Bias Current	V_{EN}=5 V (Pull-Down=150 KΩ)	15	33	50	µA
I_{EN-}	Logic Enable “0” Input Bias Current	V_{EN}=0 V			2	µA
R_{EN}	Logic Input Pull-Down Resistance		100	150	333	KΩ

© 2015 Fairchild Semiconductor Corporation

Electrical Characteristics

V_{BIAS} (V_{DD}, $V_{BS1,2,3}$) = 15.0 V and T_A = 25°C unless otherwise specified. The V_{IN} and I_{IN} parameters are referenced to V_{SS} and are applicable to all six channels. The V_O and I_O parameters are referenced to $V_{S1,2,3}$ and COM and are applicable to the respective output leads: HO1,2,3 and LO1,2,3. The V_{DDUV} parameters are referenced to V_{SS}. The V_{BSUV} parameters are referenced to $V_{S1,2,3}$.

Symbol	Parameter	Condition	Min.	Typ.	Max.	Unit
Over-Current Protection Section						
V_{CSTH+}	Over-Current Detect Positive Threshold		450	500	550	mV
V_{CSTH-}	Over-Current Detect Negative Threshold			440		mV
V_{CSHYS}	Over-Current Detect Hysteresis			60		mV
I_{CSIN}	Short-Circuit Input Current	V_{CSIN}=1 V	5	10	15	μA
I_{SOFT}	Soft Turn-Off Sink Current		25	40	55	mA
Fault Output Section						
$V_{RCINTH+}$	RCIN Positive-Going Threshold Voltage		2.7	3.3	3.9	V
$V_{RCINTH-}$	RCIN Negative-Going Threshold Voltage(5)			2.6		V
$V_{RCINHYS}$	RCIN Hysteresis Voltage(5)			0.7		V
I_{RCIN}	RCIN Internal Current Source	C_{RCIN}=2 nF	3	5	7	μA
V_{FOL}	Fault Output Low Level Voltage	V_{CS}=1 V, I_{FO}=1.5 mA		0.2	0.5	V
R_{DSRCIN}	RCIN On Resistance	I_{RCIN}=1.5 mA	50	75	100	Ω
R_{DSFO}	Fault Output On Resistance	I_{FO}=1.5 mA	90	130	170	Ω

Note:
5. These parameters are guaranteed by design.

Dynamic Electrical Characteristics

T_A=25°C, V_{BIAS} (V_{DD}, $V_{BS1,2,3}$) = 15.0 V, $V_{S1,2,3}$ = COM, C_{RCIN}=2 nF, and C_{Load} = 1000 pF unless otherwise specified.

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
t_{ON}	Turn-On Propagation Delay	$V_{LIN1,2,3}$=$V_{HIN1,2,3}$=5 V, $V_{S1,2,3}$=0 V	350	500	650	ns
t_{OFF}	Turn-Off Propagation Delay	$V_{LIN1,2,3}$=$V_{HIN1,2,3}$=0 V, $V_{S1,2,3}$=0 V	350	500	650	ns
t_R	Turn-On Rise Time	$V_{LIN1,2,3}$=$V_{HIN1,2,3}$=5 V	20	50	100	ns
t_F	Turn-Off Fall Time	$V_{LIN1,2,3}$=$V_{HIN1,2,3}$=0 V	10	30	80	ns
t_{EN}	Enable LOW to Output Shutdown Delay		400	500	600	ns
t_{CSBLT}	CS Pin Leading-Edge Blanking Time		400	650	850	ns
t_{CSFO}	Time from CS Triggering to $\overline{FO}$	From V_{CSC}=1 V to $\overline{FO}$ Turn-Off		850	1300	ns
t_{CSOFF}	Time from CS Triggering to Low-Side Gate Outputs Turn-Off	From V_{CSC}=1 V to Starting Gate Turn-Off		850	1300	ns
t_{FLTIN}	Input Filtering Time(6) (HINx, LINx, EN)		170	250	330	ns
t_{FLTCLR}	Fault-Clear Time			1.30	2.35	ms
DT	Dead Time		230	320	400	ns
MDT	Dead-Time Matching (All Six Channels)(7)				50	ns
MT	Delay Matching (All Six Channels)(8)				50	ns
PM	Output Pulse-Width Matching(9)	PW_{IN} > 1 μs		50	100	ns

Notes:
6. The minimum width of the input pulse should exceed 500 ns to ensure the filtering time of the input filter is exceeded.
7. MDT is defined as | DT1-DT2 | referenced to Figure 38.
8. MT is defined as an absolute value of matching delay time between High-side and Low-side.
9. PM is defined as an absolute value of matching pulse-width between Input and Output.

© 2015 Fairchild Semiconductor Corporation

Typical Characteristics




Figure 5. Turn-On Propagation Delay vs. Temperature




Figure 6. Turn-Off Propagation Delay vs. Temperature




Figure 7. Turn-On Rise Time vs. Temperature




Figure 8. Turn-Off Fall Time vs. Temperature




Figure 9. Enable LOW to Output Shutdown Delay vs. Temperature




Figure 10. Fault-Clear Time vs. Temperature

© 2015 Fairchild Semiconductor Corporation

Typical Characteristics (Continued)




Figure 11. Dead Time vs. Temperature




Figure 12. Dead-Time Matching vs. Temperature




Figure 13. Delay Matching vs. Temperature




Figure 14. Allowable Negative V_S Voltage vs. Temperature




Figure 15. Quiescent V_{DD} Supply Current vs. Temperature




Figure 16. Quiescent V_{BS} Supply Current vs. Temperature

Typical Characteristics (Continued)




Figure 17. Operating V_{DD} Supply Current vs. Temperature




Figure 18. Operating V_{BS} Supply Current vs. Temperature




Figure 19. V_{DD} UVLO+ vs. Temperature




Figure 20. V_{DD} UVLO- vs. Temperature




Figure 21. V_{BS} UVLO+ vs. Temperature




Figure 22. V_{BS} UVLO- vs. Temperature

Typical Characteristics (Continued)




Figure 23. High-Level Output Voltage vs. Temperature




Figure 24. Low-Level Output Voltage vs. Temperature




Figure 25. Logic HIGH Input Voltage vs. Temperature




Figure 26. Logic LOW Input Voltage vs. Temperature




Figure 27. Logic Input HIGH Bias Current vs. Temperature




Figure 28. Logic Input LOW Bias Current vs. Temperature

© 2015 Fairchild Semiconductor Corporation

Typical Characteristics (Continued)




Figure 29. Input Pull-Down Resistance vs. Supply Voltage




Figure 30. Enable Pin Pull-Down Resistance vs. Supply Voltage




Figure 31. Quiescent V_{DD} Supply Current vs. Supply Voltage




Figure 32. Quiescent V_{BS} Supply Current vs. Supply Voltage




Figure 33. Operating V_{DD} Supply Current vs. Supply Voltage




Figure 34. Operating V_{BS} Supply Current vs. Supply Voltage

Switching Time Definitions




Figure 35. Switching Time Waveform Definitions




Figure 36. Input / Output Timing Diagram




Figure 37. Detailed View of B and C Intervals During Over-Current Protection

Applications Information

1. Dead Time

Dead time is automatically inserted whenever the dead time of the external two input signals (between HINx and LINx signals) is shorter than internal fixed dead times (DT1 and DT2). Otherwise, external dead times larger than internal dead times are not modified by the gate driver and internal dead-time waveform definition is shown in Figure 38.




Figure 38. Internal Dead-Time Definitions

2. Protection Function

2.1 Fault Out ($\overline{FO}$) and Under-Voltage Lockout

The high- and low-side drivers include under-voltage lockout (UVLO) protection circuitry that monitors the supply voltage for V_{DD} and V_{BS} independently. It can be designed to prevent malfunction when V_{DD} and V_{BS} are lower than the specified threshold voltage. The UVLO hysteresis prevents chattering during power-supply transitions. Moreover, the fault signal (power supply voltage $\overline{FO}$) goes to LOW state to operate reliably during power-on events when the power supply (V_{DD}) is below the under-voltage lockout high threshold voltage for the circuit (during t_1 ~ t_2). The UVLO circuit is not otherwise activated; shown Figure 39. If VDD is lower than 3.5 V, the fault signal cannot be driven to LOW state because VDD is not enough to drive internal circuit.




Figure 39. Waveforms for Under-Voltage Lockout

2.2 Shoot-Through Protection

The shoot-through protection circuitry prevents both high- and low-side switches from conducting at the same time, as shown Figure 40.





Figure 40. Shoot-Through Protection

An interlock function is a device used to prevent both high- and low-side switches from conducting at the same time as shown Figure 41. In most applications an interlock is used to help prevent a device from harming its operator or damaging itself by when two input signals of a same leg are activated simultaneously, only one output is activated.



S1 : High-side first → First input output mode
S2 : Low-side noise → No LOx output mode
S3 : High-side noise → No HOx output mode
S4 : Low-side first → First input output mode
S5 : In-phase mode → No HOx output

Figure 41. Interlock Function

2.3 Enable Input

When the EN pin is in HIGH state, the gate driver operates normally. When a condition occurs that should shut down the gate driver, the EN pin should be LOW. The enable circuitry has an input filter; the minimum input duration is specified by t_{FLTIN} (typically 250 ns).




Figure 42. Output Enable Timing Waveform

2.4 Fault-Out ($\overline{FO}$) and Over-Current Protection

FAN73895 provides an integrated fault output ($\overline{FO}$) and an adjustable fault-clear timer (t_{FLTCLR}). There are two situations that cause the gate driver to report a fault via the $\overline{FO}$ pin. The first is an under-voltage condition of low-side gate driver supply voltage (V_{DD}) and the second is when the current-sense pin ($\overline{CS}$) recognizes a fault. If a fault condition occurs, the $\overline{FO}$ pin is internally pulled to COM, the fault-clear timer is activated, and all outputs (HO1, 2, 3 and LO1, 2, 3) of the gate driver are turned off. The fault output stays LOW until the fault condition has been removed and the fault-clear timer expires. Once the fault-clear timer expires, the voltage on the $\overline{FO}$ pin returns to pull-up voltage.

The fault-clear time (t_{FLTCLR}) is determined by an internal current source (I_{RCIN}=5 μA) and an external C_{RCIN} at the RCIN pin, as shown as:

$$t_{FLTCLR} = \frac{C_{RCIN} \times V_{RCIN,TH}}{I_{RCIN}} [s] \quad (1)$$

The R_{DSRCIN} of the MOSFET is a characteristic discharge curve with respect to the external capacitor C_{RCIN}. The time constant is defined by the external capacitor C_{RCIN} and the R_{DSRCIN} of the MOSFET.

The output of current-sense comparator (CS_COMP) passes a noise filter, which inhibits an over-current shutdown caused by parasitic voltage spikes of V_{CS}.

This corresponds to a voltage level at the comparator of V_{CSTH+} - V_{CSHYS}= 500 mV - 60 mV =440 mV, where V_{CSHYS}=60 mV is the hysteresis of the current comparator (CS_COMP), as shown in Figure 43.




Figure 43. Over-Current Protection

Figure 44 shows the waveform definitions of RCIN, $\overline{FO}$, and the low-side driver; which uses a soft turn-off method when an under-voltage condition of the low-side gate driver supply voltage (V_{DD}) or the current-sense pin ($\overline{CS}$) recognizes a fault. If a fault condition occurs, the $\overline{FO}$ Pin is internally pulled to COM and all outputs (HO1, 2, 3 and LO1, 2, 3) of the gate driver are turned off. Low-side outputs decline linearly by the internal sink current source (I_{SOFT}=40mA) for soft turn-off, as shown in Figure 44.




Figure 44. R_{CIN} and Fault-Clear Waveform Definition

3. Noise Filter

3.1 Input Noise Filter

Figure 45 shows the input noise filter method, which has symmetry duration between the input signal (t_{INPUT}) and the output signal (t_{OUTPUT}) and helps to reject noise spikes and short pulses. This input filter is applied to the HINx, LINx, and EN inputs. The upper pair of waveforms (Example A) shows input signal duration (t_{INPUT}) much longer than input filter time (t_{FLTIN}); it is approximately the same duration between the input signal time (t_{INPUT}) and the output signal time (t_{OUTPUT}). The lower pair of waveforms (Example B) shows an input signal time (t_{INPUT}) slightly longer than input filter time (t_{FLTIN}); it is approximately the same duration between input signal time (t_{INPUT}) and the output signal time (t_{OUTPUT}).

© 2015 Fairchild Semiconductor Corporation




Figure 45. Input Noise Filter Definition

3.2. Short-Pulsed Input Noise Rejection Method

The input filter circuitry provides protection against short-pulsed input signals (HINx, LINx, and EN) on the input signal lines by applied noise signal.

If the input signal duration is less than input filter time (t_{FLTIN}), the output does not change states.

Example A and B of the Figure 46 show the input and output waveforms with short-pulsed noise spikes with a duration less than input filter time; the output does not change states.




Figure 46. Noise Rejecting Input Filter Definition

Figure 47 shows the characteristics of the input filters while receiving narrow ON and OFF pulses. If input signal pulse duration, PW_{IN}, is less than input filter time, t_{FLTIN}; the output pulse, PW_{OUT}, is zero. The input signal is rejected by input filter. Once the input signal pulse duration, PW_{IN}, exceeds input filter time, t_{FLTIN}, the output pulse durations, PW_{OUT}, matches the input pulse durations, PW_{IN}. FAN73895 input filter time, $t_{FLTIN,}$ is about 250 ns for the high- and low-side outputs.







Figure 47. Input Filter Characteristic of Narrow ON





TOP VIEW



RECOMMENDED LAND PATTERN







NOTES:

A. THIS PACKAGE DOES NOT FULLY CONFORM TO JEDEC REGISTRATION, MS-013.


B. DIMENSIONS ARE IN MILLIMETERS.

C. DIMENSIONS AND TOLERANCES PER ASME Y14.5M, 2009.

D. DIMENSIONS DO NOT INCLUDE MOLD FLASH AND BURRS.

E. LAND PATTERN STANDARD : SOIC127P1030X265-28N

F. DRAWING FILENAME: MKT-M28Brev4.



PIN#1 IDENTIFICATION OPTIONS

ON Semiconductor and ON are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA
Phone: 303−675−2175 or 800−344−3860 Toll Free USA/Canada
Fax: 303−675−2176 or 800−344−3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800−282−9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81−3−5817−1050

ON Semiconductor Website: **www.onsemi.com**

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative