Pushing Performance

# Han EMC 64 Hood Top Entry M40




Image is for illustration purposes only. Please refer to product description.

| | |
|---|---|
| Part number | 19 62 064 0443 |
| Specification | Han EMC 64 Hood Top Entry M40 |
| HARTING eCatalogue | https://b2b.harting.com/19620640443 |

## Identification

| | |
|---|---|
| Category | Hoods/Housings |
| Series of hoods/housings | Han® EMC |
| Type of hood/housing | Hood |

## Version

| | |
|---|---|
| Locking type | Screw locking |
| Size | 24 B |
| Version | Top entry |
| Cable entry | 1x M40 |
| Field of application | Hoods/Housings for higher EMC requirements |

## Technical characteristics

| | |
|---|---|
| Limiting temperature | -40 ... +125 °C |
| Degree of protection acc. to IEC 60529 | IP65 |
| Type rating acc. to UL 50 / UL 50E | 4<br>12 |

## Material properties

| | |
|---|---|
| Material (hood/housing) | Aluminium die-cast |
| Surface (hood/housing) | Uncoated |
| Colour (hood/housing) | Unpainted |
| RoHS | compliant |
| ELV status | compliant |


HARTING Electric GmbH & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany
Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com

Pushing Performance

## Material properties

| | |
|---|---|
| China RoHS | e |
| REACH Annex XVII substances | No |
| REACH ANNEX XIV substances | No |
| REACH SVHC substances | No |

## Specifications and approvals

| | |
|---|---|
| Approvals | DNV GL |
| UL / CSA | UL 1977 ECBT2.E235076<br>CSA-C22.2 No. 182.3 ECBT8.E235076 |
| CE | Yes |

## Commercial data

| | |
|---|---|
| Packaging size | 1 |
| Net weight | 379.4 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |
| eCl@ss | 27440202 Shell for industrial connectors |


HARTING Electric GmbH & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany
Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com