

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

LOC  
ALDIST  
2

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
D2		UPDATED VIEW SCALE	23FEB2010	AV	GT
D4		REVISED MARKS ON -5 WAS MARKED AC	17OCT2011	AV	GT
D4		REVISED PER ECR-13-009678	18SEP2013	RS	DD
D5		ECR-16-004670	04APR2016	RS	JL

TYPICAL APPLICATION

HIGH VOLTAGE

KEYING HV-1

KEYING HV-2

KEYING HV-3

LOW VOLTAGE

KEYING LV-1

KEYING LV-2

PRINTED CIRCUIT BOARD LAYOUT  
FOR LOW VOLTAGE VERSIONTOLERANCES UNLESS OTHERWISE SPECIFIED  $\pm 0.05$   
PRINTED CIRCUIT BOARD THICKNESS: 1.6 mm NOMINAL

1) MATERIALS:

CONTACTS: SOLDERING SIDE TIN PLATED Ph. BRONZE  
RECEPTACLE IN SPECIAL ALLOY COPPER TIN PLATED  
HOUSING: PA66 GFF25 UL 94 V0

OBSOLETE.

PRINTED CIRCUIT BOARD LAYOUT  
FOR HIGH VOLTAGE VERSIONTOLERANCES UNLESS OTHERWISE SPECIFIED  $\pm 0.05$   
PRINTED CIRCUIT BOARD THICKNESS: 1.6 mm NOMINAL

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN  
R. FRABONI 15JUN2007CHK  
-APVD  
G. TURCOPRODUCT SPEC  
108-94018APPLICATION SPEC  
114-32102WEIGHT  
-DIMENSIONS:  
mmTOLERANCES UNLESS  
OTHERWISE SPECIFIED:

0 PLC	$\pm 0.5$
1 PLC	$\pm 0.5$
2 PLC	$\pm 0.3$
3 PLC	$\pm 0.3$
4 PLC	$\pm 0.3$
ANGLES	$\pm 0.5^\circ$

MATERIAL  
-FINISH  
-

TE Connectivity

NAME  
7,5 mm PCB CONNECTOR ASSEMBLY  
STRAIGHT FEMALE VERSION

SIZE CAGE CODE DRAWING NO RESTRICTED TO

A300779 C-293308

CUSTOMER DRAWING

SCALE 5:1

SHEET 1 OF 1

REV D5

1470-19 (3/11)

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[293308-6](#)