

This product supports 4K 60Hz 4:4:4 subsampling for HDR televisions. To ensure optimal performance, check the factory default settings on your TV. (1) The frequency (Hz) should be set to 60Hz (2) HDR feature should be enabled (3) HDMI input settings should be set to 2.0 (4) UHD Deep Color should be set to ON.

HDMI over Cat6 Extender Kit with PoC - 4K x 2K @ 60 Hz, 4:4:4:, 125 ft. (38.1 m), TAA

MODEL NUMBER: B127-1A1-HH



Transmitter/receiver kit extends a 4K x 2K HDMI audio/video signal via Cat6 cable to a projector, monitor or HDTV up to 125 ft. away.

Features

HDMI Extender Ideal for Digital Signage or Displaying Video in Schools or Trade Show Booths This complete transmitter and receiver system is recommended for video presentations in conference rooms, schools, trade shows, meeting facilities, houses of worship, retail settings and digital signage applications where the source and display are farther apart than conventional A/V cables allow. The B127-1A1-HH extends 4K video and stereo audio signals from an HDMI source device to an HDMI display up to 125 feet (38.1 meters) away via user-supplied Cat6 cabling.

Transmits Crystal-Clear 4K HDMI Video with Multi-Channel Audio and 4:4:4 Color The B127-1A1-HH supports Ultra HD video resolutions up to 3840 x 2160 (4K x 2K) at 60 Hz with full, rich uncompressed DTS-HD, Dolby TrueHD and 7.1-channel digital audio. Built-in equalization automatically fine-tunes the image quality at the remote display with no time-consuming manual fiddling needed. It's compatible with HDCP 2.2, EDID and HDMI 2.0 standards for carrying HDR (high dynamic range) signals. It also supports 4:4:4 chroma subsampling for top-level PC gaming or using your HDTV as a PC monitor.

Built-In PoC Technology Provides Receiver Power to Avoid Bulky External Power Bricks Built-in Power over Cable (PoC) technology powers the low-profile receiver over Cat6 cable. Green and orange LEDs on both the transmitter and receiver will light up to indicate the system is receiving power and a signal is being transmitted.

Plug-and-Play Operation for Quick Setup and Immediate Use The included transmitter and receiver units work right out of the box with no software required. Mounting hardware is included for installing the units on walls, poles or 19-inch racks. Connect the transmitter to the source and the receiver to the display with user-supplied HDMI cables (such as Tripp Lite's P568- or P569-Series). Then, connect the two units using Cat6 patch cable (such as Tripp Lite N202-Series cable). Connect an optional display to the transmitter's local HDMI output to monitor the image connected to the receiver up to 125 feet away.

TAA-Compliant for GSA Schedule Purchases The B127-1A1-HH is compliant with the Federal Trade Agreements Act (TAA), which makes it eligible for GSA (General Services Administration) Schedule and other federal procurement contracts.

Highlights

- Delivers UHD picture quality at resolutions up to 3840 x 2160 (4K x 2K) @ 60 Hz
- Power over Cable (PoC) technology provides power to the receiver via Cat6 cable
- Transmitter's local HDMI port allows you to see the Ultra HD image being displayed
- Compatible with latest HDMI standards, including 4:4:4 subsampling for HDR televisions
- Plug-and-play operation with no software required for easy, immediate installation

Applications

- Connect a media server, Blu-ray player, cable/satellite box, Roku, gaming system or other home theater component to a large-screen 4K television or projector
- Upgrade the video quality of your trade show presentation or digital signage installation in a commercial or educational setting to 4K x 2K

System Requirements

- Source device with HDMI output (Blu-ray player, cable box, laptop)
- Display device with HDMI input (HDTV, projector, monitor)

Package Includes

- Transmitter unit
- Receiver unit
- External power supply (Input:



100–240V)

- (4) International plug adapters
(North America, Europe, U.K.
and Australia)
- Mounting hardware
- Owner's manual

Specifications

| OVERVIEW | |
|--|---|
| UPC Code | 037332239112 |
| INPUT | |
| Voltage Compatibility (VAC) | 100; 110; 120; 125; 127; 200; 208; 220; 230; 240 |
| External Power Supply Input Specs (V / Hz / A) | 100-240V~50/60Hz, 0.6A |
| External Power Supply Output Specs (V / A) | 24V/1A |
| External Power Supply Cord Length (ft.) | 4.5 |
| External Power Supply Plug(s) | AS/NZS 3112 Australia; BS 1363 UK; CEE 7/16 Schuko; NEMA 1-15P North America |
| External Power Supply Certifications | CCC; CE; FCC; GS; TUV; UL; cUL |
| USER INTERFACE, ALERTS & CONTROLS | |
| LED Indicators | Tx: x1 Green (Power), x2 Orange (Local, Output); Tx RJ45 port: Green (Connected), Orange (Activity) Rx: x1 Green (Power); Rx RJ45 port: Green (Connected), Orange (Activity) |
| PHYSICAL | |
| Color | Black |
| Material of Construction | Metal |
| Rackmountable | Yes |
| Receiver Unit Dimensions (hwd / in.) | 1.06 x 4.53 x 2.46 |
| Receiver Unit Weight (lbs.) | 0.45 |
| Transmitter Unit Dimensions (hwd / in.) | 1.06 x 4.53 x 2.46 |
| Transmitter Unit Weight (lbs.) | 0.45 |
| Unit Packaging Type | Box |
| ENVIRONMENTAL | |



| | |
|--------------------------------------|--|
| Operating Temperature Range | 32 to 104°F (0 to 40°C) |
| Storage Temperature Range | 5 to 122°F (-15 to 50°C) |
| Relative Humidity | 0% to 85% RH, Non-Condensing |
| COMMUNICATIONS | |
| Signal Range (ft.) | 125 |
| Signal Range (m) | 38 |
| CONNECTIONS | |
| Side A - Connector 1 | (2) HDMI (FEMALE) |
| Side A - Connector 2 | RJ45 (FEMALE) |
| Side B - Connector 1 | HDMI (FEMALE) |
| Side B - Connector 2 | RJ45 (FEMALE) |
| FEATURES & SPECIFICATIONS | |
| Max Supported Video Resolution | 4K x 2K (3840 x 2160) @60Hz |
| HDMI Specification | 2.0 |
| HDCP Specification | 2.2 |
| Audio Specification | True uncompressed 7.1 Channel, DTS-HD & Dolby-TrueHD digital audio |
| Driver Required | No |
| Recommended Category Cable | Solid Wire Cat6 Cables (Tripp Lite's N202-Series) |
| Max Supported Color Depth | 24-bit True Color |
| EDID Compatible | Yes |
| Power Over Cable (PoC) Support | Yes |
| Technology | A/V over IP; Cat6; HDMI; HDR |
| Chroma Sub Sampling | 4:4:4 |
| SPECIAL FEATURES | |
| HDR Support | Yes |
| CERTIFICATIONS | |
| Certifications | Tested to CE, FCC, REACH, RoHS |
| WARRANTY | |
| Product Warranty Period (Worldwide) | 1-year limited warranty |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>