T1/CEPT/ISDN PRI INTERFACE TRANSFORMER

Turns Ratio (± 5%)	1:1.15CT & 1CT:1

PARAMETER	MIN.	MAX.	UNITS
OCL (Primary)	1.5		mH
Leakage Inductance		0.6	µH
Capacitance ($C_{W/W}$)		35	pF
Primary DC Resistance		0.7	ohms
Secondary DC Resistance		0.9	ohms
ET Product	10		VµS

Primary Pins 14-12 & 5-7


Flammability: Materials used in the production of these units meet requirements of UL94-VO and IEC 695-2-2 needle flame test.

1500 V_{RMS} Isolation (Hi-Pot)

Parts shipped in anti-static tubes. 33 pieces per tube


Surface mount version of this part available. Part# T-11067

PHYSICAL DIMENSIONS All dimensions in inches (mm):



Unused pins not provided

SCHEMATIC DIAGRAM:



RHOMBUS P/N: **T-10167**	
CUST P/N:	NAME:
DATE: **2/23/98**	SHEET: 1 OF 1

Rhombus Industries Inc.
Transformers & Magnetic Products

15801 Chemical Lane, Huntington Beach, CA 92649
Phone: (714) 898-0960
FAX: (714) 896-0971

www.rhombus-ind.com