杰力科技股份有限公司
Excelliance MOS Corporation

EMB16N06A

N-Channel Logic Level Enhancement Mode Field Effect Transistor

Product Summary:

BV_{DSS}	60V
$R_{DSON\ (MAX.)}$	16mΩ
I_D	42A





UIS, Rg 100% Tested

Pb-Free Lead Plating & Halogen Free

ABSOLUTE MAXIMUM RATINGS (T_A = 25 °C Unless Otherwise Noted)

PARAMETERS/TEST CONDITIONS		SYMBOL	LIMITS	UNIT
Gate-Source Voltage		V_{GS}	±20	V
Continuous Drain Current	T_C = 25 °C	I_D	42	A
	T_C = 100 °C		26	
Pulsed Drain Current[1]		I_{DM}	100	
Avalanche Current		I_{AS}	20	
Avalanche Energy	L = 0.1mH, ID=20A, RG=25Ω	E_{AS}	20	mJ
Repetitive Avalanche Energy[2]	L = 0.05mH	E_{AR}	10	
Power Dissipation	T_C = 25 °C	P_D	50	W
	T_C = 100 °C		20	
Operating Junction & Storage Temperature Range		T_j, T_{stg}	-55 to 150	°C

THERMAL RESISTANCE RATINGS

THERMAL RESISTANCE	SYMBOL	TYPICAL	MAXIMUM	UNIT
Junction-to-Case	$R_{\theta JC}$		2.5	°C / W
Junction-to-Ambient	$R_{\theta JA}$		75	

[1]Pulse width limited by maximum junction temperature.

[2]Duty cycle ≤ 1%

ELECTRICAL CHARACTERISTICS (T_J = 25 °C, Unless Otherwise Noted)

PARAMETER	SYMBOL	TEST CONDITIONS	LIMITS			UNIT
			MIN	TYP	MAX	
STATIC						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	V_{GS} = 0V, I_D = 250μA	60			V
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS} = V_{GS}, I_D = 250μA	1.0	2.0	3.0	
Gate-Body Leakage	I_{GSS}	V_{DS} = 0V, V_{GS} = ±20V			±100	nA
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS} = 48V, V_{GS} = 0V			1	μA
		V_{DS} = 40V, V_{GS} = 0V, T_J = 125 °C			25	
On-State Drain Current[1]	$I_{D(ON)}$	V_{DS} = 5V, V_{GS} = 10V	42			A
Drain-Source On-State Resistance[1]	$R_{DS(ON)}$	V_{GS} = 10V, I_D = 20A		13	16	mΩ
		V_{GS} = 4.5V, I_D = 15A		19	25	
Forward Transconductance[1]	g_{fs}	V_{DS} = 5V, I_D = 20A		25		S
DYNAMIC						
Input Capacitance	C_{iss}	V_{GS} = 0V, V_{DS} = 25V, f = 1MHz		2195		pF
Output Capacitance	C_{oss}			138		
Reverse Transfer Capacitance	C_{rss}			129		
Gate Resistance	R_g	V_{GS} = 15mV, V_{DS} = 0V, f = 1MHz		1.4		Ω
Total Gate Charge[1,2]	Q_g	V_{DS} = 30V, V_{GS} = 10V, I_D = 20A		50		nC
Gate-Source Charge[1,2]	Q_{gs}			8.8		
Gate-Drain Charge[1,2]	Q_{gd}			14.7		
Turn-On Delay Time[1,2]	$t_{d(on)}$	V_{DS} = 30V, I_D = 1A, V_{GS} = 10V, R_{GS} = 6Ω		20		nS
Rise Time[1,2]	t_r			15		
Turn-Off Delay Time[1,2]	$t_{d(off)}$			50		
Fall Time[1,2]	t_f			20		
SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTICS (T_C = 25 °C)						
Continuous Current	I_S				42	A
Pulsed Current[3]	I_{SM}				100	
Forward Voltage[1]	V_{SD}	I_F = I_S, V_{GS} = 0V			1.3	V
Reverse Recovery Time	t_{rr}	I_F = 25A, dI_F/dt = 100A / μS		60		nS
Reverse Recovery Charge	Q_{rr}			42		nC

[1]Pulse test : Pulse Width ≤ 300 μsec, Duty Cycle ≤ 2%.

[2]Independent of operating temperature.

[3]Pulse width limited by maximum junction temperature.

Ordering & Marking Information:

Device Name: EMB16N06A for DPAK (TO-252)



TYPICAL CHARACTERISTICS














Gate Charge Characteristics
I_D = 20A
V_{DS} = 15V
30V
V_{GS} - Gate-Source Voltage(V)
Q_g - Gate Charge(nC)


Capacitance Characteristics
f = 1MHz
V_{GS} = 0 V
Ciss
Coss
Crss
Capacitance(pF)
V_{DS} - Drain-Source Voltage(V)


Maximum Safe Operating Area
RDS(ON) Limited
10 μs
100 μs
1ms
10ms
DC
TC=25°C
RθJC=2.5°C/W
Vgs=10V
Single Pulse
ID, Drain Current(A)
VDS, Drain-Source Voltage(V)


Single Pulse Maximum Power Dissipation
Single Pulse
RθJC = 2.5°C/W
TC = 25°C
Power(W)
Single Pulse Time(sec)


Transient Thermal Response Curve
D=0.5
0.2
0.1
0.05
0.02
0.01
single pulse
※Note :
1. RθJC(t)=2.5°C/W Max.
2. Duty Cycle, D=t1/ t2
3. TJM - TC=PDM*RθJC(t)
PDM
t1
t2
r(t),Normalized Effective Transient Thermal Resistance
t1,Time(sec)

Outline Drawing



Dimension in mm

Dimension	A	A1	B	B1	B2	C	D	D2	D3	E	E2	H	L	L1	L2	L3	P
Min.	2.10	0.95	0.30	0.40	0.60	0.40	5.30	6.70	2.20	6.40	4.80	9.20	0.89	0.90	0.50	0.00	2.10
Max.	2.50	1.30	0.85	0.94	1.00	0.60	6.20	7.30	3.00	6.70	5.45	10.15	1.70	1.65	1.10	0.30	2.50

Footprint