

Product data sheet

Characteristics

H321NRBVW

Safety switch, heavy duty, fusible, 30A, 3 poles, 7.5 hp, 240 VAC/250 VDC, NEMA 3R, bolt-on hub, neutral, viewing window

Product availability : Non-Stock - Not normally stocked in distribution facility



Price* : 593.00 USD



Main

Product	Single Throw Safety Switch
Duty Rating	Heavy duty
Device application	Heavy application
Disconnect Type	Fusible disconnect
Factory Installed Neutral	Neutral (factory installed)
Phase	3 phase
Number of Poles	3
Current Rating	30 A
Voltage Rating	250 V DC 240 V AC
Enclosure Rating	NEMA 3R galvanized steel
Maximum Horse Power Rating	1.5 hp 240 V at AC 50-60 Hz for 1 phase conforming to NEC 240.6 3 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 3 hp 240 V at AC 50-60 Hz for 1 phase conforming to NEC 430.52 7.5 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 5 hp 250 V at DC

Complementary

Mounting Type	Surface
Wiring configuration	4-wire (3PH + G)
Wire Size	AWG 12...AWG 6 aluminium AWG 14...AWG 6 copper
Tightening torque	45 lbf.in (5.08 N.m) 0.02 in ² (13.3 mm ²) (AWG 6) 40 lbf.in (4.52 N.m) 0.01 in ² (8.367 mm ²) (AWG 8) 35 lbf.in (3.95 N.m) 0.00...0.01 in ² (2.06...5.261 mm ²) (AWG 14...AWG 10)
Depth	4.88 in (123.95 mm)

* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Width	6.63 in (168.40 mm)
Height	14.88 in (377.95 mm)
Net Weight	9.55 lb(US) (4.33 kg)

Environment

Certifications	UL listed file E2875
----------------	----------------------

Ordering and shipping details

Category	00009 - H&HU SW,2&3P,N3R,30-200A
Discount Schedule	DE1
GTIN	00785901068082
Nbr. of units in pkg.	1
Package weight(Lbs)	8.8 lb(US) (3.99 kg)
Returnability	No

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------