


Round cylinder ESNU-32-50-P-A

Part number: 196378

FESTO



Data sheet

Feature	Value
Stroke	50 mm
Piston diameter	32 mm
Piston rod thread	M10x1.25
Type code	ESNU
Cushioning	Elastic cushioning rings/pads at both ends
Mounting position	Any
Design	Piston rod Piston Cylinder barrel
Position sensing	For proximity sensor
Symbol	00991729
Operating pressure	1.2 bar ... 10 bar
Mode of operation	Single-acting Pushing
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
Corrosion resistance class (CRC)	2 - Moderate corrosion stress
Ambient temperature	-20 °C ... 80 °C
Spring resetting force with piston rod in retracted position	20 N
Theoretical force at 6 bar, retracting	20 N
Theoretical force at 6 bar, advancing	442.2 N
Moving mass	166 g
Moving mass at 0 mm stroke	121 g
Additional weight per 10 mm stroke	15.5 g
Basic weight with 0 mm stroke	370.5 g
Product weight	448 g
Additional moving mass per 10 mm stroke	9 g
Type of mounting	With accessories
Pneumatic connection	G1/8
Note on materials	RoHS-compliant
Cover material	Wrought aluminum alloy
Seals material	TPE-U(PU) NBR
Piston rod material	High-alloy steel
Material of cylinder barrel	High-alloy stainless steel