



电气特性: Electrical:

1. 额定电流: Current Rating
1.5A/contact terminal
 2. 额定电压: Voltage Rating
30V DC
 3. 接触电阻: Contact Resistance
30 millionms MAX
 4. 耐电压: Dielectric Withstanding Voltage:
500 V AC AT Sea Level
 5. 绝缘电阻: Insulation Resistance:
1000MEGA ohms MIN
- 物理性能: Mechanical:
1. 插拔力: Connector Mate and Umate Force
Mate force: 3.57kgf(MAX)
Umate force: 1.02kgf(MIN)
 2. 端子保持力: Terminal Retention
1.0kgf(MIN)

RECOMMENDED P.C.B. LAYOUT

ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING
③	Base	—	1	PA9T	White/black
②	Terminal	—	4	Phosphor Bronze	Ag Plated
①	Housing	—	1	BRASS	Ni Plated

APPROVALS		DATE	TITLE:	
DRAWN	JIANKUN.LIU	2020.07.01	USB CONNECTOR	
CHECKED			ELECTRONICS CO.,LTD	
APPROVALS			PART NO.	U-A-24DD-W-14
TOLERANCES ARE		30~Ø以上 ±0.30	UNIT: mm	SCALE: 1:1
		10~30 ±0.25		PROJ:
		5~10 ±0.20	DRAWING NO.	SHEET 1 OF 1
		~5 ±0.15		

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			