PASTERNACK®
www.pasternack.com

# 50 dB Fixed Attenuator, SMA Male To SMA Female Rated To 25 Watts Up To 8 GHz



## TECHNICAL DATA SHEET PE7357-50

**50 dB Fixed Attenuator, SMA Male To SMA Female Rated To 25 Watts Up To 8 GHz**

### Configuration

| | |
|---|---|
| Design | Fixed, Bidirectional Attenuator |
| Connector 1 | SMA Male |
| Connector 2 | SMA Female |
| Body Material and Plating | Aluminum Heatsink, Black Anodized |

### Electrical Specifications

| | |
|---|---|
| Frequency Range, GHz | DC to 8 |
| Impedance, Ohms | 50 |
| Attenuation Value, dB | 50 to 50 |
| Maximum Input Power, Watts | 25 |
| Maximum VSWR | 1.6:1 |

**Frequency 1**

| | |
|---|---|
| Range, GHz | DC to 6 |
| Insertion Loss, dB | 50 |
| VSWR | 1.25:1 |
| Attenuation Accuracy, dB | 0.5 |
| Maximum Input Power, Watts | 25 |

**Frequency 2**

| | |
|---|---|
| Range, GHz | 6 to 8 |
| VSWR | 1.45:1 |

### Mechanical Specifications

**Temperature**

| | |
|---|---|
| Operating Range, deg C | -55 to +125 |

**Size**

| | |
|---|---|
| Length, in [mm] | 4.5 [114.3] |
| Width, in [mm] | 2.41 [61.21] |
| Weight, lbs [g] | 0.8 [362.87] |

Click the following link (or enter part number in “SEARCH” on website) to obtain additional part information including price, inventory and certifications: 50 dB Fixed Attenuator, SMA Male To SMA Female Rated To 25 Watts Up To 8 GHz PE7357-50

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623
**Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451
Sales@Pasternack.com • Techsupport@Pasternack.com

ISO 9001 : 2008 Registered

© 2012 Pasternack Enterprises All Rights Reserved

PASTERNACK®
www.pasternack.com

# 50 dB Fixed Attenuator, SMA Male To SMA Female Rated To 25 Watts Up To 8 GHz



## TECHNICAL DATA SHEET PE7357-50

**Connector 1**

| | |
|---|---|
| Type | SMA Male |
| Contact Material and Plating | Beryllium Copper, Gold |
| Contact Plating Specification | Gold |
| Coupling Nut Material and Plating | Stainless Steel, Passivated |
| Coupling Nut Plating Specification | Stainless Steel |
| Hex Size, In. | 11/16 |
| Body Material and Plating | Stainless Steel, Passivated |
| Body Plating Specification | Passivated |

**Connector 2**

| | |
|---|---|
| Type | SMA Female |
| Contact Material and Plating | Beryllium Copper, Gold |
| Outer Conductor Material and Plating | Stainless Steel, Passivated |
| Hex Size, In. | 11/16 |
| Body Material and Plating | Stainless Steel, Passivated |

**Compliance Certifications** (visit www.Pasternack.com for current document)

| | |
|---|---|
| RoHS Compliant | Yes |

**Plotted and Other Data**

| | |
|---|---|
| Notes: | Values at 25 °C, sea level |

URL: http://www.pasternack.com/50db-fixed-sma-male-sma-female-25-watts-attenuator-pe7357-50-p.aspx

50 dB Fixed Attenuator, SMA Male To SMA Female Rated To 25 Watts Up To 8 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623
**Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451
Sales@Pasternack.com • Techsupport@Pasternack.com

ISO 9001 : 2008 Registered


© 2012 Pasternack Enterprises All Rights Reserved


# PE7357-50 CAD Drawing

50 dB Fixed Attenuator, SMA Male To SMA Female Rated To 25 Watts Up To 8 GHz

| Table of Information | |
|---|---|
| Connector Type | DIM "A" (REF.) |
| SMA Male | 0.68 |
| SMA Female | 0.54 |
| TNC Male | 0.98 |
| TNC Female | 0.94 |
| N Female | 0.95 |
| N Male | 0.98 |
| 7/16 Male | 1.12 |
| 7/16 Female | 1.16 |

| Part Number Configuration | | |
|---|---|---|
| xx | Input Connector | Output Connector |
| 55 | SMA Male | 7/16 Female |
| 56 | SMA Male | N Female |
| 57 | SMA Male | SMA Female |
| 58 | SMA Male | TNC Female |
| 59 | SMA Female | 7/16 Female |
| 60 | SMA Female | 7/16 Male |
| 61 | SMA Female | N Female |
| 62 | SMA Female | N Male |
| 63 | SMA Female | SMA Female |
| 64 | SMA Female | TNC Female |
| 65 | SMA Female | TNC Male |
| 66 | N Male | 7/16 Female |
| 67 | N Male | N Female |
| 68 | N Male | TNC Female |
| 69 | N Female | 7/16 Female |
| 70 | N Female | 7/16 Male |
| 71 | N Female | N Female |
| 72 | N Female | TNC Female |
| 73 | N Female | TNC Male |
| 74 | TNC Male | TNC Female |
| 75 | TNC Male | SMA Male |
| 76 | TNC Female | 7/16 Female |
| 77 | TNC Female | 7/16 Male |
| 78 | TNC Female | TNC Female |
| 79 | 7/16 Male | 7/16 Female |
| 80 | 7/16 Female | 7/16 Female |
| -yy | Indicates Attenuation Level | |




NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].

DWG TITLE: PE73xx-yy

CAD FILE 102512 | SCALE N/A | SIZE A | 2233

FSCM NO. 53919


PASTERNACK®
Pasternack Enterprises, Inc.
P.O. Box 16759 | Irvine | CA | 92623
**Phone:** (949) 261-1920 | **Fax:** (949) 261-7451
**Website:** www.pasternack.com | **E-Mail:** sales@pasternack.com


© 2012 Pasternack Enterprises All Rights Reserved