

> Chip LED / LED Lamp Data Sheet

■ HIGH-LUMINOSITY (AlGaInP) LED SERIES

(Ta = 25°C)

Radiation color	Green	Yellow-green	Amber	Sunset orange	Orange	Red	
Series	ZG, JG	ZE, JE	ZV, JV, YV	ZS, JS, YS	ZJ, JJ, YJ	ZR, JR	JU
Dominant emission wavelength (nm)	560	572	588	605	618	630	638
Radiation material	AlGaInP on GaAs						

■ HIGH-LUMINOSITY (InGaN) LED SERIES

(Ta = 25°C)

Radiation color	Blue	Green
Series	BC	GC
Dominant emission wavelength (nm)	470	525
Radiation material	InGaN	

■ WHITE TYPE LED SERIES

(Ta = 25°C)

Radiation color	White	
Series	VA	BW
Color range (x, y)	(0.33, 0.33)	(0.31, 0.31)
Radiation material	InGaN + RGB fluorescent powder	InGaN + Fluorescent powder

■ LED SERIES

(Ta = 25°C)

Radiation color	Green	Yellow-green	Yellow-green (High-luminosity)	Yellow	Sunset orange	Red	Red	Red (High-luminosity)	Red (High-luminosity)	Red
Series	KG, K	EG, E, C*	FG, F	HY, H	HS, S	HD, D	HA, A	TR, T	UR, U	PR, P
Peak emission wavelength (nm)	555	565	565	585	610	635	650	660	660	685
Radiation material	GaP	GaP	GaP	GaAsP on GaP	GaAsP on GaP	GaAsP on GaP	GaAsP on GaP	GaAlAs on GaAs Single hetero	GaAlAs on GaAlAs Double hetero	GaP

* C is the opposite polarity of EG's.

■ HIGH-LUMINOSITY (AlGaInP) LED LAMPS

(If = 20 mA, Ta = 25°C)

Appearance	Radiation shape (mm)	Resin type		High-luminosity												
				JG, ZG (Green)		JE, ZE (Yellow-green)		JV, ZV (Amber)		JS, ZS (Sunset orange)		ZJ, JJ (Orange)		ZR, JR, JU (Red)		
		Colored diffusion	Colored transparency	Colored transparency	Model No.	Luminous intensity (mcd) TYP.	Model No.	Luminous intensity (mcd) TYP.	Model No.	Luminous intensity (mcd) TYP.	Model No.	Luminous intensity (mcd) TYP.	Model No.	Luminous intensity (mcd) TYP.	Model No.	Luminous intensity (mcd) TYP.
Cylinder	ø3			●				GL3ZV402B0SE	400	GL3ZS402B0SE	400	GL3ZJ402B0SE	400	GL3ZR402B0SE	250	
				●	GL3JG402B0SE	85	GL3JE402B0SE	200						GL3JR402B0S3	200	
				●										☆ GL3JU402B0S	300	
				●			GL3ZE802B0S	80	GL3ZV802B0SE	200	GL3ZS802B0SE	210	GL3ZJ802B0SE	230	GL3ZR802B0SE	150
		●					GL3JV404B0SE	280	GL3JS404B0SE	280	GL3JJ404B0SE	200				
		●					GL3JV804B0SE	110	GL3JS804B0SE	120	GL3JJ804B0SE	100				
	ø5			●				GL5ZV152B0SE	2 700	GL5ZS152B0SE	3 000	GL5ZJ152B0SE	3 000	GL5ZR152B0SE	2 000	
				●				GL5ZV302B0SE	800	GL5ZS302B0SE	1 000	GL5ZJ302B0SE	900	GL5ZR302B0SE	600	
				●				GL5JV302B0SE	640	GL5JS302B0SE	680	GL5JJ302B0SE	570			
				●				GL0ZV042B0S	16 800	GL0ZS042B0S	22 800	GL0ZJ042B0S	18 500			
Oval	Long: 5.8 Short: 4.8			●				GL6ZV27	750	GL6ZS27	850	GL6ZJ27	750	GL6ZR27	360	
				●				GL5JV7D2D0SE	210	GL5JS7D2D0SE	230	GL5JJ7D2D0SE	190			

Taped model is also available.

Notice

In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that may occur in equipment using any SHARP devices shown in catalogs, data books, etc.
 Except where specially indicated, models listed on this page comply with the RoHS Directive*. For details, please contact SHARP.
 *RoHS Directive: Prohibits use of lead, cadmium, hexavalent chromium, mercury and specific brominated flame retardants (PBBs and PBCEs), with certain exceptions.
 Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device.

HIGH-LUMINOSITY LED LAMP

LED

☆New product


■ HIGH-LUMINOSITY LED LAMPS

(F = 20 mA, Ta = 25°C)

Appearance	Radiation shape (mm)	Resin type				High-luminosity							
		Colored diffusion	Colored transparency	Colorless transparency	Milky diffusion	BC (Blue)		GC (Green)		TR, T (Red)		UR, U (Red)	
						Model No.	Luminous intensity (mcd) TYP.	Model No.	Luminous intensity (mcd) TYP.	Model No.	Luminous intensity (mcd) TYP.	Model No.	Luminous intensity (mcd) TYP.
Cylinder	φ3	●								GL3TR8	80	GL3UR8	300
				●						GL3TR44	110	GL3UR44	250
			●							GL3TR43	20	GL3UR43	100
				●		☆ GL3BC302B0S2	900						
				●		GL3BC402B0SC	200	GL3GC402B0SC	810			GL3UR402B0S	350
				●		GL3BC402B0S1	450	GL3GC402B0S1	1 800				
	φ5			●		GL3B2402B0SC	650	GL3G2402B0SC	2 800				
		●								GL5TR8	80		
				●								GL5UR44	850
			●									GL5UR2K	2 000
			●									GL5UR3K	3 000
				●						GL5TR43	500	GL5UR2K1	2 000
				●								GL5UR3K1	3 000
				●		GL5B2302B0SC	1 200						
				●		GL5BC302B0S1	700	GL5GC302B0S1	1 700				
				●								GL6UR11T ^{*1}	900
				●								GL6UR31	950
Oval	Long: 5.8 Short: 4.6		●									GL6UR26T ^{*1}	400
Rectangle	2.0 × 5.0	●								GL8TR21	4	GL8UR21	16
	1.8 × 3.9	●								GL8TR42	4		

*1 With tie-bar

Taped model is also available.



Notice

In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that may occur in equipment using any SHARP devices shown in catalogs, data books, etc.
 Except where specially indicated, models listed on this page comply with the RoHS Directive*. For details, please contact SHARP.
 *RoHS Directive: Prohibits use of lead, cadmium, hexavalent chromium, mercury and specific brominated flame retardants (PBBs and PBDEs), with certain exceptions.
 Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device.

LED LAMPS

(If = 20 mA*, Ta = 25°C)

Appearance	Radiation shape (mm)	Resin type			K G		E G		F G		H Y		H S		H D		P R	
		Colored diffusion	Colored transparency	Colorless transparency	Green		Yellow-green		Yellow-green (HL)		Yellow		Sunset orange		Red		Red	
					(555 nm)	Luminous intensity (mcd) TYP.	(565 nm)	Luminous intensity (mcd) TYP.	(565 nm)	Luminous intensity (mcd) TYP.	(585 nm)	Luminous intensity (mcd) TYP.	(610 nm)	Luminous intensity (mcd) TYP.	(635 nm)	Luminous intensity (mcd) TYP.	(695 nm)	Luminous intensity (mcd) TYP.
Cylinder	ø3	●			GL3KG8	30	GL3EG8	60			GL3HY8	55	GL3HS8	60	GL3HD8	40	GL3PR8	8
		●					GL3EG41	130										
			●		GL3KG44	60	GL3EG44	130			GL3HY44	100	GL3HS44	100	GL3HD44	110	GL3PR44	12
		●			GL3KG43	20	GL3EG43	38			GL3HY43	25	GL3HS43	25	GL3HD43	25	GL3PR43	3
		●			GL3KG62	22	GL3EG62	65			GL3HY62	40	GL3HS62	40	GL3HD62	50		
		●			GL3KG63	6	GL3EG63	18			GL3HY63	16	GL3HS63	15	GL3HD63	17	GL3PR63	2
		●					LT3E31W*2	18			LT3H31W*2	15			LT3D31W*2	15	LT3P31W*2	1.5
		●					LT3E65W*2	25			LT3H65W*2	25	LT3S65W*2	25	LT3D65W*2	25	LT3P65W*2	3
	ø4	●			GL4KG8	30	GL4EG8	100			GL4HY8	110	GL4HS8	80	GL4HD8	110	GL4PR8	15
		●					GL5EG4	20							GL5HD4	25	GL5PR4	3
		●			GL5KG8	60	GL5EG8	150			GL5HY8	120	GL5HS8	80	GL5HD8	80	GL5PR8	15
		●			GL5KG41	70	GL5EG41	160			GL5HY41	100	GL5HS41	100	GL5HD41	150	GL5PR41	15
		●			GL5KG44	70	GL5EG44	160			GL5HY44	100	GL5HS44	100	GL5HD44	100	GL5PR44	15
		●					GL5EG261B0SB	150							GL5HD261B0SB	80	GL5PR261B0SB	15
		●					GL5EG40	250			GL5HY40	250	GL5HS40	200	GL5HD40	250	GL5PR40	35
		●			GL5KG43	120	GL5EG43	300	GL5FG43	600	GL5HY43	250	GL5HS43	250	GL5HD43	300		
	ø5 (Inverted cone)		●				GL5EG60	23							GL5HD60	8		
			●				GL6EG11T*3	120										
		●					GL5EG47	15					GL5HS47	6	GL5HD47	8		
		●					GL6EG26T*3	140										
Oval	Long: 5.8 Short: 4.6	●					GL6EG26T*3	140										
Convex	ø2	●					GL2EG6	15			GL2HY6	12			GL2HD6	12	GL2PR6	1.5
Arch	2.5 × 5.0	●					GL8EG2	30							GL8HD2	30		
	2.0 × 3.1	●					GL8EG4	50							GL8HD4	40		
Rectangle	1.8 × 3.9	●			GL8KG42	1.5	GL8EG42	5			GL8HY42	6			GL8HD42	5	GL8PR42	0.7
	1.9 × 3.9	●					GL8EG5	28			GL8HY5	25			GL8HD5	22		
	2.0 × 3.2	●			GL8KG25	9	GL8EG25	12			GL8HY25	12	GL8HS25	10	GL8HD25	12	GL8PR25	1.5
	2.0 × 3.2	●			GL8KG29	5	GL8EG29	12			GL8HY29	10	GL8HS29	7			GL8PR29	3
	2.0 × 4.5	●					GL8EG23	6			GL8HY23	8			GL8HD23	6		
	2.0 × 5.0	●			GL8KG21	4	GL8EG21	8			GL8HY21	8	GL8HS21	8	GL8HD21	8	GL8PR21	0.7
		●			GL8KG26	4	GL8EG26	8			GL8HY26	8			GL8HD26	8	GL8PR26	0.7
Square	5.0 × 5.0	●			GL8KG22	3.5	GL8EG22	6			GL8HY22	5	GL8HS22	5	GL8HD22	8	GL8PR22	1.2
Triangle	Isosceles triangle	●															GL8PR28	0.9

*1 PR series (Red): If = 5 mA (GL8PR25, GL8PR29: If = 10 mA)

*2 Taped model

*3 With tie-bar

HL: High-luminosity

Taped model is also available.

Notice

In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that may occur in equipment using any SHARP devices shown in catalogs, data books, etc.

Except where specially indicated, models listed on this page comply with the RoHS Directive*. For details, please contact SHARP.

*RoHS Directive: Prohibits use of lead, cadmium, hexavalent chromium, mercury and specific brominated flame retardants (PBBs and PBDEs), with certain exceptions.

Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device.

Cylinder



GL3PR8 series



GL3PR44 series



GL3HY43 series



GL3KG62 series



LT3E31W series



GL3PR63 series



LT3E65W series



GL4PR8 series



GL5PR4 series



GL5HS8 series



GL5KG41 series



GL5PR44 series



GL5EG40 series



GL5HY43 series



GL5EG60 series



GL6EG11T



GL5HD47 series

Oval



GL6EG26T



GL2HY6



GL8EG2 series



GL8HD4 series

Convex

Arch

Rectangle



GL8KG42 series



GL8KG25 series



GL8HY29 series



GL8HD23 series



GL8HS21 series



GL8HY26 series

Square

Triangle



GL8HD22 series



GL8PR28

Notice

In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that may occur in equipment using any SHARP devices shown in catalogs, data books, etc.
Except where specially indicated, models listed on this page comply with the RoHS Directive*. For details, please contact SHARP.
*RoHS Directive: Prohibits use of lead, cadmium, hexavalent chromium, mercury and specific brominated flame retardants (PBBs and PBDEs), with certain exceptions.
Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device.

■ DICHROMATIC LED LAMPS

(The values in luminous intensity are radiation color order) (I_F = 20 mA*1, T_a = 25°C)


Appearance	Radiation shape (mm)	Resin type				E JJ	Yellow-green + Orange (HL)		C U *	Yellow-green + Red (HL)		E P	Yellow-green + Red		E D	Yellow-green + Yellow		E H	Yellow + Red	
		Colored diffusion	Colored transparency	Colorless transparency	Milky diffusion		Luminous intensity (mod) TYP.		Luminous intensity (mod) TYP.		Luminous intensity (mod) TYP.		Luminous intensity (mod) TYP.		Luminous intensity (mod) TYP.		Luminous intensity (mod) TYP.		Luminous intensity (mod) TYP.	
Cylinder	ø3				●									GL3ED8	20/15					
	ø5				●	GL5EJJ502C0X*2	110/170			GL5EP5	40/9	GL5ED5	40/25					GL5HP5	15/9	
				●				GL5CU44	100/240				GL5ED44	80/50						
				●				GL6CU7	120/250				GL5ED60	11/8						
Rectangle	1.9 × 3.9				●							GL8ED5	10/6.5					GL8HP5	3/1.5	
	2.0 × 5.0				●							GL9ED2	8/3	GL9EH2	6/2	GL9HP2	1/0.8			
	5.0 × 5.0				●							GL9ED4	7/4							

* CU series: Common anode pin connection

*1 P (Red) and H (yellow): I_F = 10 mA

*2 Taped model

HL: High-luminosity



Notice

In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that may occur in equipment using any SHARP devices shown in catalogs, data books, etc.
 Except where specially indicated, models listed on this page comply with the RoHS Directive*. For details, please contact SHARP.
 *RoHS Directive: Prohibits use of lead, cadmium, hexavalent chromium, mercury and specific brominated flame retardants (PBBs and PBDEs), with certain exceptions.
 Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device.

☆New product
★Under development

■ HIGH-LUMINOSITY (AlGaInP) CHIP LEDs (Taped models only)

(If = 20 mA, Ta = 25°C)

Outline dimensions (mm)	Resin type				Z G		Z E J E		Z V J V		Z S J S		Z J J J		Z R J R	
	Colored diffusion	Colored transparency	Colorless transparency	Milky diffusion	Green	Luminous intensity (mcd) TYP.	Yellow-green	Luminous intensity (mcd) TYP.	Amber	Luminous intensity (mcd) TYP.	Sunset orange	Luminous intensity (mcd) TYP.	Orange	Luminous intensity (mcd) TYP.	Red	Luminous intensity (mcd) TYP.
1.6 × 0.8 (T: 0.35)			●				GM1JE35200AE ^{*1}	13	GM1JV35200AE ^{*1}	18.8	GM1JS35200AE ^{*1}	19	GM1JJ35200AE ^{*1}	19	GM1JR35200AE ^{*1}	13
1.6 × 0.8 (T: 0.55)			●				GM1JE55200AE ^{*1}	13	GM1JV55200AE ^{*1}	16.8	GM1JS55200AE ^{*1}	20.9	GM1JJ55200AE ^{*1}	19		
1.6 × 0.8 (T: 0.8)			●		LT1ZG67A	6.1	LT1ZE67A	25.4	LT1ZV67A	78.7	LT1ZS67A	123.2	LT1ZJ67A	123.3	LT1ZR67A	73.9
			●						GM1ZV80300AE	75	GM1ZS80300AE	75	GM1ZJ80300AE	75	GM1ZR80300AE	55
			●						LT1JV67A ^{*1}	16.5	LT1JS67A ^{*1}	14.1				
2.0 × 1.25 (T: 0.8)			●		LT1ZG40A	6.2	LT1ZE40A	28.2	LT1ZV40A	92.7	LT1ZS40A	144.1	LT1ZJ40A	127.8	LT1ZR40A	78.7
			●						GM1ZV40300AE	60	GM1ZS40300AE	78	GM1ZJ40300AE	60	GM1ZR40300AE	55
			●						GM1JV40300AE	11	GM1JS40300AE	12	GM1JJ40300AE	9.5		
3.2 × 2.8 (T: 1.9)		●			LT1ZG95A	15	LT1ZE95A	45	LT1ZV95A	170	LT1ZS95A	290	LT1ZJ95A	200	GM5ZR95200AE	100
		●							GM5JV95200AE	80	GM5JS95200AE	90	GM5JJ95200AE	70		
6.0 × 5.0 (T: 2.5)		●							GM5ZV01200A ^{*3}	500	GM5ZS01200A ^{*3}	700	GM5ZJ01200A ^{*3}	500	GM5ZR01200A ^{*3}	400
		●							GM5YV01210A ^{*4}	1 300	GM5YS01210A ^{*4}	1 700	GM5YJ01210A ^{*4}	1 500		
6.0 × 5.0 (T: 2.3) (board insertion type)		●							GM5ZV03200Z ^{*3}	500	GM5ZS03200Z ^{*3}	700	GM5ZJ03200Z ^{*3}	500	GM5ZR03200Z ^{*3}	400
1.6 × 1.15 (T: 0.8) (Side emitting)		●							GM4JV81200AE ^{*2}	35	GM4JS81200AE ^{*2}	40	GM4JJ81200AE ^{*2}	40	GM4JR81200AE ^{*2}	30
		●													★GM4JR81250AE ^{*2}	(45)
2.7 × 1.3 (T: 1.2) (Side emitting)			●						LT1JV45A ^{*1}	20	LT1JS45A ^{*1}	24	LT1JJ45A ^{*1}	16		

*1 LT1JS67A, LT1JV67A, GM1JV55200AE series, GM1JV35200AE series, GM1JV40300AE series, LT1JV45A series: If = 5 mA

*2 GM4JV81200AE series: If = 10 mA

*3 GM5ZR01200A series, GM5ZR03200Z series: If = 60 mA

*4 GM5YV01210A series: If = 90 mA

Notice

In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that may occur in equipment using any SHARP devices shown in catalogs, data books, etc.
Except where specially indicated, models listed on this page comply with the RoHS Directive*. For details, please contact SHARP.
*RoHS Directive: Prohibits use of lead, cadmium, hexavalent chromium, mercury and specific brominated flame retardants (PBBs and PBDEs), with certain exceptions.
Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device.

☆New product
★Under development

■ HIGH-LUMINOSITY (InGaN) CHIP LEDs (Taped models only)

(If = 10 mA, Ta = 25°C)

Outline dimensions (mm)	Resin type				BC		GC	
	Colored diffusion	Colored transparency	Colorless transparency	Milky diffusion	Blue	Luminous intensity (mcd) TYP.	Green	Luminous intensity (mcd) TYP.
1.6 × 0.8 (T: 0.35)			●				GM1GC35200AC	54
				●	★GM1BC35370AC* ¹	23		
1.6 × 0.8 (T: 0.55)			●		★GM1BC55270AC* ¹	23	GM1GC55200AC	47
3.2 × 2.8 (T: 1.9)			●		GM5BC95200AC* ²	73	GM5GC95200AC* ²	311
			●		★GM5BC95250AC* ²	120	★GM5GC95250AC* ²	500
			●		★GM5BC95270AC* ²	370		
6.0 × 5.0 (T: 2.5)			●		GM5BC01200AC* ³	200	GM5GC01200AC* ³	520
			●		★GM5BC01250AC* ³	300	★GM5GC01250AC* ³	1 200
			●		★GM5BC01270AC* ³	550		
6.0 × 5.0 (T: 2.3) board insertion type			●		GM5BC03200Z* ³	200	GM5GC03200Z* ³	520
			●		☆GM5BC03210Z* ³	300		
1.6 × 1.15 × 0.8 (Side emitting)			●		★GM4BC81250AC	50	★GM4GC81250AC	170
2.7 × 1.3 × 1.2 (Side emitting)				●	GM4BC13300AC	12	GM4GC13300AC	46

*1 GM1BC35370AC, GM1BC55270AC: If = 5 mA

*2 GM5BC95200AC series, GM5BC95250AC series: If = 20 mA

*3 GM5BC01200AC series, GM5BC01250AC series, GM5BC03200Z series: If = 50 mA

Notice

In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that may occur in equipment using any SHARP devices shown in catalogs, data books, etc.
Except where specially indicated, models listed on this page comply with the RoHS Directive*. For details, please contact SHARP.

*RoHS Directive: Prohibits use of lead, cadmium, hexavalent chromium, mercury and specific brominated flame retardants (PBBs and PBDEs), with certain exceptions.

Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device.

■ CHIP LEDs (Taped models only)

(If = 20 mA*, Ta = 25°C)

Outline dimensions (mm)	Resin type				Green	Luminous intensity (mcd) TYP.	E F E G		Yellow-green	Luminous intensity (mcd) TYP.	H H Y		Yellow	Luminous intensity (mcd) TYP.
	Colored diffusion	Colored transparency	Colorless transparency	Milky diffusion										
1.6 × 0.8 (T: 0.35)			●						GM1EG35200A	19				
1.6 × 0.8 (T: 0.55)			●						GM1EG55200A	19			GM1HY55200A	11.5
1.6 × 0.8 (T: 0.6)				●					LT1E97A	23			LT1H97A	9.8
1.6 × 0.8 (T: 0.8)				●	LT1K67A	3.8			LT1E67A LT1F67A LT1F67AF	23			LT1H67A	8.3
2.0 × 1.25 (T: 0.8)				●	LT1K40A	5			LT1E40A	19			LT1H40A	10.8
3.2 × 2.8 (T: 1.9)			●						GM5EG95200A	18.1				
1.6 × 1.15 × 0.8 (Side emitting)			●						GM4EG81200A	20				
2.7 × 1.3 × 1.2 (Side emitting)				●					LT1E45A	29				

Outline dimensions (mm)	Resin type				Sunset orange	Luminous intensity (mcd) TYP.	D H D		Red	Luminous intensity (mcd) TYP.	U U R		Red (HL)	Luminous intensity (mcd) TYP.	Red	Luminous intensity (mcd) TYP.
	Colored diffusion	Colored transparency	Colorless transparency	Milky diffusion												
1.6 × 0.8 (T: 0.55)			●		GM1HS55200A	11.4			GM1HD55200A	12.5			GM1UR55200A	29.7		
1.6 × 0.8 (T: 0.6)				●	LT1S97A	8.2			LT1D97A	11			LT1U97A	35.3	LT1P97A	1.6
1.6 × 0.8 (T: 0.8)				●	LT1S67A	6.9			LT1D67A	8.8			LT1U67A	29.7	LT1P67A	1.3
2.0 × 1.25 (T: 0.8)				●	LT1S40A	9.4			LT1D40A	11.9			LT1U40A	35.6	LT1P40A	1.3
3.2 × 2.8 (T: 1.9)			●						GM5HD95200A	13.8			GM5UR95200A	80		

*1 P (Red) series: If = 5 mA

HL: High-luminosity

 LT1D67A series LT1ZR67A series LT1JS67A series GM1ZV80300AE series	 LT1D97A series	 GM1EG55200A series GM1JV55200AE series GM1BC55250AC series	 LT1E40A series LT1ZE40A series GM1JV40300AE series GM1ZV40300AE series
 GM1JV35200AE series GM1EG35200A GM1BC35200AC series GM1BC35310AC	 LT1E45A series LT1JV45A series GM4BC13300AC series	 GM4JV81200AE series GM4EG81200A GM4BC81250AC series	 LT1ZR95A series GM5JV95200AE series, GM5EG95200A series GM5BC95200AC series, GM5BC95250AC series
 GM5ZR01200A series, GM5BC01200AC series GM5BC01250AC series, GM5YV01210A series		 GM5ZV03200Z series GM5BC03200Z series	 Taped model

Notice

In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that may occur in equipment using any SHARP devices shown in catalogs, data books, etc.

Except where specially indicated, models listed on this page comply with the RoHS Directive*. For details, please contact SHARP.
 *RoHS Directive: Prohibits use of lead, cadmium, hexavalent chromium, mercury and specific brominated flame retardants (PBBs and PBDEs), with certain exceptions.

Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device.

★Under development

■ HIGH-LUMINOSITY DICHROMATIC TYPE CHIP LEDs (Taped models only)

(If = 20 mA, [Blue, Green: If = 10 mA], Ta = 25°C)

Outline dimensions (mm)	Resin type					Luminous intensity (mcd) TYP.	Luminous intensity (mcd) TYP.
	Colored diffusion	Colored transparency	Colorless transparency	Milky diffusion			
1.6 × 1.6 (T: 0.8)				●	ZV BC Amber + Blue	43.8/14.4	ZS GC Sunset orange + Green 66/46.1

(If = 40 mA, Ta = 25°C)

Outline dimensions (mm)	Resin type					Luminous intensity (mcd) TYP.	Luminous intensity (mcd) TYP.	Luminous intensity (mcd) TYP.
	Colored diffusion	Colored transparency	Colorless transparency	Milky diffusion				
6.0 × 5.0 (T: 2.5)			●		BC GC Blue + Green 300/860	300/860	BC ZR Blue + Red 300/580	GC ZR Green + Red 860/580

■ DICHROMATIC TYPE CHIP LEDs (Taped models only)

(If = 20 mA, Ta = 25°C)

Outline dimensions (mm)	Resin type					Luminous intensity (mcd) TYP.	Luminous intensity (mcd) TYP.
	Colored diffusion	Colored transparency	Colorless transparency	Milky diffusion			
1.6 × 1.6 (T: 0.8)				●	EH Yellow-green + Yellow 19/8.3	19/8.3	ED Yellow-green + Red 19/8.3

GM5BG01210A series

LT1ED67A series
GM1ZVB80300A series

■ HIGH-LUMINOSITY WHITE TYPE CHIP LEDs (with blue chip) (Taped models only)

(Ta = 25°C)

Outline dimensions (mm)	Color coordinates (x, y)	Radiation color	White	Luminous intensity (mcd) TYP.
3.2 × 2.8 (T: 1.9)	(0.31, 0.3)	White	★ GM5BW95300A*1	1 100
6.0 × 5.0 (T: 1.5) 6-terminal leadless	(0.31, 0.31)	White	★ GM5BW01300A*3	4 200
6.0 × 5.0 (T: 2.5) 4-terminal leadless	(0.31, 0.31)	White	★ GM5BW01301A*2	1 800

*1 GM5BW95300A: If = 20 mA

*2 GM5BW01301A: If = 40 mA

*3 GM5BW01300A: If = 35 mA/chip

GM5BW95300A

GM5BW01300A

GM5BW01301A

Notice

In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that may occur in equipment using any SHARP devices shown in catalogs, data books, etc.
 Except where specially indicated, models listed on this page comply with the RoHS Directive*. For details, please contact SHARP.
 *RoHS Directive: Prohibits use of lead, cadmium, hexavalent chromium, mercury and specific brominated flame retardants (PBBs and PBDEs), with certain exceptions.
 Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device.

☆New product
★Under development

■ WHITE TYPE CHIP LEDs (with blue-violet chip) (Taped models only)

(I_F = 40 mA, T_a = 25°C)

Outline dimensions (mm)	Color coordinates (x, y)	Radiation color	VA	Luminous intensity (mcd) TYP.
6.0 × 5.0 (T: 2.5) 4-terminal leadless	(0.33, 0.33)	White	GM5VA33331AC	450
	(0.34, 0.40)	Yellowish white	★ GM5VA34400AC	(700)
	(0.29, 0.27)	Purplish white	★ GM5VA29270AC	(350)
	(0.30, 0.50)	Greenish white	★ GM5VA30500AC	(900)

() indicates reference value.



■ HIGH-LUMINOSITY DICHROMATIC TYPE CHIP LEDs (RGB 3-color) (Taped models only)

(T_a = 25°C)

Outline dimensions (mm)	Resin type				WA Red + Green + Blue	Luminous intensity (mcd) TYP.
	Colored diffusion	Colored transparency	Colorless transparency	Milky diffusion		
1.6 × 1.6 (T: 0.55)				●	★ GM1WA55360A*1	125/150/55
1.6 × 1.6 (T: 0.8)				●	GM1WA80350A*2	80/92/30
6.0 × 5.0 (T: 2.5) 4-terminal leadless			●		GM5WA02200A*3	850 [Mixed color]
6.0 × 5.0 (T: 2.5)*7 6-terminal leadless			●		GM5WA06203A*3	850 [Mixed color]
			●		GM5WA06210A*4	250/400/350
			●		GM5WA06250A*5	1 400 [Mixed color]
			●		GM5WA06260A*3	1 725 [Mixed color]
			●		GM5WA06270A*6	3 000 [Mixed color]
6.0 × 5.0 (T: 2.3 [resin part]) 6-terminal			●		GM5WA06200Z*3	850 [Mixed color]
			●		GM5WA06203Z*3	850 [Mixed color]
			●		GM5WA06250Z*4	1 400 [Mixed color]
6.0 × 5.0 (T: 1.5) 6-terminal leadless				●	☆ GM5WA05360A*6	2 200 [Mixed color]

*1 GM1WA55360A: I_F = 10 mA (Red, Green, Blue)

*2 GM1WA80350A: I_F = 20 mA (Red), I_F = 10 mA (Green, Blue)

*3 GM5WA02200A, GM5WA06203A, GM5WA06260A, GM5WA06200Z, GM5WA06203Z: I_F = 40 mA (Red, Green), I_F = 20 mA (Blue)

*4 GM5WA06210A: I_F = 40 mA (Red, Green, Blue)

*5 GM5WA06250A, GM5WA06250Z: I_F = 35 mA (Red, Green), I_F = 20 mA (Blue)

*6 GM5WA06270A, GM5WA05360A: I_F = 35 mA (Red, Green, Blue)

*7 GM5WA06270A: T: 2.4 mm



Notice

In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that may occur in equipment using any SHARP devices shown in catalogs, data books, etc.

Except where specially indicated, models listed on this page comply with the RoHS Directive*. For details, please contact SHARP.
*RoHS Directive: Prohibits use of lead, cadmium, hexavalent chromium, mercury and specific brominated flame retardants (PBBs and PBDEs), with certain exceptions.

Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device.

★Under development

■ LEDs FOR CAMERA DATA BACK

(IF = 1 mA, Ta = 25°C)

Model No.	No. of dots	Outline dimensions (mm)	Radiation color	Luminous intensity (mcd)
GW01M59001PE	7	2.6 × 2.9 (T: 0.9) Surface-mount type	Amber	(MIN. 0.4 TYP. 0.8)

() indicates reference value.



■ LED DRIVERS

Model No.	Description	Function	Supply voltage (V)	Package
★IR2D20N/U	24-dot LED panel driver with constant-current sink outputs	- Output current (constant-current sink outputs) : 30 mA (MAX.) (setup by external resistor) - Graduation function (clock cycle setting or external synchronization) - Independent current control for three systems (for RGB LED) - LED drive voltage : 15 V - Rated output voltage : 20 V (MAX.) - f_{CLK} : 20 MHz (MAX.) / 16.6 MHz (MAX.) (at cascade connection)	4.5 to 5.5	P-SSOP056-0600/ P-HQFN052-0707
★IR2D07N1	16-dot LED panel driver with constant-current sink outputs	- Output current (constant-current sink outputs) : 60 mA (MAX.) (setup by external resistor) - Rated output voltage : 7 V (MAX.) - f_{CLK} : 20 MHz (MAX.) / 16.6 MHz (MAX.) (at cascade connection)	3.0 to 5.5	P-SSOP040-0300
★IR2E46U6/Y6	RGB LED driver for flash lights and illuminations	- Output current : 155 mA/ch (MAX.) (3ch) (in flash mode) - Control by I²C bus - Illumination mode (64 levels/ch) - Flash mode (32 levels/ch) - Brightness adjustment	2.7 to 4.5	P-VQFN032-0505/ WL-CSP*1
★IR2E47U6	White LED driver for back light	- Output current : 20 mA (MAX.) (setup by external resistor) - Independent current control for two systems (4 outputs and 2 outputs) - LED non-connected judging function - Brightness adjustment	2.7 to 5.5	P-VQFN024-0404 (*2)
★IR2E48U6		- Output current : 20 mA (MAX.) - LED non-connected judging function - Brightness adjustment		P-VQFN024-0404

*1 WL-CSP : Wafer-level CSP

*2 Contact a SHARP sales office regarding a wafer-level CSP.

Notice

In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that may occur in equipment using any SHARP devices shown in catalogs, data books, etc. Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device.