


U4Y003J



Sales Region	Worldwide (except Japan)
Series	EFE
Model	EFE400
Status	Production
Feature	<div>Peak Load</div> Peak power capability <div>Full Digital</div> Full digital control
Options	End fan With chassis With cover
Option Lineup	Please refer to here.
Recommended EMC Filter	
Accessories	Please refer to the catalog



Electrical Characteristics	
Input	Single-phase
Input Voltage Range[AC]	90 to 264Vac
Input Voltage Range[DC]	
Efficiency	90% Typ.
Rated Output Voltage[DC]	12Vdc
Output Voltage Range[DC]	11.4 to 13.2Vdc
Maximum Output Current	33.3A
Maximum Average Current	
Maximum Peak Current	44.17A
Maximum Output Power	400W
Maximum Average Power	
Maximum Peak Power	530W

Package Type & Size	
Package / Mounting	Enclosed / Unit type
Width(W)	
Height(H)	
Depth(D)	
Weight	650g Typ. (1.4lbs Typ.)

Other	
Operating Temp. Range	0 to 50°C
Cooling	Forced air

Safety Standard(Certified)	IEC60950-1
	CSA60950-1
	EN60950-1
	UL60950-1
	IEC61010-1
	EN61010-1
Safety Standard(Conformed)	
Remarks	This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.