

IDC female connectors - FP 1,27/ 50-FWL - 1714909

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



IDC female connector, Nominal current at 20 °C: 1.2 A, Test voltage: 500 V AC, number of positions: 50, pitch: 1.27 mm, color: black, contact surface: Gold


The figure shows a 12-pos. version with 12 contacts

Your advantages

- ✓ Gold-plated contacts ensure transfer quality remains stable over the long term
- ✓ Compact, high-position board-to-board or wire-to-board connectors for space-saving device designs
- ✓ Can be ordered pre-assembled: IDC female connectors with flat-ribbon cable enable immediate use in the device



Key Commercial Data

| | |
|--------------|---|
| Packing unit | 160 pc |
| GTIN |  4 055626 402888 |
| GTIN | 4055626402888 |

Technical data

Item properties

| | |
|---------------------------|-----------------------|
| Brief article description | IDC female connectors |
| Plug-in system | FINEPITCH 1,27 mm |
| Type of contact | Female connector |
| Range of articles | FP 1,27/...-FWL |
| Pitch | 1.27 mm |
| Number of positions | 50 |
| Number of levels | 2 |
| Number of potentials | 50 |

Electrical data

| | |
|--------------------------|-----------------|
| Nominal current at 20 °C | 1.2 A (50-pos.) |
| Test voltage | 500 V AC |

IDC female connectors - FP 1,27/ 50-FWL - 1714909

Technical data

Electrical data

| | |
|-----------------------|----------------------------------|
| Contact resistance | ≤10 mΩ, (IEC 60512-2-1:2002-02) |
| Insulation resistance | ≥ 10 GΩ, (IEC 60512-3-1:2002-02) |

Connection capacity

| | |
|-------------------------------------|-------------------------|
| Connection method | Displacement connection |
| Conductor cross section AWG / kcmil | 30 |

Material data - contact

| | |
|---|---|
| Note | WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/ JEDEC JESD 201 |
| Contact material | Cu alloy |
| Surface characteristics | Selective coating |
| Metal surface contact area (top layer) | Gold (Au) |
| Metal surface contact area (middle layer) | Nickel (Ni), Palladium nickel (PdNi) |

Material data - housing

| | |
|--|------|
| Insulating material | LCP |
| Insulating material group | IIIa |
| CTI according to IEC 60112 | 175 |
| Flammability rating according to UL 94 | V0 |

Dimensions for the product

| | |
|--------------|--|
| Caption | Schematische Abbildung - weitere Details siehe Produktfamilienzeichnung im Download Center |
| Length [l] | 13.65 mm |
| Width [w] | 37.91 mm |
| Height [h] | 4.2 mm |
| Pitch | 1.27 mm |

Dimensions for the application

| | |
|-------------------|---|
| Medium offset | ± 0.7 mm in longitudinal and transverse direction |
| Angular tolerance | ± 4 ° in longitudinal direction |
| | ± 2 ° in transverse direction |

Packaging information

| | |
|----------------------------|------|
| Type of packaging | Tray |
| Pieces per package | 160 |
| Denomination packing units | Pcs. |

General product information

| | |
|--------------|--|
| Type of note | Note on application |
| | Note regarding documentation |
| | Notes on operation |
| Note | Please observe the application note on self-assembly in the download area. |

IDC female connectors - FP 1,27/ 50-FWL - 1714909

Technical data

General product information

| | |
|--|--|
| | Current documents such as 3D models, products family drawings, data sheets or packaging drawings are available in the Download Center. |
| | The permissible voltage during operation depends on the application, taking into consideration the air clearances and creepage distances within the scope of insulation requirements in accordance with IEC 60664-1. |

Ambient conditions

| | |
|---|-------------------|
| Ambient temperature (storage/transport) | -40 °C ... 70 °C |
| Ambient temperature (assembly) | -5 °C ... 100 °C |
| Ambient temperature (operation) | -55 °C ... 125 °C |

Service life

| | |
|--------------|--|
| Service life | 500 Insertion/withdrawal cycles, Performance level 1 |
|--------------|--|

Environmental Product Compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

Classifications

eCl@ss

| | |
|---------------|----------|
| eCl@ss 10.0.1 | 27440309 |
| eCl@ss 11.0 | 27460202 |
| eCl@ss 4.0 | 27260700 |
| eCl@ss 4.1 | 27260700 |
| eCl@ss 5.0 | 27260700 |
| eCl@ss 5.1 | 27260700 |
| eCl@ss 6.0 | 27260700 |
| eCl@ss 7.0 | 27440402 |
| eCl@ss 8.0 | 27440309 |
| eCl@ss 9.0 | 27440309 |

ETIM

| | |
|----------|----------|
| ETIM 5.0 | EC002638 |
| ETIM 6.0 | EC002638 |
| ETIM 7.0 | EC002638 |

Approvals

Approvals

Approvals

cULus Recognized / EAC

IDC female connectors - FP 1,27/ 50-FWL - 1714909

Approvals

Ex Approvals

Approval details

| | | |
|------------------|--|--|
| cULus Recognized | | http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm E118976-20170331 |
|------------------|--|--|

| | | |
|-----|--|---------|
| EAC | | B.01687 |
|-----|--|---------|

Accessories

Additional products

SMD male connectors - FP 1,27/ 50-MV 3,25 - 1714931



SMD male connector, Nominal current at 20 °C: 1.4 A, Test voltage: 500 V AC, number of positions: 50, pitch: 1.27 mm, color: black, contact surface: Gold, mounting: SMD soldering

SMD male connectors - FP 1,27/ 50-MV 1,75 - 1714943



SMD male connector, Nominal current at 20 °C: 1.4 A, Test voltage: 500 V AC, number of positions: 50, pitch: 1.27 mm, color: black, contact surface: Gold, mounting: SMD soldering

SMD male connectors - FP 1,27/ 50-MH - 1714920



SMD male connector, Nominal current at 20 °C: 1.4 A, Test voltage: 500 V AC, number of positions: 50, pitch: 1.27 mm, color: black, contact surface: Gold, mounting: SMD soldering

Phoenix Contact 2020 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>