

ARCA 403021 No MP



Sample image

Order symbol: ARCA 403021 No MP

EAN: 6418074089359

Product nbr: 8120007N


El. number:

Description: Cabinet. PC

Remarks: Grey cover. 2-point locking. hinges on the long side

- Finland:
- Denmark:
- Sweden:

Including: Cabinet base. door with PUR gasket. 3mm double bit lock(s) with key. S versions with swinghandle 2-point locking system. Door guide included.



Dimensions:

mm:	Height	Width	Depth
	400	300	210

Accessories:

DRS ARCA	DIN rail frame set
----------	--------------------

inch:	15.75	11.81	8.27
Materials:			
Material:	Polycarbonate		
Base colour:	RAL 7035 -light grey		
Cover colour:	RAL 7035 -light grey		
Gasket material:	Polyurethane		

Temperatures:			
Temperature °C (short term)::	-40 ... 120		
Temperature °C (continuous):	-40 ... 80		
Temperature °F (short term):	-40 ... 250		
Temperature °F (continuous):	-40 ... 175		

403021	(385 x 285 x 35)
SBK ARCA 30	Support bar kit (235 x 40 x 30)
RCS ARCA 4030	Rain canopy set for size 4030 (20 x 300 x 30)
SBK ARCA 40	Support bar kit (340 x 40 x 30)
IDS ARCA 4030	Inner door set (385 x 285 x 35)
PMK ARCA 30	PoleMounting kit. for pole ø100-300mm (385 x 285 x 35)
DSP ARCA VLS	Door stopper ARCA. vertical. left. small
MPMP ARCA 4030	Mounting plate multiperforated (350x250x2 mm - ø3.6 mm) (350 x 250 x 2)
DSP ARCA VRS	Door stopper ARCA. vertical. right. small
MPS ARCA 4030	Mounting plate (350x250x2 mm) (350 x 250 x 2)
MPP ARCA 4030	Mounting plate perforated (350x250x2 mm - 26x11 mm) (350 x 250 x 2)
MPX ARCA 4030	Mounting plate (350x250 mm) (350 x 250 x 5)

Rating:	
Ingress protection (EN 60529):	IP66;
Impact Resistance (EN 62262):	IK10;
Electrical insulation:	Totally insulated
Halogen free (DIN/VDE 0472, Part 815):	1
UV resistance:	UL 508
Flammability Rating:	UL 94 5VA
Glow Wire Test (IEC 695-2-1) °C:	960 °C
NEMA Class	NEMA 1, 4, 4X, 12 and 13

Certificates:	
Certificate FI 40467	