
EDB151 THRU EDB155

SINGLE PHASE 1.5AMP SURFACE MOUNT GLASS PASSIVATED BRIDGE RECTIFIER

Features

- Glass passivated die construction
- Low forward voltage drop
- High current capability
- High surge current capability
- Designed for surface mount application
- Plastic material-UL flammability 94V-0

DB-M



Dimensions in inches and （millimeters）

Mechanical Data

- Case: DB-M, molded plastic
- Terminals: plated leads solderable per MIL-STD-202, Method 208
- Polarity: as marked on case
- Mounting position: Any
- Marking: type number
- Lead Free: For RoHS / Lead Free Version

Maximum Ratings and Electrical Characteristics

Rating at 25℃ ambient temperature unless otherwise specified.
Single Phase, half wave, 60Hz, resistive or inductive load.
For capacitive load, derate current by 20%.

TYPE NUMBER	SYMBOL	EDB151	EDB152	EDB153	EDB154	EDB155	UNITS
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	V_{RRM} V_{RWM} V_{DC}	50	100	200	400	600	V
RMS Reverse Voltage	V_{RMS}	35	70	140	280	420	V
Average Rectified Output Current (Note 1)@T_A=40℃	I_O	1.5					A
Non-Repetitive Peak Forward Surge Current 8.3ms Single half sine-wave superimposed on rated load (JEDEC Method)	I_{FSM}	55					A
Forward Voltage per element @IF=1.5A	V_{FM}	0.95			1.25	1.7	V
Peak Reverse Current @T_A=25℃ At Rated DC Blocking Voltage @T_A=125℃	I_R	5.0 500					uA
Maximum reverse recovery time（Note 3）	T_{RR}	35					ns
Typical Junction Capacitance per leg (Note 2)	C_J	13					pF
Typical Thermal Resistance per leg	$R_{\theta JA}$ $R_{\theta JL}$	70 20					℃/W
Operating and Storage Temperature Range	T_J,T_{STG}	-55to+150					℃

Note:1. Mounted on glass epoxy PC board with 1.3mm^2 solder pad.
2.Measured at 1.0 MHz and applied reverse voltage of 4.0V D.C.

EDB151 THRU EDB155

Fig. 1 Output Current Derating Curve




Fig. 2 Typical Forward Characteristics (per leg)




Fig. 3 Maximum Peak Forward Surge Current (per leg)




Fig. 4 Typical Reverse Characteristics (per element)

