


Sales Region	Worldwide (except Japan)
Series	ZUP
Model	ZUP 200W
Status	 Production
Option Lineup	Please refer to here.
Recommended EMC Filter	
Accessories	Please refer to here.



Electrical Characteristics

Input	Single-phase
Input Voltage Range[AC]	85 to 265Vac
Input Frequency Range	47 to 63Hz
Rated Output Voltage[DC]	10Vdc
Output Voltage[DC]	0 to 10Vdc
Rated Output Current	20A
Output Current	0 to 20A
Rated Output Power	200W
Efficiency	77% Typ.
Voltage Ripple Noise	0.005Vrms (5Hz to 1MHz)
Current Ripple Noise	0.025Arms (5Hz to 1MHz)

Package Type & Size

Package Type	3U Rack mount / Bench top
Width(W)	70mm Nom. (2.76in Nom.)
Height(H)	153mm Nom. (6.02in Nom.)
Depth(D)	405.9mm Nom. (15.98in Nom.)
Weight	2900g Typ. (6.4lbs Typ.)

Other

Interfaces Included	RS-232
	RS-485
	Front panel output jacks
	IEC320 cable USA plug
Interface Options	Serial link cable RJ-45
Operating Temp. Range	0 to 50°C
Safety Standard(Certified)	EN61010-1
	CSA C22.2 No.1010.1-92
	UL3111-1

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.

Safety Standard(Conformed)

Remarks

This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.