

HFE1600-12/S





Sales Region	Worldwide	
Series	HFE	
Status	Production	
Feature		
Option	PM Bus option	
Option Lineup	Please refer to here.	
Recommended EMC Filter	Please refer to here.	
Accessories	Please refer to the catalog	



Electrical Characteristics		
Input Voltage Range[AC]	85 to 265V	
Input Voltage Range[DC]		
Efficiency	90% Typ.	
Rated Output Voltage[DC]	12V	
Output Voltage Range[DC]	9.6 to 13.2V	
Maximum Output Current	133A	
Maximum Output Power	1596W	

Cases Shape & Size		
Case' shape	Unit	
Width(W)	85mm Nom.	
Height(H)	41mm Nom.	
Depth(D)	300mm Nom.	
Weight	1550g Typ.	

Other		
Operating Temp. Range	-10 to 70°C	
Cooling	Blower fan cooling	
Cotoby Chandard (Countified)	UL60950-1	
Safety Standard(Certified)	EN60950-1	
Safety Standard(Conformed)		
Remarks	This page only shows representative characteristics. Please refer to the	
Reliidiks	technical data for detailed specifications and conditions.	

[!] Images are for reference only and show exemplary products. ! This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.