ADELS contact

Circular Plug Connectors IP68
Circular Plug Connectors AC 169 kompakt

AC 169 RST/ 4

Plug, 4 pole, Voltage Rating: 450 V, Current Rating: 17.5 A, Cross-Section: 1.5 mm²

Order Info

Reference Number (ref. no.)	722014
Applications	Lighting, Installation
PU	200
EAN	4028012130283

Type

Type	Plug
Number of poles	4 pole
Clamping Units per Pole	1
Colour	black
Cross-Section	1.5 mm²
Connection Type	Screw
PE Function	yes
Protection Against Incorrect Plugging	yes

Technical Data

Voltage Rating	450 V
Current Rating	17.5 A
Insulating Material	PA 6.6
Contact Material	Brass
Core Cross-Section min.	0.75 mm²
Core Cross-Section max.	2.5 mm²
Impulse Voltage Rating	4.0 kV
Flammability Rating	V-2
max. Ambient Temperature Operation	85 °C
IP Code	IP68
Type of Conductor Solid	yes
Type of Conductor Flexible	yes
Type of Conductor Stranded	yes
Stripping Length	6.0 mm
Dismantling Length PE	25.0 mm
Dismantling Length	30.0 mm

Assembly Contact Screw	0.5x3.0 / ↻ 0.5 Nm
Assembly Strain Relief	↻ 2.5 Nm
Cable Diameter min.	7.0 mm
Cable Diameter max.	13.5 mm

Accessories

AC 169 BC black	729030
AC 169 RVKS M20	729280
AC 169 RWZ/ 2-4	749964
AC 169 WKZ SW21/24	749960
DR 16 1x14,0	729031
DR 16 1x4,0	729033
DR 16 1x6,5	729034
DR 16 2x4,0	729035
DR 16 2x5,5	729036
DR 16 3x4,0	729037
DR 16 4x3,5	729038
DR 16 5x3,5	729009
DR 16 RH	729011
DR 16 GS	729032