



USB A jack		Magnetic Connector		
Pin	name	cable color	description	Pin
1	VBUS	Red	+5V	2
2	D-	White	Data-	5
3	D+	Green	Data+	3
4	GND	Black	Signal Ground	4
shell	-	-	-	1

All dimensions are in mm; tolerances according to ISO 2768 m-H

#### Interface

According to

MF2K201-400L  
USB Standard-A

#### Flammability

##### Connector parts

Insulator

Assembly parts

##### Category

material acc. to UL94 V-0

material acc. to UL94 V-1/V-2

# Technical Data Sheet

# Rosenberger

MF

CABLE ASSEMBLY

L99-838-XXX

## Material and plating

### Connector parts (MF)

Insulator	PBT GF30	Plating / Colour
Housing	PBT GF30	black
Housing insert	PA	black
Piston	Brass	min 0,25 µm Au over 2,5 µm Ni
Ferrule	Brass	min 0,25 µm Au over 2,5 µm Ni
Spring	Stainless steel	
Tension relief	TPE	black
Magnet	NdFeB N52	Ni
Silicone Tube	Silicone	

## Connectors

USB plug type A

## Electrical data

According to USB 2.0  
Peak current 500mA

## Mechanical data

Mating cycles min. 10.000  
Disengagement force > 10 N  
Force measured during vertical disengagement with counter connector  
Magnetic pole north to interface

## Environmental data

Temperature range -25°C to +75°C  
RoHS compliant

## Suitable cables

USB 2.0 Standard cable

## Available versions

Type	Length A [mm]	pieces per box	g/piece
L99-838-500	500 +20/-20	100	25
L99-838-1500	1500 +80/-80	200	54
L99-838-1800	1800 +80/-80	200	62

## Packing

Single packing 1 pcs per box

## Caution

„The magnetic field of the assembled magnets is very strong. These magnets can particularly impact the function of cardiac pacemakers, implanted cardioverter-defibrillators (e.g. by unintentional actuation of reed switch), hearing aids, data storage media, monitors, and debit- and credit cards. Therefore keep sufficient safety distance from such or similar devices to prevent malfunction and danger to health. In case of any further questions please contact our customer service center.“

Draft	Date	Approved	Date
G. Lapper	03.04.2012	C. Kainzmaier	14.10.16

Rev.	Engineering change number	Name	Date
c00	16-s322	S. Doerr	14.10.16

Rosenberger Hochfrequenztechnik GmbH & Co. KG  
P.O.Box 1260 D-84526 Tittmoning Germany  
[www.rosenberger.de](http://www.rosenberger.de)

Tel. : +49 8684 18-0  
Fax : +49 8684 18-499  
Email : [info@rosenberger.de](mailto:info@rosenberger.de)

Page

2 / 2