

LFV330-XXGBVX8R0300 LFV300



LEVEL SENSORS

LFV330-XXGBVX8R0300 | LFV300

LEVEL SENSORS



Ordering information

Туре	Part no.
LFV330-XXGBVX8R0300	6039664

Other models and accessories → www.sick.com/LFV300

Detailed technical data

Features

i catules	
Medium	Fluids
Measurement	Switch
Probe length	300 mm
Process pressure	-1 bar 64 bar
Process temperature	-50 °C +150 °C
Fill material density	0.5 g/cm ³ 2.5 g/cm ³
GOST approval	1
Performance	
Accuracy of sensor element	± 2 mm
Repeatability	≤ 1 mm
Viscosity	0.1 mPas 10,000 mPas
Response time	500 ms
Electronics	
Power consumption	5 mA 30 mA
Initialization time	<2s
VDE protection class 1	4
Electrical connection	M20 x 1.5
Supply voltage	Double relay (DPDT): 20 V DC 72 V DC / 20 V AC 253 V AC
Hysteresis	2 mm
Output current	> 10 µA; < 3A AC, 1A DC
Inductive load	750 VA 54 W
Capacitive load	750 VA 54 W
Contact load	Min. 50 mW / max. 750 VA, 54 W
Enclosure rating	IP 66 / IP 67
Temperature drift	0,03 mm/K

Mechanics

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com

