# **GPS-102** GPS Module with Dead Reckoning Sensor

# **GPS-106**

Embedded GPS and GALILEO 50-channel Module



#### **Features**

- SiRF star III 20-channel chipset
- Dead reckoning embedded
- Gyroscope enabled
- Low power consumption
- 71 x 40.8 x 18.6 mm (L x W x H)
- Operating Temperature -40 ~ + 85° C

#### Introduction

GPS-102 is a GPS receiver module with integrated dead reckoning. The GPS-102 includes dead reckoning sensors to track its course even when the GPS signal is blocked, for example in urban areas or tunnels. If GPS coverage is lost, the GPS-102 keeps on navigating.

#### **Specifications**

Receiver Type	GPS L1 frequency, C/A code
	GALILEO Open Service L1 frequency
Time-To-First-Fix	Cold Start 35 s
	Warm Start 35 s
	Hot Start 1 s
Position Accuracy	Within 10m for 90%
Velocity Accuracy	0.1 m/s
Heading Accuracy	0.5 degrees
Voltage Type	DC +5V ± 1%
Operational Limits	514 meter/second maximum
Interface	20 Pin Header, 2.0 mm pitch (J2), Male seat
Weight	≤17 a

#### Software Specifications

- Detect GPS Signal Strength
- Detect Satellites
- Parse NMEA Protocols

## ad Busin Arguesters Hommon COM Setting Stretters Lucator (Send)

#### **Packing List**

Description	Quantity
GPS-102 Embedded GPS module	x1
CD-ROM (User's Manual; Utility)	x 1

### **Ordering Information**

Part Number 968EMG0008 **Specifications** GPS module + DR + SMA connector

CEFCC

#### Features

- 50-channel positioning engine
- · Best-in-class acquisition and tracking sensitivity
- Receives GPS and GALILEO signals
- A-GPS: Supports u-blox AssistNow online and offline, OMA SUPL compliant
- UART serial port, USB, DDC (I<sup>2</sup>C compatible)
- Precision timing option

#### Introduction

GPS-106 is designed by u-blox, and sets a new standard for GPS and GALILEO receiver modules. Featuring the high performance 50-channel u-blox 5 technology, these modules provide excellent performance and flexibility at an economical price.

#### **Specifications**

Receiver Type	GPS L1 frequency, C/A code
	GALILEO Open Service L1 frequency
Time-To-First-Fix	Cold Start 29 s
	Warm Start 29 s
	Hot Start < 1 s
Sensitivity	Tracking & Navigation -160 dBm
	Reacquisition -160dBm
	Cold Start -144 dBm
Horizontal Position Accuracy	Autonomous < 2.5m
	SBAS < 2.0m
Velocity Accuracy	0.1 m/s
Heading Accuracy	0.5 degrees
Dynamics	< 4 g
Operational Limits	Velocity 515 m/s (1000 knots)
Weight	2.1 g

### **Packing List**

Description	Quantity
GPS-106 Embedded GPS Module	x1
CD-ROM with Utility	x 1

### **Ordering Information**

Part Number	Specifications
968EMG0013	Embedded GPS Module