



3 Amp Schottky Rectifier

5820SM — 5822SM



| Dim. | Inches | | Millimeter | | Notes |
|------|---------|---------|------------|---------|-------|
| | Minimum | Maximum | Minimum | Maximum | |
| A | .117 | .123 | 2.97 | 3.12 | |
| B | .260 | .280 | 6.60 | 7.11 | |
| C | .220 | .245 | 5.59 | 6.22 | |
| D | .307 | .322 | 7.80 | 8.18 | |
| E | .075 | .095 | 1.91 | 2.41 | |
| F | .380 | .400 | 9.65 | 10.16 | |
| G | .025 | .040 | .640 | 1.02 | |
| H | .030 | .060 | .760 | 1.52 | |



| Microsemi Catalog Number | Working Peak Reverse Voltage | Repetitive Peak Reverse Voltage |
|--------------------------|------------------------------|---------------------------------|
| 5820SM* | 20V | 20V |
| 5821SM* | 30V | 30V |
| 5822SM* | 40V | 40V |

*Add Suffix J For J Lead or G For Gull Wing Lead Configuration

- Schottky Barrier Rectifier
- Guard Ring Protection
- Low Forward Voltage
- High Reliability
- High Current Capability
- Surface mount package

| Electrical Characteristics | | | | | |
|------------------------------|-----------|--------|--------|--------|---|
| | | 5820SM | 5821SM | 5822SM | |
| Average forward current | $I_F(AV)$ | 3A | 3A | 3A | Square wave, $T_L = 127^\circ C$, $R_{\theta JL} = 20^\circ C/W$ 8.3ms, half sine, $T_J = 150^\circ C$ $I_{FM} = 1A$, $T_J = 25^\circ C^*$ $I_{FM} = 3A$, $T_J = 25^\circ C^*$ $I_{FM} = 9.4A$, $T_J = 25^\circ C^*$ V_{RRM} , $T_J = 25^\circ C$ $V_R = 5.0V$, $T_J = 25^\circ C$ |
| Maximum surge current | I_{FSM} | 150A | 150A | 150A | |
| Max peak forward voltage | V_{FM} | .36V | .37V | .38V | |
| Max peak forward voltage | V_{FM} | .46V | .48V | .50V | |
| Max peak forward voltage | V_{FM} | .65V | .67V | .70V | |
| Max peak reverse current | I_{RM} | 1.5mA | 1.5mA | 1.5mA | |
| Typical junction capacitance | C_J | 265pF | 265pF | 265pF | |

*Pulse test: Pulse width 300 μ sec, Duty cycle 2%

| Thermal and Mechanical Characteristics | | |
|--|-----------------|---------------------------------|
| Storage temperature range | T_{STG} | -55°C to 150°C |
| Operating junction temp range | T_J | -55°C to 150°C |
| Maximum thermal resistance | $R_{\theta JL}$ | 20°C/W Junction to Lead |
| Weight | | .008 ounces (.22 grams) typical |

5820SM-5822SM

Figure 1
Typical Forward Characteristics




Figure 3
Typical Junction Capacitance




Figure 2
Typical Reverse Characteristics

