TECH PUBLIC
台舟电子

IRLML6402

P-Channel Mosfet

www.sot23.com.tw

Product Summary

- V_{DS} = -20V,I_D = -4.1A
  $R_{DS(ON)}$ <75mΩ @ V_{GS}=-2.5V
  $R_{DS(ON)}$ < 52mΩ @ V_{GS}=-4.5V
- Advanced Trench Technology
- Excellent $R_{DS(ON)}$ and Low Gate Charge
- Lead free product is acquired

Application

- Load/Power Switching
- Interfacing Switching
- Logic Level Shift

Package and Pin Configuration

SOT-23

Circuit diagram



Marking:



"P" is TECHPUBLIC LOGO
"5P" is Part number,fixed
"xx" is internal code

Absolute Maximum Ratings (T_A=25℃unless otherwise noted)

Parameter		Symbol	Limit	Unit
Drain-Source Voltage		V_{DS}	-20	V
Gate-Source Voltage		V_{GS}	±12	V
Continuous Drain Current	T_C =25℃	I_D	-4.1	A
	T_C =70℃		-3.2	
	T_A =25℃		-3	
	T_A =70℃		-2.3	
Drain Current -Pulsed (Note 1)		I_{DM}	-15	A
Maximum Power Dissipation		P_D	1.7	W
Operating Junction and Storage Temperature Range		T_J,T_{STG}	-55 To 150	℃

Thermal Characteristic

Thermal Resistance,Junction-to-Ambient (Note 2)	$R_{\theta JA}$	74	℃/W

Electrical Characteristics (T_A=25℃unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Off Characteristics						
Drain-Source Breakdown Voltage	BV_{DSS}	V_{GS}=0V I_D=-250μA	-20	-	-	V
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS}=-20V,V_{GS}=0V	-	-	-1	μA
Gate-Body Leakage Current	I_{GSS}	V_{GS}=±12V,V_{DS}=0V	-	-	±100	nA
On Characteristics (Note 3)						
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS}=V_{GS},I_D=-250μA	-0.45	-0.7	-1.0	V
Drain-Source On-State Resistance	$R_{DS(ON)}$	V_{GS}=-4.5V, I_D=-4.1A	-	39	52	mΩ
		V_{GS}=-2.5V, I_D=-3A	-	58	75	
Forward Transconductance	g_{FS}	V_{DS}=-5V,I_D=-2A	6	-	-	S
Dynamic Characteristics (Note4)						
Input Capacitance	C_{Iss}	V_{DS}=-4V,V_{GS}=0V, F=1.0MHz	-	740	-	PF
Output Capacitance	C_{oss}		-	290	-	PF
Reverse Transfer Capacitance	C_{rss}		-	190	-	PF
Switching Characteristics (Note 4)						
Turn-on Delay Time	$t_{d(on)}$	V_{DD}=-4V,I_D=-3.3A , R_L=-1.2Ω,V_{GEN}=-4.5V,R_g=1Ω	-	12	-	nS
Turn-on Rise Time	t_r		-	35	-	nS
Turn-Off Delay Time	$t_{d(off)}$		-	30	-	nS
Turn-Off Fall Time	t_f		-	10	-	nS
Total Gate Charge	Q_g	V_{DS}=-4V,I_D=-4.1A,V_{GS}=-4.5V	-	7.8	-	nC
Gate-Source Charge	Q_{gs}		-	1.2	-	nC
Gate-Drain Charge	Q_{gd}		-	1.6	-	nC
Drain-Source Diode Characteristics						
Diode Forward Voltage (Note 3)	V_{SD}	V_{GS}=0V,I_S=-1.6A	-	-	-1.2	V
Diode Forward Current (Note 2)	I_S		-	-	1.6	A

Typical Electrical and Thermal Characteristics



Figure 1:Switching Test Circuit



Figure 2:Switching Waveforms



Figure 3 Power Dissipation



Figure 4 Drain Current



Figure 5 Output Characteristics



Figure 6 Drain-Source On-Resistance



Figure 7 Transfer Characteristics



Figure 8 Drain-Source On-Resistance



Figure 9 Rdson vs Vgs



Figure 10 Capacitance vs Vds



Figure 11 Gate Charge



Figure 12 Source- Drain Diode Forward



Figure 13 Safe Operation Area



Figure 14 Normalized Maximum Transient Thermal Impedance

SOT-23 Package Information



Symbol	Dimensions in Millimeters	
	MIN.	MAX.
A	0.900	1.150
A1	0.000	0.100
A2	0.900	1.050
b	0.300	0.500
c	0.080	0.150
D	2.800	3.000
E	1.200	1.400
E1	2.250	2.550
e	0.950TYP	
e1	1.800	2.000
L	0.550REF	
L1	0.300	0.500
θ	0°	8°