ADELS contact

## Screw Connectors

# 230/11 GW



Terminal Block, 11 pole, Insulating Material: PA 6-GW, Cross-Section: 2.5 mm², Pin Spacing: 8.0 mm, Fixing: Screw, Voltage Rating: 450 V, Current Rating: 24 A

## Order Info

| | |
|---|---|
| **Reference Number (ref. no.)** | 1212GB |
| **Applications** | Lighting, Installation, Electrical Appliances |
| **PU** | 0 |

## Type

| | |
|---|---|
| **Type** | Terminal Block |
| **Number of poles** | 11 pole |
| **Clamping Units per Pole** | 1 |
| **Colour** | white |
| **Cross-Section** | 2.5 mm² |
| **Connection Type** | Screw |

## Technical Data

| | |
|---|---|
| **Voltage Rating** | 450 V |
| **Current Rating** | 24 A |
| **Insulating Material** | PA 6-GW |
| **Contact Material** | Brass |
| **Core Cross-Section min.** | 0.5 mm² |
| **Core Cross-Section max.** | 4.0 mm² |
| **Flammability Rating** | V-2 |
| **max. Ambient Temperature Operation** | 85 °C |
| **Type of Conductor Solid** | yes |
| **Type of Conductor Flexible** | yes |
| **Type of Conductor Stranded** | yes |
| **Stripping Length** | 5.0-5.5 mm |
| **Assembly Contact Screw** | 0.8x4.0 / ↻ 0.5 Nm |
| **Pin Spacing** | 8.0 mm |
| **Fixing** | Screw |
| **Approbation EN60998** | 200_230_EN60998_20012012_VDE_ENEC_40034813_web.pdf |
| **Approbation UL** | 230_19820924_20120103_UL_E63492_1-02_Description_web.pdf |
| **Approbation CSA** | Schraub_Steck_Schraubenlos_SI_Klemmen_20160429_CSA_700765 |

## Accessories

| | |
|---|---|
| **ZEL 110** | 196420 |