


SAW Bandpass Filter 250910B



1. Features

- IF Bandpass Filter
- High Attenuation
- Single-Ended Operation
- DIP Package
- Maximum Storage Temperature Range : -40℃ ~ 85℃
- Electrostatics Sensitive Device (ESD)

2. Package Dimension



Package : D3512

Dimensions shown are nominal in millimeters

Base : Fe(SPCC), Au plating over Ni plated

Cap : Cu & Cr Alloy, Ni Plated

Termination : Kovar, Au Plated

Pin Configuration	
1	Input
5	Output
2, 4	Ground
3, 6	Case ground

 Integrated Technology Future	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809		Part No.	250910B
			Rev. Date	2008-10-30
			Rev.	NM8062-CS01 1/5

SAW Bandpass Filter 250910B



3. Specifications

Fo = 145.0 MHz

Terminating source impedance : 50Ω and matching network

Terminating load impedance : 50Ω and matching network

		Minimum	Typical	Maximum
Center Frequency	MHz	-	145.0	-
Insertion Loss	dB	-	25.3	27.0
1dB Bandwidth	MHz	9.1	9.2	-
3dB Bandwidth	MHz	-	9.4	-
40dB Bandwidth	MHz	-	10.18	10.25
Amplitude Ripple (fo ± 4.52 MHz)	dB	-	0.65	2.0
Group Delay Variation (fo ± 4.52 MHz)	nsec	-	60	150
Absolute Delay	usec	-	4.32	-
Ultimate Rejection	dB	50	52	-
Relative Attenuation				
Fo ± 5.1MHz	dB	27	42	-
Temperature Coefficient of Frequency	ppm/°C	-	-18	-

Notes :

- 1) All specifications are based on the matching schematic shown below
- 2) All specifications are measured by Agilent Network analyzer and full 2 port calibration at room temperature
- 3) All attenuation measurements are measured relative to insertion loss


 Integrated Technology Future	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	250910B	
		Rev. Date	2008-10-30	
		Rev.	NM8062-CS01	2/5

SAW Bandpass Filter 250910B



4. Matching Schematic

(Actual matching values may vary due to PCB layout and parasitics)



$$L1 = L2 = 27\text{nH}$$

$$C1 = C2 = 43\text{pF}$$

5. Marking Configuration

ITF¹⁾08A001²⁾

250910B³⁾

145⁴⁾-9.2M⁵⁾

1) Manufacturer name

2) Lot Number

3) Part Number

4) Center frequency



5) 1dB-Bandwidth

 Integrated Technology Future	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	250910B	
		Rev. Date	2008-10-30	
		Rev.	NM8062-CS01	3/5

SAW Bandpass Filter 250910B



6. Typical Performance (at +25°C)



ITF Co., Ltd.
102-901, Bucheon Technopark 364,
Samjeong-Dong, Ojeong-Gu, Bucheon-City,
Gyeonggi-Do, Korea 421-809

Part No.

250910B

Rev. Date





2008-10-30

Rev.

NM8062-CS01

4/5

SAW Bandpass Filter 250910B



ITF Co., Ltd.
102-901, Bucheon Technopark 364,
Samjeong-Dong, Ojeong-Gu, Bucheon-City,
Gyeonggi-Do, Korea 421-809

Part No.

250910B

Rev. Date

2008-10-30

Rev.

NM8062-CS01

5/5