PMV32UP

20 V, 4 A P-channel Trench MOSFET

至尚臻品

1. Product profile

1.1 General description

P-channel enhancement mode Field-Effect Transistor (FET) in a small SOT23 (TO-236AB) Surface-Mounted Device (SMD) plastic package using Trench MOSFET technology.

1.2 Features and benefits

- 1.8 V drain-source on-state resistance rated
- Very fast switching
- Trench MOSFET technology

1.3 Applications

- Relay driver
- High-side loadswitch
- High-speed line driver
- Switching circuits

1.4 Quick reference data



Table 1. Quick reference data

Symbol	Parameter	Conditions		Min	Typ	Max	Unit
V_{DS}	drain-source voltage	T_j = 25 °C		-	-	-20	V
V_{GS}	gate-source voltage			-8	-	8	V
I_D	drain current	V_{GS} = -4.5 V; T_{amb} = 25 °C	[1]	-	-	-4	A
Static characteristics							
R_{DSon}	drain-source on-state resistance	V_{GS} = -4.5 V; I_D = -2.4 A; T_j = 25 °C		-	32	36	mΩ

[1] Device mounted on an FR4 Printed-Circuit Board (PCB), single-sided copper, tin-plated, mounting pad for drain 6 cm^2.

2. Pinning information

Table 2. Pinning information

Pin	Symbol	Description	Simplified outline	Graphic symbol
1	G	gate		
2	S	source		
3	D	drain		

SOT23 (TO-236AB)

017aaa094

3. Ordering information

Table 3. Ordering information

Type number	Package		
	Name	Description	Version
PMV32UP	TO-236AB	plastic surface-mounted package; 3 leads	SOT23

4. Marking

Table 4. Marking codes

Type number	Marking code[1]
PMV32UP	NF%

[1] % = placeholder for manufacturing site code

5. Limiting values

Table 5. Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134).

Symbol	Parameter	Conditions		Min	Max	Unit
V_{DS}	drain-source voltage	T_j = 25 °C		-	-20	V
V_{GS}	gate-source voltage			-8	8	V
I_D	drain current	V_{GS} = -4.5 V; T_{amb} = 25 °C	[1]	-	-4	A
		V_{GS} = -4.5 V; T_{amb} = 100 °C	[1]	-	-2.5	A
I_{DM}	peak drain current	T_{amb} = 25 °C; single pulse; $t_p \leq 10$ µs		-	-16	A
P_{tot}	total power dissipation	T_{amb} = 25 °C	[2]	-	510	mW
			[1]	-	930	mW
		T_{sp} = 25 °C		-	4150	mW
T_j	junction temperature			-55	150	°C
T_{amb}	ambient temperature			-55	150	°C
T_{stg}	storage temperature			-65	150	°C
Source-drain diode						
I_S	source current	T_{amb} = 25 °C	[1]	-	-1	A

[1] Device mounted on an FR4 Printed-Circuit Board (PCB), single-sided copper, tin-plated, mounting pad for drain 6 cm^2.

[2] Device mounted on an FR4 PCB, single-sided copper, tin-plated and standard footprint.

6. Thermal characteristics

Table 6. Thermal characteristics

Symbol	Parameter	Conditions		Min	Typ	Max	Unit
$R_{th(j-a)}$	thermal resistance from junction to ambient	in free air	[1]	-	207	245	K/W
			[2]	-	117	135	K/W
$R_{th(j-sp)}$	thermal resistance from junction to solder point			-	25	30	K/W

[1] Device mounted on an FR4 PCB, single-sided copper, tin-plated and standard footprint.

[2] Device mounted on an FR4 PCB, single-sided copper, tin-plated, mounting pad for drain 6 cm^2.

7. Characteristics

Table 7. Characteristics

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Static characteristics						
$V_{(BR)DSS}$	drain-source breakdown voltage	I_D = -250 µA; V_{GS} = 0 V; T_j = 25 °C	-20	-	-	V
V_{GSth}	gate-source threshold voltage	I_D = -250 µA; V_{DS} = V_{GS}; T_j = 25 °C	-0.45	-0.7	-0.95	V
I_{DSS}	drain leakage current	V_{DS} = -20 V; V_{GS} = 0 V; T_j = 25 °C	-	-	-1	µA
		V_{DS} = -20 V; V_{GS} = 0 V; T_j = 150 °C	-	-	-10	µA
I_{GSS}	gate leakage current	V_{GS} = -8 V; V_{DS} = 0 V; T_j = 25 °C	-	-	-100	nA
R_{DSon}	drain-source on-state resistance	V_{GS} = -4.5 V; I_D = -2.4 A; T_j = 25 °C	-	32	36	mΩ
		V_{GS} = -4.5 V; I_D = -2.4 A; T_j = 150 °C	-	46	53	mΩ
		V_{GS} = -2.5 V; I_D = -2.0 A; T_j = 25 °C	-	40	46	mΩ
		V_{GS} = -1.8 V; I_D = -1.8 A; T_j = 25 °C	-	55	73	mΩ
g_{fs}	forward transconductance	V_{DS} = -5 V; I_D = -2.4 A; T_j = 25 °C	-	13	-	S
Dynamic characteristics						
$Q_{G(tot)}$	total gate charge	I_D = -1 A; V_{DS} = -10 V; V_{GS} = -4.5 V; T_j = 25 °C	-	15.5	-	nC
Q_{GS}	gate-source charge		-	2.7	-	nC
Q_{GD}	gate-drain charge		-	2.2	-	nC
C_{iss}	input capacitance	V_{GS} = 0 V; V_{DS} = -10 V; f = 1 MHz; T_j = 25 °C	-	1890	-	pF
C_{oss}	output capacitance		-	175	-	pF
C_{rss}	reverse transfer capacitance		-	112	-	pF
$t_{d(on)}$	turn-on delay time	V_{DS} = -10 V; V_{GS} = -5 V; $R_{G(ext)}$ = 6 Ω; T_j = 25 °C; I_D = -1 A	-	13	-	ns
t_r	rise time		-	21	-	ns
$t_{d(off)}$	turn-off delay time		-	95	-	ns
t_f	fall time		-	33	-	ns
Source-drain diode						
V_{SD}	source-drain voltage	I_S = -2.4 A; V_{GS} = 0 V; T_j = 25 °C	-	-0.75	-1	V