

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0788601585

Status:

Active

Overview:

DDR4 DIMM Sockets

Description:

DDR4 DIMM Socket, Ultra-Low-Profile, Vertical Through-Hole, 0.381µm Gold Plating, 288 Circuits, PCB Thickness 2.36mm, 2.95mm Tail Length, Natural (Off White) Housing, Natural (Off White) Latch



Series image - Reference only

Documents:

Drawing (PDF)

RoHS Certificate of Compliance (PDF)

Agency Certification	
CSA	LR19980
UL	E29179
General	
Product Family	Memory Module Sockets
Series	78860
Comments	Natural (Off-White) Housing and Latch
Component Type	Socket
Electrical Model	Yes
JEDEC Outline	MO-309
Overview	DDR4 DIMM Sockets
Product Name	DDR4 DIMM
UPC	887191603643
Physical	
Circuits (Loaded)	288
Circuits (maximum)	288
Color - Resin	Natural (Off White)
Durability (mating cycles max)	25
Entry Angle	Vertical (Top Entry)
Flammability	94V-0
Keying to Mating Part	Yes
Material - Metal	Copper Alloy
Material - Plating Mating	Gold over Nickel
Material - Plating Termination	Matte Tin
Material - Resin	Nylon
Net Weight	5.297/g
PC Tail Length	2.95mm
PCB Locator	Yes
PCB Retention	Yes
PCB Thickness - Recommended	2.36mm
Packaging Type	Tray
Pitch - Mating Interface	0.85mm
Pitch - Termination Interface	0.85mm
Plating min - Mating	0.381µm
Plating min - Termination	2.540µm
Temperature Range - Operating	-55°C to +85°C
Termination Interface: Style	Through Hole
Electrical	
Current - Maximum per Contact	0.75A
Voltage - Maximum	29V AC (RMS)/DC
Solder Process Data	
Duration at Max. Process Temperature (seconds)	005
Lead-freeProcess Capability	SMC&WAVE
Max. Cycles at Max. Process Temperature	002

EU ELV

Not Relevant

EU RoHS

China RoHS

Compliant

REACH SVHC

Contains SVHC(2015

June 15): No

Halogen-Free

Status

Low-Halogen

Need more information on product

environmental compliance?

Email productcompliance@molex.com

Please visit the [Contact Us](#) section for any

non-product compliance questions.

China ROHS

Green Image

ELV

Not Relevant

Search Parts in this Series

78860 Series

Process Temperature max. C

260

Material Info

Reference - Drawing Numbers

Electrical Model Document	EE-78860-002
Product Specification	RPS-78860-001
S-Parameter Model	SP-78860-002
Sales Drawing	SD-78860-001

This document was generated on 10/21/2015

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION