


Outgassing Compliant Power Inductors AE512PYA



- High temperature materials allow operation in ambient temperatures up to 155°C
- Passes NASA low outgassing specifications
- Tin-lead (Sn-Pb) termination for the best possible board adhesion
- Passes vibration testing to 80 G and shock testing to 1000 G
- Exceptionally low DCR; soft saturation

Terminations Tin-lead (63/37) over copper.

Core material Composite

Weight 0.6 – 0.7 g

Ambient temperature –55°C to +105°C with Irms current, +105°C to +155°C with derated current

Storage temperature Component: –55°C to +155°C.
Tape and reel packaging: –55°C to +80°C

Resistance to soldering heat Max three 40 second reflows at +260°C, parts cooled to room temperature between cycles

Moisture Sensitivity Level (MSL) 1 (unlimited floor life at <30°C / 85% relative humidity)

Enhanced crush-resistant packaging 400/7" reel
Plastic tape: 16 mm wide, 0.3 mm thick, 12 mm pocket spacing, 3.12 mm pocket depth

Part number ¹	Inductance ² ±20% (μH)	DCR (mOhms) ³		SRF (MHz) ⁴		Isat (A) ⁵	Irms (A) ⁶	
		typ	max	min	typ		20°C rise	40°C rise
AE512PYA181MSZ	0.18	1.59	1.75	113	141	39	18.0	24.0
AE512PYA331MSZ	0.33	2.30	2.53	71	89	30	15.0	18.8
AE512PYA561MSZ	0.56	3.01	3.31	49	61	29	12.0	16.5
AE512PYA102MSZ	1.0	5.62	6.18	40	50	23	9.8	13.5
AE512PYA122MSZ	1.2	6.82	7.50	34	43	22	9.0	12.0
AE512PYA182MSZ	1.8	9.57	10.52	27	34	18.2	7.6	10.5
AE512PYA222MSZ	2.2	12.70	13.97	24	30	15.9	5.3	7.5
AE512PYA332MSZ	3.3	19.92	20.81	21	26	12.2	4.5	6.0

1. When ordering, please specify **testing** code:

AE512PYA332MSZ

Testing: Z = COTS

H = Screening per Coilcraft CP-SA-10001

N = Screening per Coilcraft CP-SA-10004

2. Inductance tested at 100 kHz, 0.1 Vrms, 0 Adc.

3. DCR measured on a micro-ohmmeter.

4. SRF measured using an Agilent/HP 4395A or equivalent.

5. Typical dc current at which the inductance drops 30% from its value without current.

6. Typical current that causes the specified temperature rise from 25°C ambient.

7. Electrical specifications at 25°C.

Refer to Doc 362 "Soldering Surface Mount Components" before soldering.









Irms Testing

Irms testing was performed on a 0.060" thick pcb with 4 oz. copper traces optimized to minimize additional temperature rise.

Temperature rise is highly dependent on many factors including pcb land pattern, trace size, and proximity to other components. Therefore temperature rise should be verified in application conditions.


AE512PYA Series

L vs Current







AE512PYA Series

L vs Frequency



Irms Derating



Dimensions are in $\frac{\text{inches}}{\text{mm}}$

Dash number	A ± 0.008 in ± 0.20 mm (in / mm)	B (in / mm)
-181	0.213 / 5.42	0.224 / 5.69
-331	0.213 / 5.42	0.224 / 5.69
-561	0.213 / 5.42	0.224 / 5.69
-102	0.206 / 5.24	0.213 / 5.42
-122	0.206 / 5.24	0.213 / 5.42
-182	0.204 / 5.18	0.210 / 5.33
-222	0.201 / 5.12	0.206 / 5.24
-332	0.200 / 5.08	0.204 / 5.18

Suggested Land Pattern

