2SD1824

Silicon NPN epitaxial planer type

For low-frequency amplification



Marking symbol : 1V

Features

- High foward current transfer ratio h_{FE}.
- Low collector to emitter saturation voltage $V_{CE(sat)}$.
- High emitter to base voltage V_{EBO}.
- S-Mini type package, allowing downsizing of the equipment and automatic insertion through the tape packing and the magazine packing.

Absolute Maximum Ratings (Ta=25˚C)

Parameter	Symbol	Ratings	Unit
Collector to base voltage	V_{CBO}	100	V
Collector to emitter voltage	V_{CEO}	100	V
Emitter to base voltage	V_{EBO}	15	V
Peak collector current	I_{CP}	50	mA
Collector current	I_C	20	mA
Collector power dissipation	P_C	150	mW
Junction temperature	T_j	150	˚C
Storage temperature	T_{stg}	–55 ~ +150	˚C

Electrical Characteristics (Ta=25˚C)

Parameter	Symbol	Conditions	min	typ	max	Unit
Collector cutoff current	I_{CBO}	V_{CB} = 60V, I_E = 0			100	nA
	I_{CEO}	V_{CE} = 60V, I_B = 0			1	μA
Collector to base voltage	V_{CBO}	I_C = 10μA, I_E = 0	100			V
Collector to emitter voltage	V_{CEO}	I_C = 1mA, I_B = 0	100			V
Emitter to base voltage	V_{EBO}	I_E = 10μA, I_C = 0	15			V
Forward current transfer ratio	h_{FE}^*	V_{CE} = 10V, I_C = 2mA	400		1200	
Collector to emitter saturation voltage	$V_{CE(sat)}$	I_C = 10mA, I_B = 1mA		0.05	0.2	V
Transition frequency	f_T	V_{CB} = 10V, I_E = –2mA, f = 200MHz		90		MHz

*h_{FE} Rank classification

Rank	R	S
h_{FE}	400 ~ 800	600 ~ 1200
Marking Symbol	1VR	1VS

P_C — Ta



I_C — V_{CE}



I_C — V_{BE}



$V_{CE(sat)}$ — I_C



h_{FE} — I_C



f_T — I_E



C_{ob} — V_{CB}



NV — I_C



NV — V_{CE}