





Recommended P.C.B Layout
P.C.B Board Tolerance±0.05

NOTES:

Voltage Rating:250V AC/DC
Current Rating:3.0A AC/DC
Dielectric Withstand Voltage:500V AC/minute
Contact Voltage:20M Max.
Insulation Voltage:1000M Min
Operation temperature:-40 °C to +105 °C
Insulator Material:Polyester.UL94V-0
Contact Material:Brass
Contact Plating:AuorSn Plated on Nickel Overall



| | | | | |
|-------------|-----|-----|-----|------|
| 塑胶高度可选 (mm) | 常用 | | | |
| H | 1.0 | 1.5 | 2.0 | 2.54 |

| Dimension antitheses list | | | | |
|---------------------------|------|-----|------|-------|
| item | PA | --- | PC | L |
| Standard | 6.00 | --- | 3.00 | 11.50 |
| Alternate | --- | --- | --- | --- |

| | | | |
|-----|--------------|------|------|
| AO | MODIFICATION | DRAW | DATE |
| VER | | | |

| | | | |
|----------------------------|-------|-------|-------|
| TOLERANCE UNLESS OTHERWISE | | | |
| X. | ±0.30 | X° | ±5° |
| .X | ±0.20 | .X° | ±2° |
| .XX | ±0.08 | .XX° | ±1° |
| .XXX | ±0.03 | .XXX° | ±0.5° |

| | | |
|--------------|------------------------------|---|
| DRAWN | CK tan | XFCN 兴飞连接器有限公司 CONNECTORS XFCN CONNECTORS CO., LTD. |
| CHKD | | |
| APPD | | |
| VIEW | | |
| PRODUCT NAME | 2.54mm Pin Header Connectors | |
| PART. NO. | PZ254V-12-XX | |

| | |
|----------|-------------|
| SHEET | 1/1 |
| DATE | 2010. 4. 12 |
| UNITS | mm |
| SCALE | 1:1 |
| DWG. NO. | 009 |