



Recommended P.C.B Layout

MATERIAL

Contact Pin : Brass

SPECIFICATION

Current Rate : 2.5 AMP  
 Dielectric voltage : 250V AC for one minute  
 Insulation Resistance : 1000MΩMin.  
 Contact Resistance : 20mΩMax

744-8 1-04 T W 00  
 1 2 3 4 5

1. 8: Green Product
2. No. of contacts per row
3. G: Gold flash  
S: Selective  
T: Tin plated
4. W: Nature Color Insulator
5. Pinrex internal code.

				UNITS : mm		OLD PART NO.	TITLE	頻銳科技股份有限公司 PINREX TECHNOLOGY CORP.
C	增加塑高尺寸2.55	2012/07/19	TOLERANCE .0 =±.50 .00 =±.30 .000 =±.XXX .0000=±. ANG.=±3'	SCALE NONE	SIZE A4	DRAWER 尹小姜	2.54mm WIRE TO BOARD HEADER DIP 180° TYPE	
B	增加缺口	2011/11/30				CHECK		
A	RELEASE	2006/11/07				APP'D	NEW PART NO. 744-81-04TW00	744-81-04TW00(C版)
REV.	DESCRIPTION	DATE				SHEET 1 OF 1	REV. C	