

# MINIATURE RELAY

## 1 POLE—1 to 2 A (FOR SIGNAL SWITCHING)

### FBR211 SERIES

RoHS compliant



#### ■ FEATURES

- 2 A maximum carrying current  
Capable of 2 A maximum continuous carrying current in the contact
- Superior reliability gold-overlay contacts  
P type: Gold-overlay silver-palladium contacts
- International terminal pitch of one inch grid terminal layout
- High sensitivity, low power dissipation types also available  
Standard types: 0.45 W (A or B type)  
High sensitivity types: 0.2 W (C or E type)
- Conforms to FCC 68.302 (high dielectric strength type)
- UL recognized (File number E63615)
- CSA recognized (File number LR64026)
- RoHS compliant since date code: 0433A  
Please see page 5 for more information



#### ■ ORDERING INFORMATION

[Example]      FBR211   S   A   D012   U   –   P   2   (–CSA)  
                    (a)   (b)   (c)   (d)   (e)   (f)   (g)   (h)

|     |                           |                                                                                                                                                                      |
|-----|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| (a) | Series Name               | FBR211                                                                                                                                                               |
| (b) | Enclosure                 | S: Flux free type<br>N: Plastic sealed type                                                                                                                          |
| (c) | Coil Power and Schematics | A: Standard A type } (nominal power 450 mW type)<br>B: Standard B type }<br>C: High sensitivity C type } (nominal power 200 mW type)<br>E: High sensitivity E type } |
| (d) | Nominal Voltage           | (Example) D003: 3 VDC<br>D012: 12 VDC (refer to the COIL DATA CHART)                                                                                                 |
| (e) | UL Marking on Cover       | Nil : No UL marking<br>U : UL marking                                                                                                                                |
| (f) | Contact Material          | P : Gold-overlay silver-palladium<br>M : Gold-overlay silver                                                                                                         |
| (g) | Special Type              | Nil : Standard<br>2 : High dielectric strength type                                                                                                                  |
| (h) | CSA Marking               | Nil : Standard<br>–CSA : UL + CSA marking (valid when (e) is U)                                                                                                      |

Note: The designation name is stamped on the top of the relay case as follows:  
(Example) Designation ordered: FBR211SAD005-P  
Stamp: 211SAD005-P

# FBR211 SERIES

## ■ COIL DATA CHART

### 1. STANDARD (A or B type)

| MODEL          |                |                |                | Nominal voltage | Coil resistance (±10%) | Nominal current (at nominal voltage) approx. | Must operate voltage        | Must release voltage        | Maximum allowable voltage | Nominal power                       | Coil temperature rise               |
|----------------|----------------|----------------|----------------|-----------------|------------------------|----------------------------------------------|-----------------------------|-----------------------------|---------------------------|-------------------------------------|-------------------------------------|
| A type         |                | B type         |                |                 |                        |                                              |                             |                             |                           |                                     |                                     |
| Flux free      | Plastic sealed | Flux free      | Plastic sealed |                 |                        |                                              |                             |                             |                           |                                     |                                     |
| FBR211SAD001-n | FBR211NAD001-n | FBR211SBD001-n | FBR211NBD001-n | 1.5 VDC         | 5 Ω                    | 300 mA                                       | 70% max. of nominal voltage | 10% min. of nominal voltage | 150% of nominal voltage   | Approx. 450 mW (at nominal voltage) | Approx. 45 deg (at nominal voltage) |
| FBR211SAD003-n | FBR211NAD003-n | FBR211SBD003-n | FBR211NBD003-n | 3 VDC           | 20 Ω                   | 150 mA                                       |                             |                             |                           |                                     |                                     |
| FBR211SAD005-n | FBR211NAD005-n | FBR211SBD005-n | FBR211NBD005-n | 5 VDC           | 56 Ω                   | 89 mA                                        |                             |                             |                           |                                     |                                     |
| FBR211SAD006-n | FBR211NAD006-n | FBR211SBD006-n | FBR211NBD006-n | 6 VDC           | 80 Ω                   | 75 mA                                        |                             |                             |                           |                                     |                                     |
| FBR211SAD009-n | FBR211NAD009-n | FBR211SBD009-n | FBR211NBD009-n | 9 VDC           | 180 Ω                  | 50 mA                                        |                             |                             |                           |                                     |                                     |
| FBR211SAD012-n | FBR211NAD012-n | FBR211SBD012-n | FBR211NBD012-n | 12 VDC          | 320 Ω                  | 38 mA                                        |                             |                             |                           |                                     |                                     |
| FBR211SAD024-n | FBR211NAD024-n | FBR211SBD024-n | FBR211NBD024-n | 24 VDC          | 1,280 Ω                | 19 mA                                        |                             |                             |                           |                                     |                                     |

Note: All values in the table are measured at 20°C.

### 2. HIGH SENSITIVITY (C or E type)

| MODEL          |                |                |                | Nominal voltage | Coil resistance (±10%) | Nominal current (at nominal voltage) approx. | Must operate voltage        | Must release voltage        | Maximum allowable voltage | Nominal power                       | Coil temperature rise               |
|----------------|----------------|----------------|----------------|-----------------|------------------------|----------------------------------------------|-----------------------------|-----------------------------|---------------------------|-------------------------------------|-------------------------------------|
| C type         |                | E type         |                |                 |                        |                                              |                             |                             |                           |                                     |                                     |
| Flux free      | Plastic sealed | Flux free      | Plastic sealed |                 |                        |                                              |                             |                             |                           |                                     |                                     |
| FBR211SCD001-n | FBR211NCD001-n | FBR211SED001-n | FBR211NED001-n | 1.5 VDC         | 12 Ω                   | 125 mA                                       | 70% max. of nominal voltage | 10% min. of nominal voltage | 225% of nominal voltage   | Approx. 200 mW (at nominal voltage) | Approx. 25 deg (at nominal voltage) |
| FBR211SCD003-n | FBR211NCD003-n | FBR211SED003-n | FBR211NED003-n | 3 VDC           | 45 Ω                   | 67 mA                                        |                             |                             |                           |                                     |                                     |
| FBR211SCD005-n | FBR211NCD005-n | FBR211SED005-n | FBR211NED005-n | 5 VDC           | 120 Ω                  | 42 mA                                        |                             |                             |                           |                                     |                                     |
| FBR211SCD006-n | FBR211NCD006-n | FBR211SED006-n | FBR211NED006-n | 6 VDC           | 180 Ω                  | 33 mA                                        |                             |                             |                           |                                     |                                     |
| FBR211SCD009-n | FBR211NCD009-n | FBR211SED009-n | FBR211NED009-n | 9 VDC           | 400 Ω                  | 23 mA                                        |                             |                             |                           |                                     |                                     |
| FBR211SCD012-n | FBR211NCD012-n | FBR211SED012-n | FBR211NED012-n | 12 VDC          | 700 Ω                  | 17 mA                                        |                             |                             |                           |                                     |                                     |
| FBR211SCD024-n | FBR211NCD024-n | FBR211SED024-n | FBR211NED024-n | 24 VDC          | 2,800 Ω                | 9 mA                                         |                             |                             |                           |                                     |                                     |

Note: All values in the table are measured at 20°C.

## ■ SPECIFICATIONS

| Item       |                                             | Standard (A or B type)                                                                                                                                                                                                       | High sensitive (C or E type)                                                              |
|------------|---------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------|
| Contact    | Arrangement                                 | 1 form C (SPDT)                                                                                                                                                                                                              |                                                                                           |
|            | Material                                    | Gold-overlay silver-palladium / gold-overlay silver                                                                                                                                                                          |                                                                                           |
|            | Resistance (initial)                        | Maximum 100 mΩ (at 0.1 A 6 VDC)                                                                                                                                                                                              |                                                                                           |
|            | Rating (resistive)                          | 0.5 A 120 VAC or 1 A 28 VDC                                                                                                                                                                                                  |                                                                                           |
|            | Maximum Carrying Current                    | 2 A                                                                                                                                                                                                                          |                                                                                           |
|            | Maximum Switching Power                     | 60 VA or 28 W                                                                                                                                                                                                                |                                                                                           |
|            | Max. Switching Voltage*1                    | 220 VAC or 150 VDC                                                                                                                                                                                                           |                                                                                           |
|            | Maximum Switching Current                   | 1.25 A (AC) or 2 A (DC)                                                                                                                                                                                                      |                                                                                           |
|            | Minimum Switching load*2 (reference)        | Plastic sealed 1 mA, 1V<br>Flux free 1 mA, 5V                                                                                                                                                                                |                                                                                           |
| Coil       | Nominal Power (at 20°C)                     | Approximately 450 mW                                                                                                                                                                                                         | Approximately 200 mW                                                                      |
|            | Operate Power (at 20°C)                     | Approximately 315 mW maximum                                                                                                                                                                                                 | Approximately 140 mW maximum                                                              |
|            | Operating Temperature                       | −25°C to +55°C (no frost)                                                                                                                                                                                                    | −25°C to +75°C (no frost)                                                                 |
|            | Operating Humidity                          | 45 to 85%RH                                                                                                                                                                                                                  |                                                                                           |
| Time Value | Operate (at nominal voltage)                | Maximum 5 ms                                                                                                                                                                                                                 |                                                                                           |
|            | Release (at nominal voltage)                | Maximum 5 ms                                                                                                                                                                                                                 |                                                                                           |
| Life       | Mechanical                                  | 5 × 10 <sup>6</sup> operations minimum                                                                                                                                                                                       |                                                                                           |
|            | Electrical<br>(Refer to the REFERENCE DATA) | 3 × 10 <sup>5</sup> operations minimum (at 1 A/ 28 VDC resistive load)<br>1 × 10 <sup>5</sup> operations minimum (at 2 A/ 12 VDC resistive load)<br>1 × 10 <sup>5</sup> operations minimum (at 0.5 A/120 VDC resistive load) |                                                                                           |
| Other      | Vibration Resistance                        |                                                                                                                                                                                                                              | 10 to 55 Hz (double amplitude of 1.5 mm)                                                  |
|            | Shock Resistance                            | Misoperation                                                                                                                                                                                                                 | 100 m/s <sup>2</sup> (11± <sup>1</sup> ms)      60 m/s <sup>2</sup> (11± <sup>1</sup> ms) |
|            |                                             | Endurance                                                                                                                                                                                                                    | 1,000 m/s <sup>2</sup> (11± <sup>1</sup> ms)                                              |
|            | Weight                                      |                                                                                                                                                                                                                              | Approximately 4 g                                                                         |

\*1 If the switching voltage exceeds the rated contact voltage, reduce the current. The current values vary according to the type of load.

\*2 Values when switching a resistive load at normal room temperature and humidity and in a clean environment. The minimum switching load varies with the switching frequency and operation environment.

## ■ INSULATION


| Item                |  | Standard (A or B)                                 | High sensitive (C or E) |
|---------------------|--|---------------------------------------------------|-------------------------|
| Isolation (initial) |  | Minimum 100 MΩ (at 500VDC)                        |                         |
| Dielectric Strength |  | 500VAC 1 min. (standard)                          |                         |
|                     |  | 1,500VAC 1 min. (high isolation coil and contact) |                         |

## ■ SAFETY STANDARDS


| Type | Compliance                         | Contact rating                                                                         |
|------|------------------------------------|----------------------------------------------------------------------------------------|
| UL   | UL 110<br>E63615                   | Flammability: UL 94-V0 (plastics)<br>0.5A, 120VAC (resistive)<br>1A, 28VDC (resistive) |
| CSA  | C22.2 No. 14<br>LR 40304, LR 46016 |                                                                                        |

## CHARACTERISTIC DATA


Range of operation temperature and voltage  
(Standard 0.45 W type)




Range of operation temperature and voltage  
(high sensitive 0.2 W type)




Operate and release time data




Coil temperature rise data



Maximum switching capacity




Life curve




## REFERENCE DATA


Distribution of operate and release voltage



Distribution of operate and release time




Distribution of contact resistance



## ■ DIMENSIONS


### 1. STANDARD (Flux free type)

#### ●Dimensions




#### ●Schematics (BOTTOM VIEW)

(A type or C type)




(B type or E type)




### 2. N-TYPE (Plastic sealed type)

#### ●Dimensions




#### ●Schematics (BOTTOM VIEW)

(A type or C type)




(B type or E type)



### 3. PC BOARD MOUNTING HOLE LAYOUT

#### ●PC board mounting hole layout (BOTTOM VIEW)



Unit: mm

## RoHS Compliance and Lead Free Relay Information

### 1. General Information

- Relays produced after the specific date code that is indicated on each data sheet are lead-free now. Most of our signal and power relays are lead-free. Please refer to Lead-Free Status Info. (<http://www.fujitsu.com/us/downloads/MICRO/fcai/relays/lead-free-letter.pdf>)
- Lead free solder paste currently used in relays is Sn-3.0Ag-0.5Cu.
- All signal and most power relays also comply with RoHS. Please refer to individual data sheets. Relays that are RoHS compliant do not contain the 5 hazardous materials that are restricted by RoHS directive (lead, mercury, chromium IV, PBB, PBDE).
- It has been verified that using lead-free relays in leaded assembly process will not cause any problems (compatible).
- "LF" is marked on each outer and inner carton. (No marking on individual relays).
- To avoid leaded relays (for lead-free sample, etc.) please consult with area sales office.
- We will ship leaded relays as long as the leaded relay inventory exists.

Note: Cadmium was exempted from RoHS on October 21, 2005. (Amendment to Directive 2002/95/EC)

### 2. Recommended Lead Free Solder Profile

- Recommended solder paste Sn-3.0Ag-0.5Cu.

#### Reflow Solder condition

**Flow Solder condition:**

Pre-heating: maximum 120°C  
Soldering: dip within 5 sec. at  
260°C solder bath

**Solder by Soldering Iron:**

Soldering Iron  
Temperature: maximum 360°C  
Duration: maximum 3 sec.

**We highly recommend that you confirm your actual solder conditions**

### 3. Moisture Sensitivity

- Moisture Sensitivity Level standard is not applicable to electromechanical relays.

### 4. Tin Whisker

- Dipped SnAgCu solder is known as low risk tin whisker. No considerable length whisker was found by our in house test.

## Fujitsu Components International Headquarter Offices

### Japan

Fujitsu Component Limited  
Gotanda-Chuo Building  
3-5, Higashigotanda 2-chome, Shinagawa-ku  
Tokyo 141, Japan  
Tel: (81-3) 5449-7010  
Fax: (81-3) 5449-2626  
Email: [promothq@ft.ed.fujitsu.com](mailto:promothq@ft.ed.fujitsu.com)  
Web: [www.fcl.fujitsu.com](http://www.fcl.fujitsu.com)

### North and South America

Fujitsu Components America, Inc.  
250 E. Caribbean Drive  
Sunnyvale, CA 94089 U.S.A.  
Tel: (1-408) 745-4900  
Fax: (1-408) 745-4970  
Email: [components@us.fujitsu.com](mailto:components@us.fujitsu.com)  
Web: <http://www.fujitsu.com/us/services/edevices/components/>

### Europe

Fujitsu Components Europe B.V.  
Diamantlaan 25  
2132 WV Hoofddorp  
Netherlands  
Tel: (31-23) 5560910  
Fax: (31-23) 5560950  
Email: [info@fceu.fujitsu.com](mailto:info@fceu.fujitsu.com)  
Web: [emea.fujitsu.com/components/](http://emea.fujitsu.com/components/)

### Asia Pacific

Fujitsu Components Asia Ltd.  
102E Pasir Panjang Road  
#01-01 Citilink Warehouse Complex  
Singapore 118529  
Tel: (65) 6375-8560  
Fax: (65) 6273-3021  
Email: [fcal@fcal.fujitsu.com](mailto:fcal@fcal.fujitsu.com)  
Web: <http://www.fujitsu.com/sg/services/micro/components/>

©2009 Fujitsu Components America, Inc. All rights reserved. All trademarks or registered trademarks are the property of their respective owners.

Fujitsu Components America or its affiliates do not warrant that the content of datasheet is error free. In a continuing effort to improve our products Fujitsu Components America, Inc. or its affiliates reserve the right to change specifications/datasheets without prior notice.  
Rev. June 30, 2009.