Corrugated tube screw connection - HC-B-GCA-M32-PLRBK - 1412022

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



EVO corrugated pipe screw connection, size: M32, protection class: IP66, plastic

Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	80.0 g
Custom tariff number	39269097
Country of origin	Poland

Technical data

General

Assembly instructions	Please observe the installation note provided for the WP-PA HF-HB.....BK corrugated pipe

Ambient conditions

Ambient temperature (operation)	-40 °C ... 115 °C
Degree of protection	IP66

Classifications

eCl@ss

eCl@ss 5.1	27143424
eCl@ss 6.0	27261207
eCl@ss 8.0	27449290
eCl@ss 9.0	27440290

ETIM

ETIM 4.0	EC000441

Corrugated tube screw connection - HC-B-GCA-M32-PLRBK - 1412022

Classifications

ETIM

ETIM 5.0	EC000441

Approvals

Approvals

Approvals

EAC

Ex Approvals


Approvals submitted

Approval details

EAC

Drawings

Dimensional drawing



Dimensional drawing

Phoenix Contact 2016 © - all rights reserved
http://www.phoenixcontact.com