



Section A-A

NOTES:

MATERIAL

- 1. Insulator Material: PBT+30%GF(UL94V-0)
- 2. Contact Material : Brass
- 3. Contact Plating :
AWP xx-8241-T : Gold flash over Ni
AWP xx-8541-T : Tin over Ni

ELECTRICAL

- 1. Current Rating : 3AMP
- 2. Voltage Rating : 500V AC/DC
- 3. Withstand Voltage : 1000V AC/DC
- 4. Contact Resistance : 20mΩ max
- 5. Insulation Resistance: 1000MΩ min

ENVIRONMENTAL

- 1. Operation Temperature: -40°C to +105°C
- 2. Packing: Tray

RoHS compliant

| | | | | | | | | | |
|-----------|-------|-----|--------------|------------|------|----------|------------|---------|---|
| Scale | 1:1 | | | | | | Date | Name | Customer-No. |
| TOLERANCE | | | | | | Drawn | 25.01.2006 | Alex | |
| X.X | ±0.40 | | | | | Approved | 21.12.2009 | Hellwig | ASSMANN WSW-No. AWP xx-8x41-T |
| X.XX | ±0.25 | | | | | | | | Drawing-No. |
| X.XXX | ±0.15 | | | | | | | | ASS 2261 CO |
| Angle | ±3° | ② | Update | 21.12.2009 | Dean | | | | rev02 |
| | | ① | Drawn | 25.01.2006 | Alex | | | Replace | Sheet |
| | | Id. | Modification | Date | Name | | | | |



ASS 2261 CO rev02
Replace Sheet