Coupling - SC 4/ 1-L BU - 3042609

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://download.phoenixcontact.com)

The illustration shows various color versions of the article

Coupling, Connection method: Spring-cage connection, Number of positions: 1, Cross section: 0.08 mm² - 6 mm², AWG: 28 - 10, Width: 6.2 mm, Height: 22.3 mm, Color: blue

Product Features

- Tested for railway applications
- The coupling is assembled directly on site by snapping together single-position coupling elements
- The ST-COMBI couplings for self-assembly provide solutions that users can implement themselves

Key commercial data

Packing unit	1 1
Weight per Piece (excluding packing)	5.69 GRM
Custom tariff number	85366990
Country of origin	Poland

Technical data

General

Number of levels	1
Number of connections	2
Color	blue
Insulating material	PA
Inflammability class according to UL 94	V0
Area of application	Railway industry
	Mechanical engineering
	Plant engineering
Maximum load current	32 A (with 6 mm² conductor cross section)
Rated surge voltage	8 kV

Coupling - SC 4/ 1-L BU - 3042609

Technical data

General

Pollution degree	3
Surge voltage category	III
Insulating material group	I
Connection in acc. with standard	IEC 61984
Nominal current I_N	32 A
Nominal voltage U_N	800 V
Open side panel	ja
Number of positions	1

Dimensions

Width	6.2 mm
Length	48.6 mm
Height	22.3 mm

Connection data

Conductor cross section solid min.	0.08 mm²
Conductor cross section solid max.	6 mm²
Conductor cross section AWG/kcmil min.	28
Conductor cross section AWG/kcmil max	10
Conductor cross section stranded min.	0.08 mm²
Conductor cross section stranded max.	4 mm²
Min. AWG conductor cross section, stranded	28
Max. AWG conductor cross section, stranded	12
Conductor cross section stranded, with ferrule without plastic sleeve min.	0.14 mm²
Conductor cross section stranded, with ferrule without plastic sleeve max.	4 mm²
Conductor cross section stranded, with ferrule with plastic sleeve min.	0.14 mm²
Conductor cross section stranded, with ferrule with plastic sleeve max.	4 mm²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min.	0.5 mm²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max.	1 mm²
Connection method	Spring-cage connection
Stripping length	10 mm
Internal cylindrical gage	A4

Classifications

eCl@ss

eCl@ss 4.0	272607xx

Coupling - SC 4/ 1-L BU - 3042609

Classifications

eCl@ss

eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27141120
eCl@ss 7.0	27141120
eCl@ss 8.0	27141120

ETIM

ETIM 2.0	EC000897
ETIM 3.0	EC000897
ETIM 4.0	EC000897
ETIM 5.0	EC000897

UNSPSC

UNSPSC 6.01	30211802
UNSPSC 7.0901	39121402
UNSPSC 11	39121402
UNSPSC 12.01	39121402
UNSPSC 13.2	39121402

Approvals

Approvals

Approvals

UL Recognized / cUL Recognized / GOST / GOST / cULus Recognized

Ex Approvals

Approvals submitted

Approval details

Coupling - SC 4/ 1-L BU - 3042609

Approvals

UL Recognized

	B	C
mm²/AWG/kcmil	28-10	28-10
Nominal current IN	30 A	30 A
Nominal voltage UN	600 V	600 V

cUL Recognized

	B	C
mm²/AWG/kcmil	28-10	28-10
Nominal current IN	30 A	30 A
Nominal voltage UN	600 V	600 V

GOST

GOST

cULus Recognized

Accessories

Accessories

End cover

End cover - D-SC 4 - 3043307

End cover, Length: 48.6 mm, Width: 2.2 mm, Color: gray

Coupling - SC 4/ 1-L BU - 3042609

Accessories

Insulating sleeve

Insulating sleeve - MPS-IH WH - 0201663

Insulating sleeve, Color: white

Insulating sleeve - MPS-IH RD - 0201676

Insulating sleeve, Color: red

Insulating sleeve - MPS-IH BU - 0201689

Insulating sleeve, Color: blue

Insulating sleeve - MPS-IH YE - 0201692

Insulating sleeve, Color: yellow

Insulating sleeve - MPS-IH GN - 0201702

Insulating sleeve, Color: green

Coupling - SC 4/ 1-L BU - 3042609

Accessories

Insulating sleeve - MPS-IH GY - 0201728

Insulating sleeve, Color: gray

Insulating sleeve - MPS-IH BK - 0201731

Insulating sleeve, Color: black

Insulating sleeve - ISH 4/0,5 - 3002885

Insulating sleeve, Color: gray

Insulating sleeve - ISH 4/1,0 - 3002898

Insulating sleeve, Color: black

Mounting material

Strain relief - CZ/2 - 3043831

Strain relief, Number of positions: 2, Color: black

Coupling - SC 4/ 1-L BU - 3042609

Accessories

Screwdriver tools

Screwdriver - SZF 1-0,6X3,5 - 1204517

Actuation tool, for ST terminal blocks, also suitable for use as a bladed screwdriver, size: 0.6 x 3.5 x 100 mm, 2-component grip, with non-slip grip

Test plug terminal block

Test plugs - MPS-MT - 0201744

Test plugs, Color: silver

Drawings

Circuit diagram

© Phoenix Contact 2013 - all rights reserved
http://www.phoenixcontact.com