

APPLIED CONCEPTS INC.

397 Route 281 - P.O. BOX 453
Tully, New York 13159-0453
Phone: (315) 696-6676 Fax: (315) 696-9923
www.acipower.com

ACL-12-1129

PRODUCT DATA SHEET

7/29/03

CCFL INVERTER

(For Multiple Tube Applications)

The ACL-12-1129 is designed to power 12 CCFL's to a nominal power level of 43 watts.

Intensity control (0-100%) is accomplished by the user providing a variable dc level of 0V(off) to 5V(full-on) at pin 4 of CON1.

Enable control is accomplished at pin 7 of CON1 (0V=off, 5V=on).

All outputs are open and short circuit protected.

This unit is mechanically and plug-in compatible to the BI220A series Landmark Inverter. Contact factory for your unique electrical requirements.


Specifications:

- Vin = +12V +/- 10%
- CCFL strike voltage = 1800Vrms @ Vin=12V
- CCFL tube current = 6.0mA/tube @ 100% intensity/Vin=12V
- Recommended CCFL sustaining voltage = 450Vrms - 750Vrms
- Nominal tube current frequency = 41khz +/- 10%
- Nominal pwm frequency = 98Hz +/- 3%
- Pwm duty cycle range = 0 to 100%
- Average electrical efficiency >90%
- External PWM signal input control via enable pin

Additional control/capability:*

- Supports multiple units ie: Master/Slave(s)
- Synchronization to display frame-rate
- Low power sleep-mode and soft-start
- 70 Watt total output power capability @ 70DegC

* Please contact factory for information



CON1
MOLEX 22-28-0070

CON2(CON3)
MOLEX 22-28-0130

PIN #		PIN #	
1	+5V OUTPUT	1	CCFL 1(7)
2	+12V INPUT(PWR)	2	NC
3	+12V INPUT(PWR)	3	CCFL 2(8)
4	VCNTL	4	NC
5	GND(PWR)	5	CCFL 3(9)
6	GND(PWR)	6	NC
7	ENABLE	7	CCFL 4(10)
		8	NC
		9	CCFL 5(11)
		10	NC
		11	CCFL 6(12)
		12	NC
		13	CCFL COM