

产品规格书

PRODUCT SPECIFICATION

客户名称:

CUSTOMER:

产品名称:

PRODUCT NAME:

贴片保险丝 SMD FUSE

型号规格:

MODEL DETAIL:

12D (RoHS Compliant) 2A 63V 快断型 (Fast-Acting)

料 号:

PART NO.:

LM12D1200D

供货商:

SUPPLIER:

地 址:

ADDRESS:

编 制 PREPARED BY	审 核 CHECKED BY	批 准 APPROVED BY

承 认 SIGNATURE	审 核 CHECKED BY	批 准 APPROVED BY

供方签章:

SUPPLIER:

需方签章:

CUSTOMER:

日期:

DATE:

日期:

DATE:

1. 适用范围 Scope of Application

本产品适用于各种电子电路中起过电流保护作用。

This product is suitable for various kinds of electronic machines to work for over current protection.

2. 相关标准及认证 Relevant Standards and Certification


2.1 执行标准 Standard: UL248-1、UL248-14

2.2 认证 Certification

认证 Certification	认证范围 Scope of Certification	证书编号 Certification No.
UL	250mA~20A	E221465

3. 结构尺寸及原材料明细 Structure Size and Material Detail

3.1 结构尺寸 Structure Size (unit: mm)



3.2 原材料明细 Material Detail

编号 No.	零件名称 Part Name	材质 Material
①	电极 Electrode	银 Silver
②	涂层 Coating	玻璃浆 Glass cover
③	端头 End Termination	镀银 Silver plated
④	熔丝 Fuse element	银 Silver
⑤	基片 Substrate	陶瓷 Ceramic

4. 标示 Mark

4.1 保险丝上需有下列标示:

The fuse shall have the following marking:

额定电流 Ampere Rating	产品标示 Marking
250mA	.25
375mA	●
500mA	.5
750mA	.75
1A	1
1.25A	▲
1.5A	1.5
2A	2
2.5A	2.5
3A	3
4A	4
5A	5
6.5A	6.5
7A	7
10A	10
12A	12
15A	15
20A	20

5. 电气特性 Electrical Characteristics

5.1 实验条件: 所有测试环境温度均为 $25 \pm 5^\circ\text{C}$ 。

Test Condition: All electrical characteristics tests are conducted at an ambient temperature of $25 \pm 5^\circ\text{C}$.

5.2 时间-电流特性

Time-Current Characteristics

额定电流 Ampere Rating	额定电流的% % of Ampere Rating	熔断时间 Opening Time
250mA~20A	100%	4 hours min(大于 4 小时)
250mA~3A	250%	5 S Max(小于 5 秒)
4A~20A	350%	5 S Max(小于 5 秒)

5.3 额定分断能力:

Interrupting Rating:

50 Amperes at 63V DC (250mA~3A)

50 Amperes at 32V DC (4A~7A)

150 Amperes at 24V DC (8A~20A)

6. 环境特性 Environmental Characteristics

6.1 使用温度范围 Operating Temperature

-40℃~125℃。

6.2 保存条件 Storage Conditions

相对湿度≤75%，可以存放 3 年。

Relative humidity≤75%, store 3 years.

7. 可靠性试验 Reliability Test

7.1 冷热冲击试验 Thermal Shock Test

MIL-STD-202G, Method 107G。

7.2 防潮湿试验 Moisture Resistance Test

MIL-STD-202G, Method 106G。

7.3 振动试验 Vibration Test

MIL-STD-202G, Method 201A。

7.4 可焊性试验 Solderability Test

MIL-STD-202G, Method 208H, IEC60127-2, IEC60068-2。

8. 时间-电流曲线图 Time-Current Curve

