PE feed-through terminal block - HDFK 25-PE - 0707785

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://download.phoenixcontact.com)



PE feed-through terminal block, Connection method: Screw connection, Load current : 125 A, Cross section: 6 mm² - 35 mm², AWG 8 - 3, Connection direction of the conductor to plug-in direction: 0 °, Width: 15.1 mm, Color: green-yellow

Key commercial data

Packing unit	1
Minimum order quantity	1
Catalog page	Page 630 (CC-2009)
GTIN	4 017918 004231
Custom tariff number	85369010
Country of origin	GREECE

Technical data

General

Number of levels	1
Number of connections	2
Color	green-yellow
Insulating material	PA
Inflammability class according to UL 94	V0

Dimensions

Width	15.1 mm

Technical data

Rated surge voltage	6 kV
Pollution degree	3
Surge voltage category	III
Insulating material group	I
Connection in acc. with standard	IEC 60947-7-2
Nominal current IN	101 A
Nominal voltage UN	500 V
Open side panel	nein

PE feed-through terminal block - HDFK 25-PE - 0707785

Technical data

Connection data

Note	Note: Product releases, connection cross sections and notes on connecting aluminum cables can be found in the download area.
Conductor cross section solid min.	6 mm²
Conductor cross section solid max.	35 mm²
Conductor cross section stranded min.	10 mm²
Conductor cross section stranded max.	25 mm²
Conductor cross section AWG/kcmil min.	10
Conductor cross section AWG/kcmil max	2
Conductor cross section stranded, with ferrule without plastic sleeve min.	4 mm²
Conductor cross section stranded, with ferrule without plastic sleeve max.	25 mm²
Conductor cross section stranded, with ferrule with plastic sleeve min.	4 mm²
Conductor cross section stranded, with ferrule with plastic sleeve max.	25 mm²
2 conductors with same cross section, solid min.	2.5 mm²
2 conductors with same cross section, solid max.	10 mm²
2 conductors with same cross section, stranded min.	4 mm²
2 conductors with same cross section, stranded max.	10 mm²
2 conductors with same cross section, stranded, ferrules without plastic sleeve, min.	2.5 mm²
2 conductors with same cross section, stranded, ferrules without plastic sleeve, max.	10 mm²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min.	2.5 mm²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max.	10 mm²
Connection method	Screw connection
Stripping length	19 mm
Internal cylindrical gage	B8
Screw thread	M5
Tightening torque, min	4 Nm
Tightening torque max	4.5 Nm

Classifications

eclass

eCl@ss 4.0	27141131
eCl@ss 4.1	27141131
eCl@ss 5.0	27141134
eCl@ss 5.1	27141134
eCl@ss 6.0	27141134
eCl@ss 7.0	27141134

PE feed-through terminal block - HDFK 25-PE - 0707785

Classifications

etim

ETIM 2.0	EC001283
ETIM 3.0	EC001283
ETIM 4.0	EC001283
ETIM 5.0	EC001283

unspsc

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39121410

Approvals

Approvals

Approvals

CSA / UL Recognized / KEMA-KEUR / GOST / PRS / CCA / IECEE CB Scheme / GOST

Ex Approvals

Approvals submitted

Approval details

CSA

mm²/AWG/kcmil	8-4

UL Recognized

mm²/AWG/kcmil	8-2

KEMA-KEUR

PE feed-through terminal block - HDFK 25-PE - 0707785

Approvals

GOST

PRS

CCA

IECEE CB Scheme

GOST

Accessories

Accessories

Tools


Screwdriver - SZS 1,0X6,5 VDE - 1205079




Screwdriver, bladed, VDE insulated, size: 1.0 x 6.5 x 150 mm, 2-component grip, with non-slip grip

Drawings

Dimensioned drawing



Dimensioned drawing



© Phoenix Contact 2012 - all rights reserved
http://www.phoenixcontact.com