



Main

Range	PowerLogic
Device short name	ION7650
Product or component type	Energy and power quality meter

Complementary

Power quality analysis	harmonic distortion voltage sag and swell detection waveform capture compliance monitoring dip and swell, transient disturbance direction detection programmability (logic and math functions) setpoint learning up to the 63rd harmonic
Device application	Equipment monitoring and control Instrument transformer correction Co-generation and IPP monitoring Tariff metering Energy pulsing and totalisation Load curtailment Demand and power factor control
Type of measurement	Current Voltage Frequency Apparent power total Power factor total Apparent power per phase Power factor per phase Active power total Active power per phase Reactive power total Reactive power per phase
Supply voltage	110...300 V DC 85...240 V AC 47...63 Hz
Network frequency	60 Hz

Line Rated Current	5 A
Type of network	3P + N 1P + N 3P
Power consumption in VA	20 VA
Maximum power consumption in VA	45 VA
Display resolution	320 x 240 pixels QVGA
Display type	Backlit LCD
Sampling rate	512 samples/cycle
Measurement current	0...5 A
Input type	current 0.005...20 A 0.002 Ohm)
Measurement voltage	100...600 V AC phase to phase 57...347 V AC phase to neutral
Frequency measurement range	42...69 Hz
Number of inputs	8 digital 120 V DC
Measurement accuracy	Current 0.1 % 1...5 A Voltage 0.1 % 57...288 V Energy 0.2 %
Accuracy class	Class 0.2S energy IEC 62053-22
Number of outputs	3 relay 4 solid state
Communication port protocol	ION Telnet IEC 61850 DNP3 Modbus TCP/IP
Communication port support	RJ45 Ethernet RS485 RJ11 modem SUB-D 9 RS232 ST fiber optic
Data recording	GPS synchronisation Data logs Trending/forecasting Sequence of event recording Time stamping Event logs Min/max of instantaneous values
Transmission rate	300...115200 bauds <= 19200 bauds 300...57600 bauds 10/100 Mbit/s
Memory capacity	5 MB
Web services	Web server
Tamperproof of settings	Protected by access code
Compatibility code	ION7650

Environment

Electromagnetic compatibility	Electrical fast transient/burst immunity test IEC 61000-4-4 Electrostatic discharge IEC 61000-4-2 Susceptibility to electromagnetic fields IEC 61000-4-3 1.2/50 µs shock waves immunity test IEC 61000-4-5 Conducted and radiated emissionsB CISPR 22
Mounting mode	Flush-mounted
Mounting support	Enclosure door
Type of installation	Indoor installation
Overvoltage category	III
IP degree of protection	Back IP30 IEC 60529 Front face IP50 IEC 60529
Relative humidity	5...95 %

Pollution degree	2
Ambient air temperature for operation	-4...158 °F (-20...70 °C)
Ambient air temperature for storage	-40...185 °F (-40...85 °C)
Operating altitude	0...6561.68 ft (0...2000 m)
Standards	IEC 61010-1
Width	7.56 in (192 mm)
Depth	6.85 in (174 mm)
Height	7.56 in (192 mm)
Net weight	4.19 lb(US) (1.9 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Dichloromethane (Methylene chloride) and Bisphenol A (BPA) which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------