
Dip type LVDS output
12.8 x 12.8 x 5.5 mm



RoHS Compliance


Applications


- For high frequency LVDS output clock oscillators .
- " HDF " series : Best performance among the three series. Phase jitter is less than 1 ps.
- 2.5 V or 3.3 V supply voltage .

General Specifications

Paramenters		Electrical Spec.							
Input Voltage (V_{DD})		2.5 V ± 5 %							
Frequency Range / Load		38.0 MHz ~ 640,0 MHz							
Output Wave Form		LVDS output							
Output Logic High " 1 "	typical	1.43 V (RL = 100 Ω)							
	max.	1.60 V (RL = 100 Ω)							
Output Logic Low " 0 "	min.	0.9 V (RL = 100 Ω)							
	typical	1.1 V (RL = 100 Ω)							
Integrated Phase Noise (12 KHz to 20 MHz)		0.4 ps (typical) ; 0.5 ps (max.)							
Rise Time (Tr) / Fall Time (Tf)		0.4n sec.(typical) ; 0.6 n sec. (max.)							
Output Voltage Swing		250 mV min. (V_{DD} = +2.5V)							
Duty Cycle		50% ± 10% [50% ± 5% is also available]							
Load		50 Ω into Vcc - 2V or Thevenin equivalent							
Current Consumption (15 pF load)		38.0 ~ 100.0 MHz		100.1 ~ 320.0 MHz		320.1 ~ 800.0 MHz			
		65 mA (max.)		80 mA (max.)		90 mA (max.)			
Start - Up Time (Ts)		10 m sec.(typical)							
Storage Temperature		- 50°C to 100°C							
Aging		± 3 ppm per year (max.)							
Frequency Stability [1] Codes	Frequency Stability over Operating Temperature Range	± 25 ppm	± 50 ppm	± 100 ppm	If non-standard , please enter the desired stability after the " C " or " I " For example : " C20 " ±20 ppm over -10°C to +70°C ; " I20 " ± 20 ppm over -40°C to +85°C				
	Commercial (*-10°C to +70°C*)	*A*	*B*	*C*					
	Industrial (*-40°C to +85°C*)	*D*	*E*	*F*					
Phase Noise (typical) [156.250 MHz]		Offset	10 Hz	100 Hz	1K Hz	10 KHz	100KHz	1 MHz	10 MHz
		dBc / Hz	-62	-90	-120	-132	-128	-140	-150

Outline Dimensions (Unit : mm)





3 -Ø1.6 glass stand-off

Pin Connections :
Pin 1 : Complimentary output
Pin 4 : Ground
Pin 5 : Output
Pin 8 : Supply voltage

Mercury www .mercury-crystal.com

■Taiwan : (886)-2-2406-2779 / sales-tw@mercury-crystal.com ■U.S.A: (1)-909-466-0427 / sales-us@mercury-crystal.com ■China : (86)-512-5763-8100 / sales-cn@mecxtal.com