



## Model Number

NJ2-11-N-G

## Features

- 2 mm flush
- Usable up to SIL 2 acc. to IEC 61508

## Technical Data

### General specifications

Switching function		Normally closed (NC)
Output type		NAMUR
Rated operating distance	$s_n$	2 mm
Installation		flush
Assured operating distance	$s_a$	0 ... 1.62 mm
Actual operating distance	$s_r$	1.8 ... 2.2 mm
Reduction factor $r_{AI}$		0.4
Reduction factor $r_{CU}$		0.3
Reduction factor $r_{304}$		0.85
Output type		2-wire

### Nominal ratings

Nominal voltage	$U_o$	8.2 V ( $R_i$ approx. 1 k $\Omega$ )
Switching frequency	f	0 ... 3000 Hz
Hysteresis	H	0.5 ... 3.5 typ. 2 %

### Current consumption

Measuring plate not detected	$\geq 3$ mA
Measuring plate detected	$\leq 1$ mA

### Functional safety related parameters

Safety Integrity Level (SIL)	SIL 2
MTTF <sub>d</sub>	5887 a
Mission Time ( $T_M$ )	20 a
Diagnostic Coverage (DC)	0 %

### Ambient conditions

Ambient temperature	-25 ... 100 °C (-13 ... 212 °F)
---------------------	---------------------------------

### Mechanical specifications

Connection type	cable PVC , 2 m
Core cross-section	0.34 mm <sup>2</sup>
Housing material	Stainless steel 1.4305 / AISI 303
Sensing face	PVDF
Degree of protection	IP68
Cable	
Bending radius	> 10 x cable diameter

### General information

Use in the hazardous area	see instruction manuals
---------------------------	-------------------------


### Compliance with standards and directives

Standard conformity	
NAMUR	EN 60947-5-6:2000 IEC 60947-5-6:1999
Standards	EN 60947-5-2:2007 EN 60947-5-2/A1:2012 IEC 60947-5-2:2007 IEC 60947-5-2 AMD 1:2012


### Approvals and certificates

EAC conformity	TR CU 012/2011
FM approval	
Control drawing	116-0165
UL approval	
Ordinary Location	E87056
Hazardous Location	E501628
Control drawing	116-0452
CCC approval	CCC approval / marking not required for products rated $\leq 36$ V

## Dimensions



Electrical Connection



**Data for application in connection with hazardous areas**

Equipment protection level	Ga , Gb , Gc (ic) , Da , Mb
----------------------------	-----------------------------

**Equipment protection level Ga**

Type of protection	intrinsic safety
CE marking	CE 0102

**Certificates**

Appropriate type	NJ2-11-N-G...
ATEX certificate	PTB 00 ATEX 2048 X
ATEX marking	Ⓔ II 1G Ex ia IIC T6...T1 Ga
Standards	EN 60079-0:2012+A11:2013 , EN 60079-11:2012
IECEX certificate	IECEX PTB 11.0037X
IECEX marking	Ex ia IIC T6...T1 Ga
Standards	IEC 60079-0:2011 , IEC 60079-11:2011

Effective internal capacitance	$C_i$	$\leq 30$ nF A cable length of 10 m is considered.
--------------------------------	-------	---

Effective internal inductance	$L_i$	$\leq 50$ $\mu$ H A cable length of 10 m is considered.
-------------------------------	-------	--

Maximum permissible ambient temperature $T_{amb}$	Also observe the maximum permissible ambient temperature stated in the general technical data. Keep to the lower of the two values.
---	--

for ATEX	<p>at <math>U_i = 16</math> V , <math>I_i = 25</math> mA , <math>P_i = 34</math> mW ,  T6 : 59 °C (138.2 °F)  T5 : 71 °C (159.8 °F)  T4 : 99 °C (210.2 °F)  T3 : 99 °C (210.2 °F)  T2 : 99 °C (210.2 °F)  T1 : 99 °C (210.2 °F)</p> <p>at <math>U_i = 16</math> V , <math>I_i = 25</math> mA , <math>P_i = 64</math> mW ,  T6 : 56 °C (132.8 °F)  T5 : 68 °C (154.4 °F)  T4 : 96 °C (204.8 °F)  T3 : 96 °C (204.8 °F)  T2 : 96 °C (204.8 °F)  T1 : 96 °C (204.8 °F)</p> <p>at <math>U_i = 16</math> V , <math>I_i = 52</math> mA , <math>P_i = 169</math> mW ,  T6 : 45 °C (113 °F)  T5 : 57 °C (134.6 °F)  T4 : 81 °C (177.8 °F)  T3 : 81 °C (177.8 °F)  T2 : 81 °C (177.8 °F)  T1 : 81 °C (177.8 °F)</p> <p>at <math>U_i = 16</math> V , <math>I_i = 76</math> mA , <math>P_i = 242</math> mW ,  T6 : 37 °C (98.6 °F)  T5 : 49 °C (120.2 °F)  T4 : 63 °C (145.4 °F)  T3 : 63 °C (145.4 °F)  T2 : 63 °C (145.4 °F)  T1 : 63 °C (145.4 °F)</p>
----------	--

for IECEX	<p>at <math>U_i = 16</math> V , <math>I_i = 25</math> mA , <math>P_i = 34</math> mW ,  T6 : 76 °C (168.8 °F)  T5 : 91 °C (195.8 °F)  T4 : 100 °C (212 °F)  T3 : 100 °C (212 °F)  T2 : 100 °C (212 °F)  T1 : 100 °C (212 °F)</p> <p>at <math>U_i = 16</math> V , <math>I_i = 25</math> mA , <math>P_i = 64</math> mW ,  T6 : 73 °C (163.4 °F)  T5 : 88 °C (190.4 °F)  T4 : 100 °C (212 °F)  T3 : 100 °C (212 °F)  T2 : 100 °C (212 °F)  T1 : 100 °C (212 °F)</p> <p>at <math>U_i = 16</math> V , <math>I_i = 52</math> mA , <math>P_i = 169</math> mW ,  T6 : 62 °C (143.6 °F)  T5 : 77 °C (170.6 °F)  T4 : 81 °C (177.8 °F)  T3 : 81 °C (177.8 °F)  T2 : 81 °C (177.8 °F)  T1 : 81 °C (177.8 °F)</p> <p>at <math>U_i = 16</math> V , <math>I_i = 76</math> mA , <math>P_i = 242</math> mW ,  T6 : 54 °C (129.2 °F)  T5 : 63 °C (145.4 °F)  T4 : 63 °C (145.4 °F)  T3 : 63 °C (145.4 °F)  T2 : 63 °C (145.4 °F)  T1 : 63 °C (145.4 °F)</p>
-----------	---

**Equipment protection level Gb**

Type of protection	intrinsic safety	
CE marking	CE 0102	
<b>Certificates</b>		
Appropriate type	NJ 2-11-N-G...	
ATEX certificate	PTB 00 ATEX 2048 X	
ATEX marking	Ex II 1G Ex ia IIC T6...T1 Ga	
Standards	EN 60079-0:2012+A11:2013 , EN 60079-11:2012	
IECEX certificate	IECEX PTB 11.0037X	
IECEX marking	Ex ia IIC T6...T1 Ga	
Standards	IEC 60079-0:2011 , IEC 60079-11:2011	
Effective internal capacitance	$C_i$	$\leq 30$ nF A cable length of 10 m is considered.
Effective internal inductance	$L_i$	$\leq 50$ $\mu$ H A cable length of 10 m is considered.
Maximum permissible ambient temperature $T_{amb}$	Also observe the maximum permissible ambient temperature stated in the general technical data. Keep to the lower of the two values. at $U_i = 16$ V , $I_i = 25$ mA , $P_i = 34$ mW , T6 : 76 °C (168.8 °F) T5 : 91 °C (195.8 °F) T4 : 100 °C (212 °F) T3 : 100 °C (212 °F) T2 : 100 °C (212 °F) T1 : 100 °C (212 °F) at $U_i = 16$ V , $I_i = 25$ mA , $P_i = 64$ mW , T6 : 73 °C (163.4 °F) T5 : 88 °C (190.4 °F) T4 : 100 °C (212 °F) T3 : 100 °C (212 °F) T2 : 100 °C (212 °F) T1 : 100 °C (212 °F) at $U_i = 16$ V , $I_i = 52$ mA , $P_i = 169$ mW , T6 : 62 °C (143.6 °F) T5 : 77 °C (170.6 °F) T4 : 81 °C (177.8 °F) T3 : 81 °C (177.8 °F) T2 : 81 °C (177.8 °F) T1 : 81 °C (177.8 °F) at $U_i = 16$ V , $I_i = 76$ mA , $P_i = 242$ mW , T6 : 54 °C (129.2 °F) T5 : 63 °C (145.4 °F) T4 : 63 °C (145.4 °F) T3 : 63 °C (145.4 °F) T2 : 63 °C (145.4 °F) T1 : 63 °C (145.4 °F)	

**Equipment protection level Gc (ic)**

Type of protection	intrinsic safety	
CE marking	CE	
<b>Certificates</b>		
ATEX certificate	PF13CERT2895 X	
ATEX marking	Ex II 3G Ex ic IIC T6...T1 Gc	
Standards	EN 60079-0:2012+A11:2013 , EN 60079-11:2012	
Effective internal capacitance	$C_i$	$\leq 30$ nF A cable length of 10 m is considered.
Effective internal inductance	$L_i$	$\leq 50$ $\mu$ H A cable length of 10 m is considered.
Maximum permissible ambient temperature $T_{amb}$	Also observe the maximum permissible ambient temperature stated in the general technical data. Keep to the lower of the two values. at $U_i = 20$ V , $I_i = 25$ mA , $P_i = 34$ mW , T6 : 55 °C (131 °F) T5 : 55 °C (131 °F) T4 : 55 °C (131 °F) T3 : 55 °C (131 °F) T2 : 55 °C (131 °F) T1 : 55 °C (131 °F) at $U_i = 20$ V , $I_i = 25$ mA , $P_i = 64$ mW , T6 : 55 °C (131 °F) T5 : 55 °C (131 °F) T4 : 55 °C (131 °F) T3 : 55 °C (131 °F) T2 : 55 °C (131 °F) T1 : 55 °C (131 °F) at $U_i = 20$ V , $I_i = 52$ mA , $P_i = 169$ mW , T6 : 52 °C (125.6 °F) T5 : 52 °C (125.6 °F) T4 : 52 °C (125.6 °F) T3 : 52 °C (125.6 °F) T2 : 52 °C (125.6 °F) T1 : 52 °C (125.6 °F) at $U_i = 20$ V , $I_i = 76$ mA , $P_i = 242$ mW , T6 : 44 °C (111.2 °F) T5 : 44 °C (111.2 °F) T4 : 44 °C (111.2 °F) T3 : 44 °C (111.2 °F) T2 : 44 °C (111.2 °F) T1 : 44 °C (111.2 °F)	

Release date: 2019-07-08 14:30 Date of issue: 2019-07-08 306126\_eng.xml

**Equipment protection level Da**

Type of protection	intrinsic safety	
CE marking	CE 0102	
<b>Certificates</b>		
Appropriate type	NJ 2-11-N-G...	
ATEX certificate	PTB 00 ATEX 2048 X	
ATEX marking	Ⓔ II 1D Ex ia IIIC T135°C Da	
Standards	EN 60079-0:2012+A11:2013 , EN 60079-11:2012	
IECEX certificate	IECEX PTB 11.0037X	
IECEX marking	Ex ia IIIC T135°C Da	
Standards	IEC 60079-0:2011 , IEC 60079-11:2011	
Effective internal capacitance	$C_i$	$\leq 30$ nF A cable length of 10 m is considered.
Effective internal inductance	$L_i$	$\leq 50$ $\mu$ H A cable length of 10 m is considered.
Maximum permissible ambient temperature $T_{amb}$	Also observe the maximum permissible ambient temperature stated in the general technical data. Keep to the lower of the two values. at $U_i = 16$ V , $I_i = 25$ mA , $P_i = 34$ mW : 100 °C (212 °F) at $U_i = 16$ V , $I_i = 25$ mA , $P_i = 64$ mW : 100 °C (212 °F) at $U_i = 16$ V , $I_i = 52$ mA , $P_i = 169$ mW : 81 °C (177.8 °F) at $U_i = 16$ V , $I_i = 76$ mA , $P_i = 242$ mW : 63 °C (145.4 °F)	

**Equipment protection level Mb**

Type of protection	intrinsic safety	
<b>Certificates</b>		
Appropriate type	NJ 2-11-N-G...	
IECEX certificate	IECEX PTB 11.0037X	
IECEX marking	Ex ia I Mb	
Standards	IEC 60079-0:2011 , IEC 60079-11:2011	
Effective internal capacitance	$C_i$	$\leq 30$ nF A cable length of 10 m is considered.
Effective internal inductance	$L_i$	$\leq 50$ $\mu$ H A cable length of 10 m is considered.
Maximum permissible ambient temperature $T_{amb}$	Also observe the maximum permissible ambient temperature stated in the general technical data. Keep to the lower of the two values. at $U_i = 16$ V , $I_i = 25$ mA , $P_i = 34$ mW : 100 °C (212 °F) at $U_i = 16$ V , $I_i = 25$ mA , $P_i = 64$ mW : 100 °C (212 °F) at $U_i = 16$ V , $I_i = 52$ mA , $P_i = 169$ mW : 81 °C (177.8 °F) at $U_i = 16$ V , $I_i = 76$ mA , $P_i = 242$ mW : 63 °C (145.4 °F)	