

NEMA Contactor, Type S, nonreversing, Size 4, 135A, 100 HP at 575 VAC, 3 phase, up to 100 kA, 5 pole, 480 VAC coil, open

8502SFO4V06

Price*: 6,579.00 USD

V	aı	r

Contactor
8502S
Non-reversing

Complementary	
NEMA Size	4
Rated Current	135 A
Number of Poles	5P
Maximum Voltage Rating	600 V AC
Phase	3 phase
Horsepower Rating	40 HP 200 V AC 50 HP 230 V AC 100 HP 460 V AC 100 HP 575 V AC
SCCR	Circuit-breaker 225 A maximum, SCCR: 100 kA at 480 V AC Fuse J 200 A maximum, SCCR: 100 kA at 600 V AC Fuse T 200 A maximum, SCCR: 100 kA at 600 V AC Fuse RK1 200 A maximum, SCCR: 100 kA at 600 V AC Fuse RK5 200 A maximum, SCCR: 100 kA at 600 V AC
Coil Voltage	480 V AC 60 Hz 440 V AC 50 Hz
Control Circuit Type	Common control circuit
Control Units	No control units
Pilot Light	No indicator
Auxiliary Contacts	Without
Other Equipment	Fuse not supplied
Terminal Type	Screw clamp terminals
Height	8.19 in (208.03 mm)
Width	9.75 in (247.65 mm)
Depth	6.50 in (165 mm)

Environmental

Enclosure Type	Not rated (open device)

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Certifications	UL listed file E78351 CCN NLDX CSA
----------------	---------------------------------------

Ordering and shipping details

Category	21193-8502,36 SE,SF(NOT S*R,T,W)
Discount Schedule	CP1
Package weight(Lbs)	22.00 lb(US) (9.979 kg)
Returnability	No
Country of origin	MX

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Not compliant	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.	

Contractual warranty

Warranty 18 months
