



## 477RSS035M

RADIAL LEAD LOW PROFILE

Parts are RoHS compliant

Date code when parts became RoHS: 23

**APPLICATIONS:** General Purpose, Bypass, coupling, Filtering, Handheld devices

### ELECTRICAL SPECIFICATIONS

**Capacitance:** 470 uF

**Dissipation Factor:** 0.12 Max at 120 Hz and 20°C

**Temperature Range:** -40°C to +85°C

**ESR:** 0.423 Ohms Max at 20°C and 120 Hz

**Impedance:** N/A

**Tolerance:** -20 %, +20 %

**WVDC:** 35 Volts DC

**SVDC:** 44 Volts DC

**Ripple Current:** 524 mA at 120 Hz and 85°C

**Impedance Ratios:**-25°C/20°C 2 and -40°C/20°C - 4

**Leakage Current:** .01CV or 3uA, whichever is greater  
164.5 uA after 2 Minutes

**Load Life:** 1000 hours at 85°C with 100 % of rated voltage and with 0 % of rated ripple current

**Capacitance Change:** ≤20% of initial measured value

**Dissipation Factor:** ≤200% of maximum specified value

**Leakage Current:** ≤100% of maximum specified value

#### Frequency Multipliers:

50 HZ	120 HZ	400 HZ	1 KHZ	10 KHZ	100 KHZ
0.8	1	1.23	1.34	1.5	1.5

#### Temperature Multipliers:

45°C	60°C	70°C	65°C	75°C	85°C	105°C	125°C
1.8	1.7	1.4	1.6	1	1	0	0

### PHYSICAL DIMENSIONS

**Diameter (D):** 10 mm + 0.5 mm

**Length (L):** 12.5 mm + 1.5 mm


**Lead Spacing (S):** 5 mm +/- 0.5 mm

**Coating:** YellowPET sleeving

**Lead Wire Diameter (d):** 0.6 mm +/- 0.05 mm

**Lead Length:** 15 mm +/- MIN mm

**Lead Finish:** Matte Tin



3757 W. Touhy Ave. Lincolnwood, IL 60712 (847) 675-1760 FAX (847) 673-2850  
Illinois Capacitor (HK) Ltd., Tel: 85227930931, Fax: 85227930731, [www.illcap.com.hk](http://www.illcap.com.hk)  
© Copyright 2017 Illinois Capacitor. A division of Cornell Dubilier, All Rights Reserved