



7/16 DIN Male to 7/16 DIN Male LSZH Jacketed Cable  
200 CM Length Using SR402FLJ Low PIM Coax, RoHS

TECHNICAL DATA SHEET

PE3C2003-200CM

**Configuration**

Connector 1	7/16 DIN Male
Connector 2	7/16 DIN Male
Cable Type	PE-SR402FLJ Low PIM

**Electrical Specifications**

Frequency Range	DC to 3 GHz
Impedance	50 Ohms
Maximum VSWR	1.15:1
RF Shielding	-100 dB
Maximum Input Power	440 Watts
Passive Intermodulation	-160 dBc

**Typical Performance by Frequency**

**Frequency 1**

Frequency	500 MHz
Insertion Loss,	0.5 dB
Power Handling, Watts	440

**Frequency 2**

Frequency	1000 MHz
Insertion Loss	0.82 dB
Power Handling	300 Watts

**Frequency 3**

Frequency	2 GHz
Insertion Loss	1.2 dB
Power Handling	220 Watts

**Frequency 4**

Frequency	2.5 GHz
Insertion Loss	1.37 dB
Power Handling	190 Watts

**Frequency 5**

Frequency	3 GHz
Insertion Loss	1.5 dB
Power Handling	170 Watts

**Mechanical Specifications**

**Temperature**

Temperature Operating Range	-55 to +125 deg C
-----------------------------	-------------------

**Size**

Length	78.74 in [200 cm]
One Time Minimum Bend Radius	1.5 in [38.1 mm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [7/16 DIN Male to 7/16 DIN Male LSZH Jacketed Cable 200 CM Length Using SR402FLJ Low PIM Coax, RoHS PE3C2003-200CM](#)





7/16 DIN Male to 7/16 DIN Male LSZH Jacketed Cable  
200 CM Length Using SR402FLJ Low PIM Coax, RoHS

TECHNICAL DATA SHEET

PE3C2003-200CM

**Cable**

Cable Type	PE-SR402FLJ Low PIM
Cable Inner Conductor	Copper, Silver
Cable Outer Conductor	Copper, Tin
Dielectric Type	PTFE
Jacket Material	PVC LSZH
Jacket Diameter	0.163 in [4.14 mm]

**Connector 1**

Type	7/16 DIN Male
Configuration	Straight
Inner Conductor Material and Plating	Brass, Silver
Coupling Nut Material and Plating	Brass, Tri-Metal
Hex Size	1 1/4 inch
Body Material and Plating	Brass, Silver
Dielectric Type	PTFE

**Connector 2**

Type	7/16 DIN Male
Configuration	Straight
Inner Conductor Material and Plating	Brass, Silver
Coupling Nut Material and Plating	Brass, Tri-Metal
Hex Size	1 1/4 inch
Body Material and Plating	Brass, Silver
Dielectric Type	PTFE

**Compliance Certifications** (visit [www.Pasternack.com](http://www.Pasternack.com) for current document)

RoHS Compliant	Yes
----------------	-----

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [7/16 DIN Male to 7/16 DIN Male LSZH Jacketed Cable 200 CM Length Using SR402FLJ Low PIM Coax, RoHS PE3C2003-200CM](#)





7/16 DIN Male to 7/16 DIN Male LSZH Jacketed Cable  
200 CM Length Using SR402FLJ Low PIM Coax, RoHS

TECHNICAL DATA SHEET

PE3C2003-200CM

Notes:

- Values at +25 °C, sea level

7/16 DIN Male to 7/16 DIN Male LSZH Jacketed Cable 200 CM Length Using SR402FLJ Low PIM Coax, RoHS from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [7/16 DIN Male to 7/16 DIN Male LSZH Jacketed Cable 200 CM Length Using SR402FLJ Low PIM Coax, RoHS PE3C2003-200CM](http://www.pasternack.com/7-16-male-7-16-male-sr402flj-low-pim-cable-assembly-pe3c2003-200cm-p.aspx)


URL: <http://www.pasternack.com/7-16-male-7-16-male-sr402flj-low-pim-cable-assembly-pe3c2003-200cm-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

# PE3C2003-200CM CAD Drawing

7/16 DIN Male to 7/16 DIN Male LSZH Jacketed Cable 200 CM

Length Using SR402FLJ Low PIM Coax, RoHS



Part Number Configuration		How To Order		Part # Ext.	Length In Inches	Part # Ext.	Length In Centimeters		
PE3	zzz	yy	-	xx	uu				
00 - 99999 LF = RoHS Compliant < Blank > = Standard Note: LF applies only to RF cables				Examples PE3000LF-100 PE3000-100 PE3000LF-100CM PE3000-100CM				Custom Length	
				-12	12"	-25CM	25Cm		
				-24	24"	-50CM	50Cm		
				-36	36"	-75CM	75Cm		
				-48	48"	-100CM	100Cm		
				-60	60"	-125CM	125Cm		
				-XX	Custom Length	-XXCM	Custom Length		

NOTES:  
 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.  
 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.  
 3. DIMENSIONS ARE IN INCHES [mm].  
 4. LENGTH TOLERANCE IS ± 1.5% OR 3/8", WHICHEVER IS GREATER.

DWG TITLE  
**PE3C2003**

**(PE) PASTERNAK®**  
 THE ENGINEER'S RF SOURCE  
 Pasternack Enterprises, Inc.  
 P.O. Box 16759 | Irvine | CA | 92623  
 Phone: (949) 261-1920 | Fax: (949) 261-7451  
 Website: www.pasternack.com | E-Mail: sales@pasternack.com

FSCM NO. 53919	CAD FILE 062514	SCALE N/A	SIZE A	2233
----------------	-----------------	-----------	--------	------